



**ALLIANCE  
AGRICULTURE**

TRA: I-3  
Speed Rating: D

Alliance 388 is designed to meet the requirement of severe agricultural applications ranging from spreaders to special trailers (eg. for sugar cane production and implements). The directional tread pattern provides moderate traction as well as efficient selfcleaning. The tires large soil contact area, strong rounded lugs and low inflation pressure promises low ground pressure thus minimizing soil compaction and damage. Dense lug distribution around the tire enables smooth and efficient movement on roads.

**IMPLEMENT - 560/60R22.5 Steel Belted**

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load								
		SW inch	OD inch					Speed								
								Mixed application								
								Static mph	6 mph	16 mph	19 mph	25 mph	31 mph	37 mph	40 mph	43 mph
560/60R22.5 Steel Belted	AG 16.00	21.2	48.4	21.5	146.5	151D	15	9590	7500	6590	6280	5670	5050	4450	4170	3790
							22	12130	9480	8330	7960	7170	6370	5640	5270	4780
							29	14350	11220	9860	9410	8490	7540	6680	6240	5690
							35	15980	12500	10980	10490	9440	8400	7430	6950	6330
							41	17510	13690	12020	11490	10340	9190	8140	7610	6920
						156D	46	18360	14370	12610	12060	10850	9660	8530	7980	7250
							51	19310	15120	13270	12680	11420	10160	9000	8400	7650
							55	20280	15870	13930	13320	11990	10670	9440	8820	8030

**Note: For abovementioned size 151D is no longer active for production. Steel belt available in 156D only.**

1) When fitted on tractor steering wheels load capacity is 80% of free rolling and inflation pressure 20% higher. 2) For 10 km/h and stationary use inflation pressure raised 20% and 25% respectively.

