



ALLIANCE
AGRICULTURE

TRA: I-2
Speed Rating: D

Alliance 390 Heavy Duty steel belted flotation radial Implement tires belong to the Agri-Transport series combining the best of flotation characteristics with the best of radial construction characteristics to provide excellent performance both on and off road. The tires can be used for multiple machines in on/off-the-road applications. MPT tires can drive upto 100 km/h and are best suited for tough applications compared to the standard range.

HEAVY DUTY FLOTATION - 560/60R22.5

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load							
								Speed							
								Mixed Application							
		SW inch	OD inch					Static mph	6 mph	16 mph	19 mph	25 mph	31 mph	37 mph	40 mph
560/60R22.5	AG16.00	22.2	49.6	22.4	152.2	169D	12	10410	8140	7140	6830	6150	5470	4830	4520
							15	11820	9240	8110	7760	6990	6220	5490	5140
							22	15010	11750	10320	9860	8890	7890	6990	6530
							29	17750	13890	12190	11660	10490	9350	8270	7720
							36	20240	15830	13890	13270	11970	10650	9410	8800
							44	22510	17620	15480	14770	13320	11840	10470	9790
							51	24650	19290	16930	16180	14570	12960	11460	10710
							58	26680	20880	18320	17510	15760	14020	12410	11600
							65	28590	22380	19640	18780	16910	15040	13290	12430
							73	29010	22710	19930	19050	17150	15260	13490	12610
							87	29410	23020	20190	19310	17390	15480	13690	12790

