



ALLIANCE
CONSTRUCTION &
INDUSTRIAL

TRA: R-4
Speed Rating: D

Alliance 606 tire for Loaders and Dozers is a low section tire for light earthmoving equipment. The tire is an all steel radial tire with steel belted construction. The unique non-directional tread design suits on/off road services. High mileage, easy self cleaning, best traction, fuel saving and ride comfort are some of its advantages.

EM - 365/70R18

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load			
								Speed			
								Off-the road			
		Static mph	3 mph					6 mph	16 mph		
365/70R18	11 13	15.7	39.4	17.3	114.3	146A2	33	7870	5560	4920	4190
							36	8360	5910	5230	4430
							40	8820	6240	5510	4700
							44	9280	6550	5800	4940
							47	9740	6880	6090	5180
							51	10160	7170	6350	5400
							54	10580	7470	6610	5620
Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load			
								Speed			
								Hard Improved Surfaces			
		Static mph	3 mph					6 mph	16 mph		
365/70R18	11 13	15.7	39.4	17.3	114.3	146A2	39	8840	7120	6640	6150
							44	9410	7580	7060	6530
							48	9920	8000	7450	6900
							52	10430	8400	7830	7250
							57	10960	8820	8220	7610
							61	11420	9220	8580	7940
							65	11910	9590	8930	8270

Recommended rim in red

