



**ALLIANCE
EARTHMOVER &
MINING**

TRA: **G-2/L-2**
Speed Rating: **B**

Alliance 308 is a tire designed for rugged service on front-end loaders. Husky tread bars are sized and angled for maximum traction and specially contoured to resist tearing and chipping. The overlapping lugs ensure smooth rolling on any type of surface and the spacing between lugs provides self-cleaning properties. It is built with ozone and weather-resistant compounds and has a strong nylon construction.

LOADER DOZER - 15.5-25 L2,G2

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load			
		SW inch	OD inch					Speed			
								Off-the road			
								Static mph	3 mph	6 mph	16 mph
15.5-25 L2,G2	12SDC	15.5	50.3	22.2	146.5	8PR	25	12170	8600	7610	6460
						158A2	29	13160	9280	8220	6990
							33	14110	9970	8820	7500
						10PR	36	14990	10580	9370	7960
							40	15590	11000	9740	8290
						163A2	44	16400	11570	10250	8710
							47	17200	12150	10750	9130
						12PR	51	18280	12900	11420	9130
						168A2	54	19000	13430	11880	9500
							58	19750	13960	12350	9880
						14PR	62	20330	14350	12700	10800
						171A2	65	21030	14840	13140	11180
69	21690	15320	13560	11530							

For the above size 8PR,10PR and 14Pr is no longer active for production

