



**ALLIANCE  
EARTHMOVER &  
MINING**

Alliance 307 is a pattern developed for Grader-Loader applications. The design provides optimal traction and cut resistance and also enables the tire to have excellent self cleaning characteristics and long life.

TRA: **G-2/L-2**  
Speed Rating: **A8**

**Bias Ply Loader Grader L-2/G-2 - 14.00-24**

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load	
		SW inch	OD inch					Speed	
								Recommended Load Capacity (For Grader)	Recommended Load Capacity (For Loader/Dozer/TH)
								25 mph	6 mph
14.00-24	8.00TG	14.2	52.7	23.9	153.9	12PR	36	6780	NA
							62	NA	13890
Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load	
		SW inch	OD inch					Speed	
								Recommended Load Capacity (For Grader)	Recommended Load Capacity (For Loader/Dozer/TH)
								25 mph	6 mph
14.00-24	8.00TG	14.2	52.7	23.9	153.9	16PR	47	8050	NA
							80	NA	16090

