



**ALLIANCE
LAWN GARDEN & TURF**

TRA: **HF-1**
Speed Rating: **B**

Alliance 322 tread pattern provides extremely gentle operation of golf carts, turf equipment and lawn mowers. The high void to rubber ratio enables long tread life, large footprint, as well as low and uniform ground pressure. Low tread depth and unique shoulder design minimize turf damage on hills and during sharp turns. The large footprint allows more tread on the ground and keeps the machine/equipment from sinking in while crossing wet or soft ground. The 322 tread pattern also provides smooth operation on hard surfaces.

IMPLEMENT - 41X14.00-20 NHS

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load				
		SW inch	OD inch					Speed				
								Mixed application				
								Static mph	6 mph	9 mph	19 mph	31 mph
41X14.00-20	11	15.0	43.0	19.4	126.9	4PR	17	5420	3970	3310	2820	2510
						120B	22	6200	4520	3790	3220	2870
							25	6660	4870	4080	3460	3090
						6PR	28	7100	5180	4340	3680	3290
						127B	32	7720	5640	4720	3990	3570
							36	8330	6110	5090	4320	3860

Note: For abovementioned size 4 PR is no longer active for production.

