



**ALLIANCE
AGRICULTURE**

TRA: I-3
Speed Rating: C

Alliance 328 HS (High Speed Flotation I-328) is designed with good self-cleaning characteristics, which is suitable for on and off-the-road agricultural service on trailers and implements. The high load capacity and low inflation pressure of the tire results in high degree of agricultural soil protection, as well as low rolling resistance on both, on and off-road uses. The tire is available in heavy and regular duty versions of flotation tires. Its strong nylon construction and compounds ensure long life

IMPLEMENT - 500/50R17

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load							
		SW inch	OD inch					Speed							
								Free rolling							
								Static mph	6 mph	12 mph	19 mph	25 mph	31 mph	37 mph	40 mph
500/50R17	16	19.4	37.8	16.7	112.9	145D	15	6550	5120	4500	4300	3860	3440	3040	2840
							22	8310	6500	5710	5470	4920	4370	3860	3620
							29	9790	7650	6720	6420	5780	5160	4560	4260
							36	11160	8730	7670	7320	6590	5860	5180	4850
							46	12940	10120	8890	8490	7650	6810	6020	5620
							52	13850	10830	9500	9080	8180	7280	6440	6020
							58	14710	11510	10100	9660	8690	7740	6830	6390

For stationary service (0 km/h) and speed upto 10km/h inflation pressure must be increased by 20% Overall width(+/- 2%) Overall Diameter(+/-1.5%) Static Radius(+/-2%) Circumference(+/-2.5%)

