



ALLIANCE
FORESTRY

TRA: **LS-2**
Speed Rating: **A8**

FORESTAR 346 Forestry Flotation is a bias belted tire with steel reinforcement for high puncture resistance. The tire has a special tread compound and has very thick sidewalls and under tread. The reinforced bead of the tire provides exceptional performance. Its lower lug angle provides excellent grip and exhibits self cleaning characteristics due to its wide inter-lug space which is vital in logging applications. The close spacing of the lugs in the centre of the tire reduces rolling resistance on hard surfaces. The 346 is designed to handle various terrains without chains/ bogie trucks.

FORESTRY - 600/65-34

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load						
								Speed						
								Recommended load, kg (lbs)						
								Drive wheel					Forestry use	
		SW inch	OD inch					Static mph	6 mph	12 mph	19 mph	25 mph	6*HT mph	6*LT mph
600/65-34	DW20A	23.6	64.6	30.0	194.0	14PR	23	16490	10030	8820	7670	7170	7170	8820
							26	17700	10780	9460	8220	7690	7690	9460
						157A8 164A2	29	18810	11440	10050	8750	8180	8180	10050
							32	19890	12100	10630	9240	8640	8640	10630
							35	20920	12740	11180	9720	9090	9090	11180
						16PR	58	21300	12960	11400	9900	9260	9260	11400
						160A8 167A2	65	22820	13890	12210	10630	9920	9920	12020

