



ALLIANCE  
AGRICULTURE  
  
TRA: **R-1W**  
Speed Rating: **D**

The high speed rated AGRI STAR II comes with a Stratified Layer technology (SLT) - a unique combination of two layers: The top layer with a single angle profile and bottom layer with a multi-angle profile. After 40% wear of the tire, bottom layer of the lug comes in contact with the ground which leads to increased contact area at the central portion. This leads to better roadability and performance of the tire. The increased amount of rubber volume in AGRI STAR II enhances its stiffness that results in better wear resistance.

Tractor R-1W - 320/85R36

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load							
								Speed							
		Tractor Applications													
									Static mph	6 mph	16 mph	19 mph	25 mph	31 mph	40 mph
320/85R36	W11 X 36	13.1	57.5	26.8	172.0	128D	12	5830	3800	3010	2920	2780	2660	2540	
							17	7610	4960	3920	3800	3620	3470	3310	
							20	8370	5460	4310	4180	3980	3820	3640	
							23	9130	5950	4700	4560	4350	4170	3970	
Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load							
								Speed							
		TRACTOR APPLICATION													
									Static mph	6 mph	12 mph	19 mph	25 mph	31 mph	37 mph
320/85R36	W11 X 36	13.1	57.5	27.1	178.1	147D	12	5180	4170	3860	3570	3260	2980	2690	2540
							17	6750	5420	5030	4670	4280	3880	3510	3310
							29	9000	7230	6700	6220	5690	5160	4670	4410
							41	10340	8310	7720	7140	6550	5930	5380	5070
							52	11930	9590	8890	8250	7540	6830	6200	5840
							64	13820	11110	10300	9570	8750	7940	7190	6780

Overall Width (+/- 2%) Overall Diameter (+/- 1.5%) Static radius (+/- 2%) Circumference (+/- 2.5%)

