



ALLIANCE
AGRICULTURE

TRA: **R-1**
Speed Rating: **A8**

Alliance 768 Value Plus is specially designed to meet the unique demands of pivot irrigation. Built with strong nylon carcass construction which enhances its ability to carry continuous heavy loads. Designed with low lug angles and rounded shoulders for optimal traction and maximum crop protection. The presence of special ozone compound protects it from cracking ensuring excellent durability.

TRACTOR - 11.2-24

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load											
								Speed											
								Tractor Application											
		Static mph	3 mph					6 mph	9 mph	12 mph	16 mph	19 mph	22 mph	25 mph	28 mph	31 mph			
11.2-24	W10X24, W9X24	11.0	43.3	19.4	128.0	6 110A8	12	3350	2470	2180	1940	1790	1610	1570	1500	1460	1390	1320	
							17	4560	3150	2780	2490	2270	2050	1980	1920	1850	1790	1680	
							20	4960	3440	3040	2710	2490	2250	2160	2090	2030	1940	1850	
							23	5030	3700	3290	2930	2690	2430	2340	2250	2180	2090	1980	
							26	5730	3970	3510	3130	2870	2600	2490	2400	2340	2250	2120	

