



GALAXY  
AGRICULTURE  
  
TRA: **R-1**  
Speed Rating: **A6**

EarthPRO 348 has a modern curved design developed mainly for the heavy duty agricultural segment. The multi angled lug design enables smooth riding on the road and displays excellent traction during field operations. The special stepped surfaces between lugs enable the tire to have excellent self cleaning characteristics. The special tread compound provides protection against cuts and cracks.

TRACTOR DIAGONAL - 16.9-30

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load							
								Speed							
								Tractor application							
		SW inch	OD inch					Static mph	6 mph	9 mph	12 mph	16 mph	19 mph	22 mph	25 mph
16.9-30	W15L X 30	16.9	58.5	26.3	172.0	12  144A6	12	7500	4560	4230	3920	3480	3260	3110	2930
	DW15A X 30						17	9480	5780	5360	4940	4410	4120	3920	3700
	W14L X 30						23	11200	6810	6330	5840	5200	4870	4630	4390
	DW14A X 30						29	12790	7780	7230	6660	5950	5560	5270	5000
	X 30						35	14200	8640	8030	7410	6610	6170	5860	5560

