



GALAXY
AGRICULTURE

TRA: I-3
Speed Rating: A8

Galaxy Flotation is specially constructed to carry heavy loads and is used in harsh conditions. The high load carrying capacity and low inflation pressure of the tire results in high degree of agricultural soil protection, as well as low rolling resistance during both, on and off-road usage. The unique tread pattern ensures excellent self-cleaning. The high rubber to void ratio ensures large footprint and hence lower pressure on soil resulting in maximum soil and plant protection. The wide center block and low lug angles provide tread stability and uniform wear. The strong nylon construction and compounds ensure long tire life.

Agri Transport - 550/45-22.5

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load									
								Speed									
		Drive Wheel						Free rolling									
SW inch	OD inch	6 mph	16 mph	19 mph	25 mph	31 mph	6 mph	16 mph	19 mph	25 mph	31 mph						
550/45-22.5	AG16.00 X 22.5	21.7	42.1	18.7	125.0	16	12	4560	3880	3660	3260	2930	6500	5530	5200	4650	4190
						159A8(156B)	23	6860	5820	5490	4890	4410	9740	8290	7800	6970	6260
						147A8(144B)	35	8660	7360	6950	6200	5580	12350	10490	9880	8820	7940
						⌚	41	9500	8070	7580	6780	6110	13510	11490	10800	9650	8690

