



**GALAXY
 AGRICULTURE**

TRA:
 Speed Rating: **A8**

The Galaxy Super Soil Softee is designed for use in spreading liquid fertilizers. The frame provides very low footprint pressure. It is ideal for machinery and equipment used in wet soil conditions. Radial construction provides superior cut and puncture resistance.

Agri Transport - 750/60R26

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load													
								Speed													
		SW inch	OD inch					Drive Wheel					Free Rolling								
								Static mph	6 mph	16 mph	19 mph	22 mph	25 mph	31 mph	Static mph	6 mph	16 mph	19 mph	22 mph	25 mph	31 mph
750/60R26	DW25BX26	29.5	62.6	28.1	185.9	175A8 [⊕] ⊕ 175A8 [⊖] ⊖	12	9850	5860	4990	4930	4400	4190	3770	9790	8310	7060	6980	6230	5930	5340
							23	14780	8800	7480	7390	6600	6290	5660	14700	12480	10600	10470	9350	8910	8020
							35	18730	11160	9480	9370	8370	7970	7170	18630	15810	13430	13270	11850	11290	10160
							46	22160	13210	11220	11090	9900	9430	8490	22040	18700	15900	15710	14030	13360	12020
							58	25260	15060	12790	12640	11290	10750	9670	25100	21300	18100	17890	15970	15210	13690

E-Marking Number:

