



ALLIANCE
FORESTRY

TRA: **LS-2**
Speed Rating: **A8**

Alliance 643 Forestar III is engineered for ultimate track compatibility. Even without tracks it provides exceptional grip under critical forestry conditions. With improved heavier nylon steel belted construction and reinforced hexagonal bead technology ,643 Forestar III ensures excellent puncture resistance, high load carrying capacity and prevents rim slippage. The unique tread pattern with wider shoulder lugs and horizontal grooves enhances track compatibility and overall lateral stability. Excellent self-cleaning , superior grip and resilient construction makes 643 Forestar III the perfect solution for all your forestry needs.

Forwarder & Harvester - 750/55-26.5

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load				
								Speed				
								Forestry Use	Road Service			
		SW inch	OD inch						Static mph	12 mph	19 mph	25 mph
750/55-26.5	AG24.00 X 26.5	29.5	58.7	27.1	179.7	24 182A8 182A2	51	13670	36910	16810	14630	13670
							58	14770	39880	18170	15810	14770
							65	15830	42740	19470	16940	15830
							73	16840	45480	20720	18020	16840
							80	17810	48100	21910	19060	17810
							87	18740	50600	23050	20050	18740

*LT-Low Torque(Forwarder Application) *HT-High Torque(Skidder Application) At stationery service inflation pressure must be increased by 0.3Bar Maximum
Inflation pressure for Tracks - 6Bar or 87psi

