



ALLIANCE
EARTHMOVER &
MINING

TRA: E-2/L-2/G-2
Speed Rating: B

Alliance 600 is a modern wide base, all steel radial tire for all types of earthmoving equipments. Its unique tread design and sophisticated construction ensure superior performance coupled with smoother rides and higher productivity

LOADER DOZER - 15.5R25 L2

| Size | Rim | Unloaded Dimension | | Loaded Static radius inch | Rolling Circumference inch | Load Index PR Symbols | Inflation Pressure psi | Recommended Load | | | |
|------------|-----------|--------------------|-------|---------------------------|----------------------------|-----------------------|------------------------|------------------------|--------|-------|-------|
| | | | | | | | | Speed | | | |
| | | | | | | | | Off-the road | | | |
| | | Static mph | 3 mph | | | | | 6 mph | 16 mph | | |
| 15.5R25 L2 | 12.00/1.3 | 15.4 | 50.2 | 22.7 | 148.0 | * 169A2 | 51 | 17680 | 12480 | 11050 | 9390 |
| | | | | | | | 58 | 19090 | 13470 | 11930 | 10140 |
| | | | | | | | 65 | 20460 | 14440 | 12790 | 10870 |
| Size | Rim | Unloaded Dimension | | Loaded Static radius inch | Rolling Circumference inch | Load Index PR Symbols | Inflation Pressure psi | Recommended Load | | | |
| | | | | | | | | Speed | | | |
| | | | | | | | | Hard Improved Surfaces | | | |
| | | Static mph | 3 mph | | | | | 6 mph | 16 mph | | |
| 15.5R25 L2 | 12.00/1.3 | 15.4 | 50.2 | 22.7 | 148.0 | * 169A2 | 61 | 19890 | 16010 | 14900 | 13800 |
| | | | | | | 70 | 21470 | 17280 | 16090 | 14900 | |
| | | | | | | 78 | 23020 | 18540 | 17260 | 15980 | |

Speed:10km/h (5mph); Distance:up to 76km (250 miles) - one way

