



ALLIANCE  
EARTHMOVER &  
MINING

TRA: E-3/G-3/L-3  
Speed Rating: B

Alliance 650 has a well proven tread pattern that enables its use for a wide range of applications on different kinds of mobile construction equipments. Its all steel construction ensures higher productivity with lower downtime.

LOADER DOZER - 15.5R25 L-3/E3

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load			
								Speed			
								Off-the road			
		Static mph	3 mph					6 mph	16 mph		
15.5R25 L-3/E3	12.00/1.3	15.6	50.3	22.2	151.9	** 176A2	36	15390	10870	9610	8180
							44	17110	12080	10690	9080
							58	20240	14310	12660	10760
							73	23060	16290	14420	12260
							83	25040	17680	15650	13320
Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load			
								Speed			
								Hard Improved Surfaces			
		Static mph	3 mph					6 mph	16 mph		
15.5R25 L-3/E3	12.00/1.3	15.6	50.3	22.2	151.9	** 176A2	44	17310	13930	12990	12020
							52	19250	15500	14440	13360
							70	22770	18340	17090	15830
							87	25950	20900	19470	18030
							100	28180	22710	21140	19580

Grader application

