



GALAXY
MATERIAL HANDLING

TRA:
Speed Rating:

Lifter SDS is specially designed keeping in mind the needs of forklifts performing low-intensity operations. Its robust construction is made up of high performing rubber compounds, ensuring excellent durability. The unique tread design with continuous centre lug ensures traction and safeguards the tread against wear. With affordable prices and unmatched efficiency Lifter SDS redefines better value

FORKLIFT - 250-15

SIZE	RIM SIZE	O.D. mm	S.W. mm	60J mm	Rim Type	Rad / Bia / Sol	LOAD CAPACITY lbs					
250-15	7.00-15	716	230	62	Quick Heel	Solid - Resilient	STATIC	COUNTER BALANCE LIFT TRUCKS		OTHER VEHICLES		
							0kmph	Load Wheels 25 kmph	Steer Whels 25 kmph	Load Wheels 6 kmph	Steer Wheels 10 kmph	Load Wheels 25 kmph
							12147.4562	10460.9219	8046.863	10460.9219	9501.9122	8046.863
	7.00-15	716	230	62	Standard Heel	Solid - Resilient	STATIC	COUNTER BALANCE LIFT TRUCKS		OTHER VEHICLES		
							0kmph	Load Wheels 25 kmph	Steer Wheels 25 kmph	6 kmph	10 kmph	25 kmph
							12144	10458	8045	10458	9499	8045

