



ALLIANCE  
EARTHMOVER &  
MINING

TRA: E-3/L-3/G-3  
Speed Rating: B

Alliance 310 pattern is constructed for heavy-duty jobs. The tough tread design ensures high mileage even on the most abrasive surfaces. This is a directional tire built with weather and ozone-resistant compounds. Its nylon construction gives it long life.

TRANSPORT - 16.00-25 E-3

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load								
		SW inch	OD inch					Speed								
								9 mph	12 mph	16 mph	19 mph	22 mph	25 mph	28 mph	31 mph	34 mph
16.00-25 E-3	11.25	17.0	58.8	27.0	175.6	24PR	58	13400	13160	12920	12700	12460	12320	12210	11970	11620
							170B	62	13870	13630	13380	13140	12880	12770	12630	12390
						65		14350	14090	13820	13580	13320	13180	13070	12810	12430
								69	14820	14550	14290	14020	13760	13630	13490	13230
						28PR	73	15230	14970	14680	14420	14150	14020	13870	13600	13180
							174B	76	15680	15410	15120	14840	14550	14420	14290	14000
						80		16120	15830	15540	15260	14970	14840	14680	14400	13960
								83	16540	16250	15960	15650	15370	15210	15060	14770
						32PR	87	17220	16910	16600	16290	15980	15830	15680	15370	14900
						177B	91	17620	17280	16980	16670	16360	16180	16030	15720	15260
							94	18030	17700	17370	17060	16730	16580	16420	16090	15610

Note: For above mentioned size 24 PR is no longer active for production.

