



ALLIANCE
AGRICULTURE

TRA:
Speed Rating: **F**

392 is an all steel tire with an F speed rating for high speed agri-transport operations. High load carrying capacity, protection against cuts & punctures, low soil compaction and low rolling resistance are some of its key features. It is suitable for heavy duty applications. Its unique tread design ensures high traction in all terrains. It is suitable for sandy and soft soil operations.

Agri Transport - 24R20.5

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load									
								Speed									
								MIXED APPLICATION									
		SW inch	OD inch					Static mph	6 mph	16 mph	19 mph	25 mph	31 mph	37 mph	40 mph	43 mph	50 mph
24R20.5	18.00X20.5	23.6	54.0	24.4	165.7	176F	17	15210	10950	8210	7610	7000	6810	6690	6530	6390	6090
							23	18020	12980	9730	9010	8290	8070	7930	7740	7570	7210
							35	22870	16470	12350	11440	10520	10250	10060	9830	9610	9150
							46	27060	19480	14610	13530	12450	12120	11910	11630	11370	10830
							58	30870	22220	16670	15430	14200	13830	13580	13260	12960	12350
							87	39130	28180	21130	19570	18000	17530	17220	16810	16440	15650

