



ALLIANCE  
AGRICULTURE  
  
TRA: **R-1W**  
Speed Rating: **D**

AGRISTAR 375 VF is ideal for applications on combine harvesters. The tread pattern and lugs are designed to enable a comfortable and smooth ride on hard surfaces, combined with high traction and excellent self cleaning abilities off-road. Durable and elastic sidewalls contribute to a long tire life. A special stubble guard tread rubber compound contributes to long and efficient work on harvesters.

Harvester - VF 800/65R32

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load						
								Speed						
								Not high and sustained torque; Road transport					CFO	
		SW inch	OD inch					6 mph	9 mph	12 mph	37 mph	43 mph	9 mph	19 mph
VF 800/65R32	DW27 X 32	31.5	73.0	31.8	217.8	181D	12	11510	10750	10750	10750	9790	16660	13970
							15	12880	12020	12020	12020	10940	18620	15620
							17	14180	13230	13230	13230	12040	20500	17200
							23	17240	16090	16090	16090	14640	24950	20920
							29	19490	18190	18190	18190	16560	28190	23650

From 15Kmph-60Kmph, the Load will remain same for the Respective Inflation Pressure. For Non-Cyclic Application only.

