



**ALLIANCE  
AGRICULTURE**

TRA:  
Speed Rating: **D**

Alliance 590 is a heavy duty radial flotation tire designed specifically to suit the needs of agriculture and construction applications. A robust steel belted construction with non-directional tread design and superior cut and chip resistant compound enables it to handle heavy Loads and operate both in farms as well as on/off road applications.

**Agri Transport - 600/55R26.5**



Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load								
								Speed								
								Mixed Application								
		Static mph	6 mph					12 mph	19 mph	25 mph	31 mph	37 mph	40 mph	43 mph		
600/55R26.5	AG20.00 X 26.5	24.1	52.5	24.1	160.3	173D	17	11050	8650	7930	7260	6540	5820	5140	4810	4370
							23	13440	10520	9640	8820	7950	7070	6250	5840	5320
							35	16990	13290	12190	11150	10040	8940	7900	7390	6720
							46	21550	16870	15460	14150	12740	11340	10030	9370	8530
							58	26110	20440	18740	17150	15440	13740	12150	11350	10330
							73	29410	23020	21100	19310	17390	15470	13680	12790	11640
							87	32960	25790	23650	21640	19490	17340	15330	14330	13040
Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load								
								Speed								
								Mixed Application								
		Static mph	6 mph					12 mph	19 mph	25 mph	31 mph	40 mph	43 mph			
600/55R26.5	AG20.00 X 26.5	24.1	52.5	23.7	157.6	165D	12	8620	6750	6200	5670	5090	4540	3750	3420	
							17	11050	8640	7940	7250	6530	5820	4810	4370	
							23	13450	10520	9630	8820	7940	7080	5840	5310	
							29	14710	11510	10560	9660	8690	7740	6390	5820	
							35	17000	13290	12190	11160	10050	8930	7390	6720	
							41	19640	15390	14090	12900	11620	10340	8540	7780	
							46	21560	16870	15450	14150	12740	11330	9370	8530	
							52	23460	18360	16820	15390	13870	12350	10200	9280	
58	26130	20440	18740	17150	15430	13740	11350	10340								
Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load								
								Speed								
								Mixed Application								
		Static mph	6 mph					12 mph	19 mph	25 mph	31 mph	40 mph	43 mph			
600/55R26.5	AG20.00 X 26.5	24.1	52.5	24.1	160.2	178D	17	11050	8640	7940	7250	6530	5820	4810	4370	
							23	13450	10520	9630	8820	7940	7080	5840	5310	
							29	14710	11510	10560	9660	8690	7740	6390	5820	
							35	17000	13290	12190	11160	10050	8930	7390	6720	
							41	19640	15390	14090	12900	11620	10340	8540	7780	
							46	21560	16870	15450	14150	12740	11330	9370	8530	
							52	23460	18360	16820	15390	13870	12350	10200	9280	
							58	26130	20440	18740	17150	15430	13740	11350	10340	
							73	29410	23020	21100	19310	17390	15480	12790	11640	
							87	32960	25790	23660	21650	19490	17350	14330	13050	
							102	38030	29760	27290	24980	22490	20020	16540	15060	

