



PRIMEX
**EARTHMOVER &
MINING**

TRA: **HF-1**
Speed Rating: **B**

Primex Geomaster is designed specifically for the exploration and geophysics industries. The large area of this tire provides superior buoyancy and reduces ground disturbance and soil compaction

Geoseismic Vehicle - 66X44.00-25NHS



Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load	
								Speed	
		SEISMIC VEHICLES						9 mph	31 mph
		SW inch	OD inch						
66X44.00-25NHS	36HFX25	43.3	67.8	29.6	190.7	6 151B 160A3	15	9920	7610

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load	
								Speed	
		SEISMIC VEHICLES						9 mph	31 mph
		SW inch	OD inch						
66X44.00-25	36HFX25	43.3	67.8	29.6	190.7	20 176B 185A3	49	20390	15650

Size	Rim	Unloaded Dimension		Loaded Static radius inch	Rolling Circumference inch	Load Index PR Symbols	Inflation Pressure psi	Recommended Load	
								Speed	
		SEISMIC VEHICLES						9 mph	31 mph
		SW inch	OD inch						
66X44.00-25	36HFX25	43.3	67.8	29.6	190.7	26 181B 191A3	65	24030	18190