

FLOTATION TIRE FAMILY
ADVANCED
DESIGN.
SUPERIOR
TECHNOLOGY.

AGRIFLEX+ 389 VF FLOTATION HF2

OEM FITMENT

The Alliance Agriflex+ 389 VF-imp provides the best possible solution for soil protection on large and heavy implements such as towed spreaders, grain wagons, liquid manure tankers and other agricultural trailers.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
38950009	VF500/50R17		150	NA	TL	27	16	36.5	19.8	109.7	15.7	7380	46	40
38950102	VF500/60R22.5		157	NA	TL	27	16	46.1	19.8	139	20	9910	46	40
38900011	VF 560/60R22.5		163D		TL	29	AG16.00	49.2	22.2	146.1	21.2	10750	41	40
38900018	VF 600/55R26.5		167D		TL	33	AG20.00	53.1	24.8	160	23.1	12020	41	40
38900025	VF 650/55R26.5		171D		TL	33	AG20.00	54.5	25.6	164.3	23.6	13560	41	40
38900026	VF 650/60R26.5		174D		TL	33	AG20.00	57.2	26.2	172.8	24.5	14760	41	40
38900028	VF 710/50R26.5		173D		TL	33	AG24.00	55.1	28.8	168.1	23.7	14330	41	40
38900030	VF 750/45R26.5		172D		TL	33	AG24.00	53.5	29.7	160.9	23.2	13890	41	40
38900045	VF 750/60R30.5		183D		TL	33	AG24.00	66.1	30.7	199.6	28.4	19290	41	40
38900065	VF 800/60R32		188D		TL	33	DW27B	70.9	31.5	215.2	30.6	22030	41	40

398 MPT FLOTATION R-4

The Alliance 398 MPT is a definitive solution for modern off road and on road vehicles. It enhances the productivity and reduces cycles time by moving effortlessly between the field and the road. Its high load carrying and high speed capacity saves both time and money.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
39800025	445/65R22.5		160J		TL	38	W14L	45.9	17.9	141.4	21	9910	87	62
39800060	445/70R24		151J		TL	45	W14L	48.9	17.9	149	22.6	7600	65	62
39800075	495/70R24		155J		TL	47	W16L	51.6	20.2	151.5	23.7	8540	65	62
39810020	600/50R22.5		164J		TL	38	AG20.00	46.1	24.4	141.9	21.3	11010	94	62

380 STEEL BELTED FLOTATION RADIAL

OEM FITMENT

The Alliance 380 is a premium non-directional radial with steel belts for durability. The flat profile and thick lug design minimizes compaction.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
38022953	550/45R22.5		151E		TL	31	AG16.00	42.1	21.7	125.2	19.3	7600	58	43
38026010	560/45R22.5		152D		TL	31	AG16.00	42.3	21.4	128.5	19.1	7850	58	40
38022922	560/60R22.5		161E		TL	29	AG16.00	49	21.8	149.6	22	10200	58	43
38025001	560/60R22.5		172D		TL	29	AG16.00	49.2	21.7	150.6	21.8	13880	73	40
38032358	580/65R22.5		166D		TL	29	AG16.00	51.9	23	160.3	22.8	11680	58	40
38022960	600/50R22.5		164J		TL	32	AG20.00	46.1	23.9	142.4	21.2	11010	94	62
38022956	600/50R22.5		159D		TL	31	AG20.00	46.1	24.05	139.33	20.78	9640	58	40
38022999	600/55R22.5		162E		TL	29	AG20.00	49	23.6	144.5	22.1	10500	58	43
38028020	620/40R22.5		155D		TL	33	AG20.00	42.2	24.4	125.2	19.2	8550	58	40
38028058	620/40R22.5		171A8		TL	33	AG20.00	42.2	24.4	125.2	19.2	13600	102	25
38022975	650/50R22.5		163E		TL	33	AG20.00	48.6	25.6	142.9	21.8	10700	58	43
38040800	710/45R22.5		165D		TL	33	AG24.00	47.6	28.6	145	21	11350	58	40
38022961	750/45R22.5		166E		TL	33	AG24.00	49	29.5	144.5	22.1	11700	58	43
38023010	750/45R22.5		177D		TL	33	AG24.00	49.2	29.3	144.5	21.9	16100	73	40
38030050	600/55R26.5		165E		TL	33	AG20.00	53.1	24.6	162.8	23.9	11350	58	43
38030001	600/55R26.5		177D		TL	33	AG20.00	53.1	24.6	162.8	23.9	16080	73	43
38030110	650/55R26.5		178D		TL	33	AG20.00	53.8	25.2	163.4	24.2	16520	73	40
38031010	650/55R26.5		167E		TL	33	AG20.00	53.5	25.4	164.4	24.3	12000	58	43
38030522	650/60R26.5		173D		TL	33	AG20.00	57.1	26	168.5	25.8	14320	58	40

CONTINUED ON NEXT PAGE

380 STEEL BELTED FLOTATION RADIAL (CONTINUED)

PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
38030545	650/60R26.5		181D		TL	33	AG20.00	57.1	26	167.7	25.8	18200	73	40
38030750	650/65R26.5		174D		TL	33	AG20.00	59.8	26.1	180.7	26.9	14770	58	40
38030740	650/65R26.5		181D		TL	33	AG20.00	59.9	26.1	184.1	27.1	18170	73	40
38041001	710/50R26.5		170D		TL	33	AG24.00	55.1	28.8	168.9	24.8	13220	58	40
38041005	710/50R26.5		178D		TL	33	AG24.00	55.2	28.7	168.8	24.8	16500	73	40
38022992	750/45R26.5		170E		TL	33	AG24.00	53.5	29.1	162.9	24.3	13220	58	43
38040751	650/65R30.5		176D		TL	33	AG20.00	64	26.8	187.8	28.6	15640	58	40
38040790	650/65R30.5		181D		TL	33	AG20.00	64.1	26.6	197	29.2	18170	73	40
38060001	750/60R30.5		181D		TL	33	AG24.00	66.1	30.2	201.3	29.7	18200	58	40
38060008	800/60R32		185D		TL	33	DW27A	70.9	31.7	212.9	32	20370	58	40

390 STEEL BELTED AGRI-TRANSPORT FLOTATION RADIAL

OEM FITMENT

The Alliance 390 is the completely original Agri-Transport tire that set the standard for flotation—the tire the competition strives to duplicate. This steel-belted, high-speed tire is sought after by OEMs and in the replacement market for a wide range of on-road and off-road applications.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
39000102	24R20.5		176F		TL	29	AG16.00	54	23.8	165.6	24.4	15640	87	50
39020700	560/45R22.5		152D		TL	22	AG16.00	42.4	21.5	133.5	19	7820	58	40
39021040	500/45R22.5 AS		154F		TL	25	AG16.00	40.4	20	124.3	18.6	8250	87	50
39021100	500/60R22.5		155D		TL	22	16.00DC	46.5	20.1	142.4	20.8	8540	58	40
39021250	560/60R22.5		164D		TL	22	AG16.00	49.3	22.5	144.5	22	11010	58	40
39021292	560/60R22.5		170D		TL	22	AG16.00	49.7	22.2	151.3	22.1	13220	73	40
39021310	560/60R22.5 AS		170D		TL	22	AG16.00	49.3	21.9	150.9	22	13220	73	40
39021285	580/65R22.5		166D		TL	24	AG16.00	51.7	22.9	156.9	22.9	11670	58	40
39022808	600/50R22.5		159E		TL	31	20.00DC	46.1	23	136.6	20.9	9640	58	43
39022822	600/50R22.5 AS		166F		TL	31	20.00DC	46.5	23	138.2	21.2	11700	87	50
39023150	600/50R22.5		174A8		TL	31	20.00DC	46	23.8	135.8	20.8	14800	94	25
39005728	620/75R26	23.1R26	174D		TL	34	DW20B	62.6	24.4	185.9	27.8	14760	58	40
39005725	710/65R26		185D		TL	35	DW25	61.8	28.7	188.3	27.4	20370	73	40
39005710	710/65R26		176D		TL	35	DW25	60.8	28	178.3	27.2	15640	58	40
39005731	28LR26	750/65R26	176A8/173B		TL	35	DW25	60.7	28.6	178	27.1	14300	41	30
39021300	600/55R26.5		165D		TL	31	AG20.00	53.3	24.6	162.2	24.1	11340	58	40
39021315	600/55R26.5		177D		TL	31	AG20.00	53.1	24.6	162.2	24	16080	73	40
39030125	650/55R26.5		170D		TL	31	20.00DC	54.9	26	161.8	24.8	13220	58	40
39021600	650/55R26.5		178D		TL	31	20.00DC	54.9	26.2	162.2	24.8	16500	73	40
39022112	750/60R30.5		181D		TL	33	24.00DC	65.9	30.7	194.9	29.8	18170	58	40
39022135	750/60R30.5		190D		TL	33	24.00DC	66.3	30.3	201.8	29.6	23350	73	40
39022334	800/45R26.5		177D		TL	33	28.00DC	54.7	31.9	161.4	24.7	16080	58	40
39022521	710/50R26.5		172D		TL	33	24.00DC	54.7	28.7	167.3	24.7	13900	58	40
39022524	710/50R26.5		180D		TL	33	24.00DC	55	28.9	167.3	24.6	17620	73	40
39022620	600/60R30.5		173D		TL	33	20.00DC	59.3	25	175.6	26.9	14320	58	40
39022632	600/60R30.5		179D		TL	33	20.00DC	59.4	24.8	181.9	27	17070	73	40
39022775	710/50R30.5		176D		TL	33	24.00DC	58.9	28.6	174.4	26.8	15640	58	40
39022790	710/50R30.5		184D		TL	33	24.00DC	59.1	28.5	180.2	26.6	19820	73	40
39030277	850/50R30.5		182D		TL	34	28.00DC	70.9	31.5	208.3	31.7	19820	58	40
39022456	30.5LR32		181B		TL	39	DW27A	70.9	31.1	207.9	31.7	18200	44	30
39022661	800/60R32		184D/181E		TL	39	DW27A	70.9	31.3	209.8	32.1	19800	58	40

885 STEEL BELTED FLOTATION RADIAL IMPLEMENT

OEM FITMENT

The Alliance 885 is the new generation in steel-belted radial flotation tires engineered for all applications. Strong bead bundle, extra-thick reinforced sidewall and a high turn-up plies ensure excellent stability and protection against external damages.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
88500003	560/45R22.5		152D		TL	25	AG16.00	41.7	21.4	128.3	18.8	7850	58	40
88500015	560/60R22.5		164D		TL	25	AG16.00	48.4	21.9	142.5	21.8	11000	58	40
88500502	580/65R22.5		166D		TL	25	AG16.00	51.8	22.6	159.1	22.8	11700	58	40
88500582	600/50R22.5		159D		TL	26	AG20.00	46.1	23.9	136.6	20.9	9650	58	40
88500612	650/50R22.5		163D		TL	25	AG20.00	48.6	25.6	142.9	21.8	10700	58	40
88500622	710/45R22.5		165D		TL	30	AG24.00	47.6	28.5	144.7	21.1	11400	58	40
88500588	600/55R26.5		165D		TL	33	AG20.00	53	24.6	156.6	24	11340	58	40
88500620	650/55R26.5		170D		TL	33	AG20.00	54.3	25.5	160.6	24.8	13200	58	40
88500621	650/65R26.5		174D		TL	33	AG20.00	59.8	25.4	180.3	26.4	14760	58	40
88500640	710/50R26.5		170D		TL	33	AG24.00	55.1	28.8	168.9	24.8	13200	58	40
88500670	750/45R26.5		170D		TL	33	AG24.00	53.5	29.1	162.9	24.3	13200	58	40
88500600	800/45R26.5		174D	174D	TL	34	28	54.72	31.49	165.98	24.52	14760	58	40
88500645	710/50R30.5		173D	173D	TL	34	24	58.7	28.9	179.5	26.7	14320	58	40
88500710	750/60R30.5		181D		TL	33	AG24.00	66.1	30.2	201.3	29.7	18200	58	40

882 STEEL BELTED AGRI-TRANSPORT FLOTATION RADIAL

The Alliance 882 has shoulder lugs provide better grip in muddy fields as well as in other soil conditions. Strong bead bundle and high turn-up plies ensure excellent stability and protection against external damages on and off road. (TUBELESS - STEEL BELTED)



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
88200010	500/50R17		149D/146E		TL	19	AG16.00	36.69	19.8	111.53	16.1	7160	73	40
88200005	560/45R22.5		152D		TL	23	AG16.00	49	22.2	143.7	21.9	11000	58	40
88200050	580/65R22.5		166D		TL	24	AG16.00	52.2	22.6	158.7	23.1	11680	58	40
88200020	385/65R22.5		164D		TL	16	AG11.75	42.3	15.3	126.2	19.4	9520	100	40

381 STEEL BELTED FLOTATION RADIAL

The Alliance 381 is a steel belted radial flotation tire that has been developed to serve the needs of specific niche applications on sensitive surfaces like grasslands, which require optimized soil and plant protection. The unique rib type pattern, together with rounded shoulders and more aggressive lugs, enables maximum possible tires footprint and lowest possible ground pressure. The shoulder lugs, with excellent self cleaning capabilities, enable strong grip, thus preventing any excessive tire slippage and any consequent damage to the surface.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
38100005	500/50R17		146D		TL	18	AG16.00	37.4	19.4	113	16.6	6600	58	40
38100006	500/50R17	SB	146D		TL	18	AG16	37.4	19.4	113	16.6	6600	58	40
38110060	500/45R20		157A8		TL	18	DW16	37.7	19.8	113.3	16.2	9090	58	30
38100100	560/45R22.5	SB	146D		TL	23	AG16.00	42.5	21.3	129.7	19.1	6600	46	40
38100135	560/45R22.5		146D		TL	23	AG16.00	42.5	21.3	129.7	19.1	6600	46	40
38100150	560/45R22.5		146D		TL	23	AG16.00	42.5	21.3	129.7	19.1	6600	46	40
38102600	620/40R22.5		148D		TL	23	AG20.00	42.5	24.1	129.7	19.1	6950	46	40
38102620	620/40R22.5		154D		TL	23	AG20.00	42.5	24.1	129.7	19.1	8250	58	40
38102618	620/50R22.5		161D		TL	24	AG20.00	46.1	23.6	141.8	20.5	10200	58	40
38100810	710/40R22.5	SB	162D		TL	24	AG24.00	45.7	27.6	140.6	20.5	10500	58	40
38101965	710/50R22.5	SB	172D		TL	25	AG24.00	50.39	27.95	152.75	22.63	13880	73	40
38100952	620/55R26.5	SB	166D		TL	25	AG20.00	53.4	24	159.8	23.9	11670	58	40
38101000	710/50R26.5	SB	170D		TL	35	AG24.00	53.5	28	164.2	24	13200	58	40
38101600	800/45R26.5	SB	174D		TL	40	AG28.00	54.1	31.5	166.9	24.1	14800	58	40

382 ALL-STEEL HIGH SPEED FLOTATION RADIAL MPT

OEM FITMENT

The Alliance 382 All-Steel is built for speeds of up to 62 mph. The block-type pattern enables high-speed travel and provides exceptional grip and a smooth ride on the road. Semi-sharp shoulder lugs provides better grip in muddy fields as well as in other soil conditions. (TUBELESS - ALL STEEL)



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
38200008	400/55R22.5		148F		TL	30	13.00DC	40.2	15.9	120.9	18.7	6940	87	50
38200010	400/55R22.5		146J		TL	30	13.00DC	40.2	15.7	120.5	18.6	6600	87	62
38200430	600/50R22.5		164J		TL	32	20.00DC	46.1	23.6	141.3	21.1	11000	94	62

393 STEEL BELTED FLOTATION RADIAL

OEM FITMENT

The Alliance 393 is a steel-belted tire for both on and off road applications. Shoulder lugs provides better grip in muddy fields as well as in other soil conditions. Strong bead bundle with extra-thick reinforced sidewalls and high turn-up plies ensure excellent stability and protection against external damages. (TUBELESS - STEEL BELTED)



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
39322800	35.5LR32	900/60R32	193A8/190B		TL	34	DH31	78.2	36.4	234.7	30	25400	87	25

388 STEEL BELTED FLOTATION RADIAL

The Alliance 388 is designed for minimal soil compaction and maximum tire life. For agricultural applications, primarily used on spreaders and special trailers (i.e. sugar cane production). Flat footprint, steel belts, rounded shoulders and low inflation pressure for superior performance over bias flotation.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
38828012	500/60R22.5		155D		TL	26	AG16.00	46.1	19.8	126.5	20.2	8550	58	40
38828025	560/60R22.5		156D		TL	26	AG16.00	48.2	21.2	146.5	21.5	8800	55	40
38828220	600/50R22.5		156D		TL	26	AG20.00	46	23.4	139.4	20.7	8800	52	40
38829000	710/45R22.5		156D		TL	25	AG24.00	47.6	28	144.9	21.1	8800	41	40
38830005	600/55R26.5		165D		TL	29	AG20.00	52.5	23.7	161.4	23.7	11400	58	40
38830030	650/65R26.5		165D		TL	33	20.00DC	59.8	25.7	177.5	26.8	11400	41	40
38830220	750/55R26.5		164D		TL	33	AG24.00	60	29.7	175.7	26.9	11000	35	40
38830000	600/65R34		164D		TL	34	DW20	65	24.2	200.8	28.8	11000	41	40
38830060	650/60R34		175D		TL	34	DW20	65.2	25.8	201.5	29.4	15200	58	40
38830150	710/55R34		169D		TL	34	DW24	65.2	28.2	193.3	28.9	12800	41	40
38830350	800/50R34		168D		TL	34	DW25	65.2	31.7	200.3	28.9	12300	35	40
38830380	850/45R34		168D		TL	34	DW28	65.2	33.2	190.6	28.9	12300	30	40

328 FLOTATION IMPLEMENT I-3

OEM FITMENT

The Alliance 328 I-3 is the broadest line of bias flotation tires in the market. High load capacities and low inflation pressures ensure minimal soil compaction.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
32826751	400/60-15.5		145A8	14	TL	21	13.00DC	34.4	15.9	98.8	14.8	5520	41	25
32826833	400/60-15.5			16	TL	21	13.00DC	34.4	15.9	98.9	14.8	6400	52	25
32826671	500/60-15.5			12	TL	35	16.00DC	39.1	19.8	113.9	17.3	9100	48	25
32826442	400/60-15.5		145A8	14	TL	21	13	34.4	15.9	98.8	14.8	8630	49	10
32827071	400/60-15.5		148 A8	16	TL	21	13	34	15.9	98.8	15	6940	58	25
32827075	400/60-15.5		152 A8	20	TL	21	13	34	15.9	98.8	15	7820	73	25
32826712	500/60-15.5		157A2	12	TL	35	16	39.1	19.8	113.9	17.3	9100	48	5
32829560	500/55-17			12	TL	35	16.00DC	39.1	19.8	112.2	17.1	6940	48	25

CONTINUED ON NEXT PAGE

328 FLOTATION IMPLEMENT I-3 (CONTINUED)

PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
32829630	500/55-17		148A8	12	TL	35	16	39.1	19.8	112.3	17.1	6940	48	25
32827420	500/50R17		145D		TL	35	16.00DC	37.6	19.5	110	16.8	6400	58	40
32826004	400/55-17.5			8	TL	33	13.00DC	34.9	15.3	102.5	15.2	4540	39	25
32826593	400/55-17.5		149A8/145B	16	TL	33	13.00DC	34.9	15.3	102.5	15.2	7150	58	25
32827011	44X1800-20		145D	8	TL	33	W14L	45	18	128.7	19.4	6410	41	30
32879505	42X2500-20		137A8	12	TL	32	20.50VF	42.5	24.5	124.4	18.9	5080	45	25
32880005	48X2500-20		149A8/145B	12	TL	33	20.50VF	49	25	142.5	21.6	7600	45	25
32881107	48X3100-20			12	TL	33	26.00VF	49	30.5	142.9	21.7	7400	41	25
32827033	400/55-22.5		149B	16	TL	33	13.00DC	40.6	15.8	124	17.9	7820	58	25
32897024	400/55-22.5			18	TL	33	13.00DC	40.6	15.8	124	17.9	8800	65	25
32827045	400/60-22.5		160A8	18	TL	33	11.75	42.1	15.7	122.8	18.6	9920	62	25
32827042	500/45-22.5		144B	12	TL	33	16.00DC	40.6	19.7	118.1	17.9	6940	39	25
32827046	500/45-22.5		150B		TL	33	16.00DC	40.6	19.7	124.1	17.9	8270	52	25
32827061	500/45-22.5		146E	16	TL	33	16.00DC	40.6	19.7	118.1	17.9	6600	52	43
32827645	500/45-22.5			16	TL	33	16.00DC	40.6	19.7	118.1	17.9	5840	52	25
32828000	500/60-22.5		145A8	12	TL	32	16.00DC	46.1	19.7	136.6	20.1	6390	35	25
32828123	500/60-22.5		159B	16	TL	32	16.00DC	46.1	19.7	136.6	20.1	10740	46	25
32828145	500/60-22.5		165A8 FR/153A8 DW	18	TL	33	16	46.1	19.7	136.6	20.1	11330	52	25
32827210	550/45-22.5		153B	12	TL	33	16.00DC	42.1	21.7	122.2	18.5	8040	30	25
32827054	550/45-22.5		156B		TL	33	16.00DC	42.1	21.7	125	18.7	9650	41	25
32827055	550/45-22.5		151E	16	TL	33	16.00DC	42.1	21.7	122.2	18.5	7600	41	43
32827153	550/45-22.5		165A8/161B	20	TL	33	22.5	42.12	21.65	125.19	18.74	8030	52	25
32832298	550/60-22.5			12	TL	32	16.00DC	48.7	21.7	140.9	21.3	9900	33	25
32832318	550/60-22.5		162B		TL	32	16.00DC	48.7	21.7	148.2	21.3	11680	44	25
32832285	550/60-22.5		166D	20	TL	32	16.00DC	48.7	21.7	147.4	22	9650	41	40
32832320	600/50-22.5			8	TL	32	20.00DC	46.1	23.6	135.8	20.1	6160	20	25
32832455	600/50-22.5		156B	12	TL	32	20.00DC	46.1	23.6	135.8	20.1	9640	29	25
32832520	600/50-22.5		161B		TL	32	20.00DC	46.1	23.6	135.8	20.5	11350	38	25
32832518	600/50-22.5		153A8/149B	16	TL	32	20.00DC	46.1	23.6	133.1	20.1	9100	38	25
32833065	600/55-22.5		151A8/148B	12	TL	32	20.00DC	50	23.6	143.7	23.6	11010	29	25
32841117	600/55-22.5		156A8/143B	16	TL	32	20.00DC	50	23.6	143.7	23.6	12780	38	25
32833108	600/55-22.5		161E	16	TL	32	20.00DC	50	23.6	143.7	21.7	10200	41	43
32835319	700/40-22.5		162B	16	TL	32	24.00DC	46.1	27.6	137.2	20.1	11670	38	25
32835324	700/40-22.5		168A8/164B	18	TL	32	24.00DC	46.1	27.6	137.2	20.1	12330	49	25
32840020	700/50-22.5		174A8/170B	16	TL	32	24.00DC	50	27.6	143.7	21.7	14800	41	25
32841144	700/50-22.5		166E	16	TL	32	24.00DC	50	27.6	143.7	21.7	11700	35	43
32874035	800/35-22.5		162D		TL	33	28.00DC	46.1	31.1	136.7	20.7	10470	38	40
32850011	600/55-26.5		165A8/161B	12	TL	32	20.00DC	52.5	23.3	151.6	22.8	13610	39	25
32852215	600/55-26.5		163A8/167B	16	TL	32	20.00DC	52.5	23.6	151.6	22.8	10700	38	35
32853003	600/55-26.5		170A8/167B	16	TL	32	20.00DC	52.5	23.3	151.6	22.8	13200	38	25
32862011	700/50-26.5		166A8/170B	16	TL	32	24.00DC	52.5	27.6	151.6	22.8	11700	35	35
32862023	700/50-26.5		174A8/170B	16	TL	32	24.00DC	52.5	27.6	151.4	22.8	14800	35	25
32871514	800/45-26.5		177A8/173B	16	TL	32	28.00DC	54.8	31.5	159.4	24.2	16100	32	25
32872509	650/60-30.5		174A8/170B	12	TL	33	20.00DC	65.7	25.6	188.6	28.3	14760	25	25
32827056	650/60-30.5		179D		TL	33	20.00DC	65.74	25.59	188.6	27.73	11990	32	40
32873604	750/60-30.5		182A8/179B	16	TL	33	24.00DC	65.7	29.5	188.6	28.3	18700	32	25
32873903	750/60-30.5		172D/179B	16	TL	33	24.00DC	65.7	29.5	188.6	28.3	13900	36	40
32872000	800/45-30.5			16	TL	33	28.00DC	59.4	31.9	175.1	26.1	16500	35	25
32874609	850/50-30.5		186A8/182B	16	TL	33	28.00DC	65.7	33.5	188.6	28.3	20900	32	25

328 FLOTATION IMPLEMENT VALUE PLUS I-3

The Alliance 328 Value Plus is designed for use on free-rolling axles. The tread pattern provides low rolling resistance and minimal soil compaction.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
32826825VP	400/60-15.5		148A8	16	TL	21	13.00DC	34.4	15.9	98.8	14.8	4940	64	25
32897081VP	500/45-22.5		154A8	16	TL	33	16.00DC	40.6	19.7	118.1	17.9	8250	52	25
32828108VP	500/60-22.5		163A8		TL	32	16.00DC	46.1	19.7	139.3	20.1	10750	46	25
32832150VP	550/60-22.5		166A8		TL	32	16.00DC	48.7	21.7	148.2	21.3	11680	44	25
32887060VP	550/45-22.5		159A8		TL	33	16.00DC	42.1	21.7	122.2	18.5	9650	41	25
32897021VP	400/55-22.5		152A8		TL	33	13.00DC	40.6	15.8	124	17.9	7830	58	25
32800010	14.0/65-16		142A8	14	TL	24	16	13.9	34.3	101.5	15.1	4070	58	25
32800011	19.0/45-17		146A8	14	TL	24	17	19.3	34.1	100.9	15	4664	41	25

331 FLOTATION IMPLEMENT I-3 / HF-3

The Alliance 331 I-3/HF-3 offers an aggressive directional pattern commonly used on drive axles. The robust lug also provided a smooth transition from lug to lug.

OEM FITMENT



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
33177985	38X1800-20			12	TL	48	W14L	39	18	113.8	17.2	4080	54	25
33178011	42X2500-20			12	TL	48	20.50VF	42.5	24.5	124.4	18.9	5080	45	25
33178108	48X2500-20			12	TL	49	20.50VF	49	25	142.5	21.6	7600	45	25
33181109	48X3100-20		148B	12	TL	49	26.00VF	49	30.5	142.9	21.7	7400	41	30
33115046	500/45-20		147A8	12	TL	48	16.00DC	37.4	19.3	111	17	6770	28	25
33115052	500/45-20		160A8/164A6	16	TL	48	16.00DC	38.6	19.3	114.6	17.6	9900	87	25
33117000	500/60-22.5		157A8/154B	12	TL	50	16.00DC	46.14	19.8	136.69	20.43	9075	35	25
33117108	500/60-22.5			16	TL	49	16.00DC	46.1	19.7	133.1	20.1	10740	46	25
33120001	550/45-22.5		153A8/149B	12	TL	47	16.00DC	42.1	21.7	125.2	19.2	8040	30	25
33120206	550/45-22.5		159A8/156B	16	TL	47	16.00DC	42.1	21.7	122.2	18.5	9650	41	25
33160210	550/45-22.5			20	TL	42	16.00DC	42.1	21.7	125.2	19.2	11670	58	25
33132211	550/60-22.5			16	TL	49	16.00DC	48.7	21.7	140.9	21.3	12000	41	25
33132243	600/40-22.5		154A8/150B	12	TL	47	20.00DC	42.9	23.6	124.7	18.9	8260	30	25
33132247	600/40-22.5		169A8	16	TL	47	20.00DC	42.9	23.6	129.1	19.9	12800	87	25
33122541	600/45R22.5		165A8/161B		TL	47	20.00DC	45.4	23.9	132.3	20.1	11340	58	25
33141010	650/45-22.5		169	169A8	TL	50	20DC	46.1	25.4	140.4	21.1	12780	65	25
33132608	600/50-22.5			16	TL	47	20.00DC	46.1	23.6	133.1	20.1	11340	38	25
33132623	600/50-22.5		174A6/170A8	18	TL	47	20.00DC	46.1	23.6	136.6	21	13200	87	25
33134008	600/55-22.5			16	TL	49	20.00DC	50	23.7	140.9	21	12780	38	25
33135112	700/40-22.5		177A6/173A8	16	TL	49	24.00DC	46.1	27.6	143.7	22	14300	87	25
33139513	700/50-22.5			16	TL	49	24.00DC	50	27.6	143.7	21.7	14800	35	25
33140107	500/60-26.5			12	TL	49	16	50	19.7	145.3	22	6610	35	25
33140126	500/60-26.5			16	TL	49	16.00DC	50	19.7	145.3	22	11340	46	25
33141205	600/50-26.5			16	TL	49	20.00DC	50	23.6	145.4	22	12000	38	25
33151204	600/55-26.5			16	TL	49	20.00DC	52.5	23.3	151.6	22.8	13220	38	25
33155272	700/40-26.5			22	TL	49	24.00DC	50	27.6	145.3	22	12330	32	25
33170015	700/50-26.5			16	TL	49	24.00DC	52.5	27.6	156.5	22.8	14760	35	25
33170080	700/50-26.5			20	TL	49	24	52.5	27.6	156.5	22.8	13230	73	25
33173010	800/45-26.5			16	TL	49	28.00DC	54.8	31.5	159.5	24.2	16080	32	25
33177208	600/60-30.5			16	TL	50	20.00DC	59.1	23.6	170.9	25.8	14760	38	25
33177321	700/50-30.5			16	TL	50	24.00DC	59.1	27.6	170.7	25.8	15640	32	25
33172000	710/50R30.5		176D		TL	50	AG24.00	59.1	27.6	179.9	26.5	21280	58	25
33177522	800/45-30.5			16	TL	50	28.00DC	59.1	31.5	170.9	25.8	17070	32	25

128 HS HIGH SPEED FLOTATION

The Alliance 128 HS (High Speed Flotation I-128) is designed with good self-cleaning characteristics which is suitable for on and off-the-road agricultural service on trailers and implements. The high load capacity and low inflation pressure of the tire results in high degree of agricultural soil protection, as well as low rolling resistance on both, on and off-road uses. The unique tread design enables smooth and quiet ride on road as well as high traction off the road. Its strong nylon construction and compounds ensure long life.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
12874035	800/35-22.5		162D	16	TL	33	28.00DC	46.1	31.5	135.8	20.6	10460	38	40

WHAT MAKES FLOTATION GREAT?

The Alliance Agriflex+ 389 VF, the world's first VF flotation tire, is a shining example of what makes it—and other flotation tires from Yokohama Off-Highway Tires—state-of-the-art farming technology. Alliance developed the world's first radial flotation tire, and for decades, the Alliance brand has been at the cutting edge of flotation tire technology.



STEEL RADIAL BELTS

Providing durability, heat dissipation and puncture resistance.

ULTRA-FLEXIBLE SIDEWALLS

For a larger footprint and low-pressure operation

REINFORCED CASING

Optimized for use with central tire inflation systems (CTIS)

SPECIALLY ENGINEERED TREAD

purpose-built for outstanding performance in the field and on the road

ROUNDED SHOULDERS

Engineered to minimize rutting

HEAT-DISSIPATING CONSTRUCTION

Ensures performance at high-speed—up to 40 mph

LARGE, EVEN FOOTPRINT

Reduces soil compaction and rolling resistance while improving flotation and traction

Distributor:

Yokohama Off-Highway Tires (YOHT) is a division of The Yokohama Rubber Co., specializing in Agriculture, Forestry, Construction, Industrial, Material Handling, Earthmoving, Mining, Port and other commercial tires. YOHT sells its diverse product range, consisting of over 4,000 SKUs, in over 120 countries through its subsidiaries and channel partners. YOHT products are engineered to be application-specific and purpose-built. For more information visit www.yokohama-oht.com or email us at info@yokohama-oht.com.



Contact Yokohama Off-Highway Tires America, Inc. at (800) 343-3276 or (399) 900-8080 for your nearest Yokohama OHT Tire Dealer.

