

AGRIFLEX+ 372

HEAVY DUTY TIRES FOR HIGH PERFORMANCE TRACTORS AND COMBINES.



- Engineered with increased flexion and very increased flexion (IF/VF) technology
- High speed capabilities, both on and off road
- Provides up to 40% more load capacity than standard tires for higher productivity
- Allows up to a 40% decrease in tire pressure compared to standard tires, preventing soil compaction and field damage
- Steel-belted tread for puncture resistance
- Stubble guard compound for long tread life
- Unique multi-angled tread design to ensure long life and a smooth ride, on the road or in the field

R1-W

D

H

0&0

**LARGE FOOTPRINT, LOW SOIL COMPACTION, GREAT TRACTION.
INCREASED PRODUCTIVITY AND REDUCED COSTS.**



AGRIFLEX+ 372 CFO STEEL BELTED R-1W

OEM FITMENT



The Alliance Agriflex+ 372 has state-of-the-art materials and steel-belted construction allowing our IF/VF radial tires to deliver outstanding performance. VF tires carry up to 40% more load at the same inflation pressure as conventional radials, or require 40% lower inflation pressure for the same load, reducing soil compaction. IF tires carry up to 20% more load at the same inflation pressure as conventional radials, or require 20% lower inflation pressure for the same load. Stronger carcass designed for cyclic service and intended for use on minimal torque applications such as combines, harvesters and grain carts (up to 1 mile). (TUBELESS - STEEL BELTED - STUBBLE GUARD)



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
37250024	VF 520/80R26 CFO		168A8		TL	57	DW16L	57.7	19.9	1707.0	24.7	12330	41	25
37200080	VF 620/70R26		170D		TL	57	DW21B	58.5	24.6	172.7	25.4	13220	35	40
37250001	VF 750/65R26		177B		TL	71	DW25B	64.4	29.7	187.2	27.5	16080	35	40
37200008	VF 420/85R28 CFO		151D		TL	58	DW15	56.6	17.6	167.5	24.7	7600	23	40
37200048	VF 600/60R28		146D		TL	62	DW20B	61.4	24.6	163.7	26.8	14320	41	40
37200052	IF 600/65R28 CFO		160D		TL	57	DW21B	58.5	23.9	176.4	26.2	9900	35	40
37200096	VF 600/70R28 CFO		173D		TL	71	DW21B	61.4	24.6	179.9	26.8	14300	41	40
37200054	VF 600/60R30		147D		TL	63	DW20B	58.7	23.2	170.0	25.6	6770	15	40
37200105	VF 600/70R30 CFO		170D		TL	70	DW21B	63.0	24.6	187.8	28.0	13200	35	40
37200063	IF 620/75R30 CFO		164D		TL	73	DW23B	65.9	25.6	191.1	28.9	11020	23	40
37200126	VF 650/75R30 CFO		172D		TL	74	DW20B	67.7	26.0	194.6	28.9	13900	23	40
37250002	VF 710/55R30		165D		TL	63	DW25B	60.8	28.8	187.2	26.6	19270	23	40
37250003	VF 710/60R30		171D		TL	68	DW25B	63.6	28.0	186.8	27.4	13550	29	40
37200136	VF 800/65R32 CFO	30.5LR32	184D		TL	73	DW27B	72.6	30.5	213.2	31.7	19840	35	40
37200104	IF 800/70R32 CFO		182A8		TL	74	DW27B	76.1	30.9	224.6	33.7	18700	35	25
37200103	IF 900/60R32 CFO	35.LR32	193D		TL	73	DW30B	74.4	34.8	222.4	33.3	22000	46	40
37200150	IF 1250/50R32 CFO		201B		TL	76	DH44B	81.9	49.2	244.5	35.6	22480	46	30
37250004	VF 600/70R34		167D		TL	71	DW21B	67.1	24.6	196.1	26.5	19270	23	40
37200097	IF 650/65R34		161D		TL	73	DW23	67.7	25.6	198.1	30.3	10200	23	40
37250032	VF 520/85R38		170D		TL	69	DW16L	72.8	20.9	215.9	31.8	13220	29	40
37250052	VF 600/65R38		163D		TL	57	DW21B	58.5	23.9	172.5	25.6	10740	29	40
37200130	VF 710/60R38		160D		TL	68	DW25B	71.5	28.0	209.2	31.6	9910	28	40
37200141	VF 710/70R38 CFO		178D		TL	77	DW25B	77.1	28.3	225.1	33.2	16540	23	40
37250093	VF 710/85R38		183D		TL	84	DW25B	85.2	28.7	249.2	36.7	19270	23	40
37200118	IF 800/70R38 CFO		187A8		TL	79	DW27	81.9	32.3	240.2	36.5	21500	41	25
37250106	VF 900/60R38 CFO NRO		155D		TL	79	DW30B	80.1	35.0	234.8	34.5	21480	29	25
37200035	IF 520/85R42	20.8R42	169D		TL	70	DW16L	77.0	21.3	230.9	34.6	12780	35	40
37200036	VF 520/85R42 CFO		177A8		TL	69	DW16L	77.0	21.3	228.6	34.4	16100	41	25
37200044	VF 580/85R42		183D		TL	71	DW20B	80.3	23.4	238.3	35.8	19270	41	40
37200068	VF 620/70R42		172D		TL	68	DW21B	76.2	24.4	225.0	33.4	13880	23	40
37200133	VF 710/60R42		161D		TL	68	DW25B	75.7	28.0	224.0	33.5	10190	15	40
37200095	VF 710/70R42 CFO		185D		TL	79	DW25B	81.2	29.3	239.9	36.4	20390	35	40
37200180	VF 710/75R42 CFO		181D		TL	79	DW25B	84.8	28.5	247.2	37.0	18190	23	40


MINIMIZE SOIL COMPACTION



STEEL BELTED



HIGH SPEED CAPABILITIES



VISIT YOKOHAMA-OHT.COM FOR DETAILED LOAD AND PRESSURE TABLES

Distributor:

Yokohama Off-Highway Tires (YOHT) is a division of The Yokohama Rubber Co., specializing in Agriculture, Forestry, Construction, Industrial, Material Handling, Earthmoving, Mining, Port and other commercial tires. YOHT sells its diverse product range, consisting of over 4,000 SKUs, in over 120 countries through its subsidiaries and channel partners. YOHT products are engineered to be application-specific and purpose-built. For more information visit www.yokohama-oht.com or email us at info@yokohama-oht.com.



Contact Yokohama Off-Highway Tires America, Inc. at (800) 343-3276 or (339) 900-8080 for your nearest Yokohama OHT Tire Dealer.

