

APPLICATOR TIRE FAMILY
MAXIMIZE YIELD.
MINIMIZE
COMPACTION.



AGRIFLEX+ 363 STEEL BELTED R-1

OEM FITMENT



The Alliance Agriflex+ 363 is rated for speeds up to 40 mph over the road, and is designed for sprayers that need to perform both on the fields and on the road. State-of-the-art materials and the steel-belted construction allow IF (Increased Flexion) radial tractor tires to deliver outstanding performance in any conditions. IF tires carry 20% more load on the same inflation pressure as conventional radials, or require 20% less inflation pressure for the same load, to reduce soil compaction. (TUBELESS - STEEL BELTED - STUBBLE GUARD)

PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
36350532	VF 270/95R32		138D		TL	44	W9	52.4	11.2	156.2	24.0	5200	35	40
36350462	VF 270/95R36		140D		TL	44	W9	56.1	10.9	168.8	26.0	5510	35	40
36350004	VF 270/95R38		141D		TL	44	W9	58.1	10.9	174.5	26.8	5670	35	40
36350002	VF 380/80R38		154D		TL	48	DW12	62.6	15.0	188.5	28.4	7518	35	40
36350020	VF 320/90R46		155D		TL	47	DW11	68.8	12.1	210.0	31.8	8540	41	40
36300036	VF 380/90R46	14.9R46	173D		TL	49	DW13	72.5	15.3	218.4	33.4	14300	64	40
36300011	VF 230/95R48	9.5R48	146D		TL	42	DW9	65.4	9.1	199.1	30.9	6600	52	40
36300014	VF 270/95R48	11.2R48	155D		TL	44	DW10	68.2	10.8	209.8	32.1	8540	58	40
36300220	VF 320/90R50		166D		TL	47	DW11	72.7	13.0	221.1	33.9	11670	64	40
36350090	VF380/105R50		179D		TL	50	W13	80.7	15.7	244.3	37.2	15549	64	40
36300100	IF 480/80R50	18.4R50	166D		TL	52	DW16B	80.2	18.9	242.2	37.0	11700	35	40
36350100	VF 480/80R50	18.4R50	169D		TL	52	DW16L	80.2	18.7	240.3	36.2	12780	29	40
36350104	VF 480/80R50	18.4R50	177D		TL	52	DW16L	80.2	18.9	242.7	36.9	13558	35	40
36300017	VF 270/95R54	11.2R54	156D		TL	44	DW10	76.6	11.3	226.1	35.2	8800	52	40

AGRIFLEX+ 354 STEEL BELTED R-1W

OEM FITMENT



The Alliance Agriflex+ 354 has state-of-the-art materials and the steel-belted construction allow VF (Very High Flexion) and IF (Increased Flexion) radial tractor tires to deliver outstanding performance in any conditions. VF tires carry 40% more load on the same inflation pressure as conventional radials, or require 40% less inflation pressure for the same load, to reduce soil compaction. IF tires carry 20% more load on the same inflation pressure as conventional radials, or require 20% less inflation pressure for the same load. (TUBELESS - STEEL BELTED - STUBBLE GUARD)

PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
35410005	VF 380/85R30		146D		TL	59	DW13	55.6	15.5	163.9	24.6	6610	29	40
35400105	VF 420/90R30		153D		TL	62	DW13	59.8	17.7	176.6	26.3	8040	29	40
35400224	VF 320/85R32		139D		TL	56	W11	53.4	12.6	158.1	24.2	7490	23	40
35400028	VF 320/85R34		143D		TL	56	W11	55.7	12.8	166.0	25.3	8410	29	40
35400028	VF 320/85R34		149D		TL	56	W11	55.7	12.8	166.0	25.3	6000	29	40
35400009	VF 380/85R34		149D		TL	59	DW13	60.0	15.6	177.3	26.7	7160	29	40
35450109	VF 420/85R34		159D		TL	60	DW14L	62.0	16.4	183.5	27.7	9640	35	40
35400140	VF 420/95R34		157D		TL	62	w14I	65.4	16.5	194.0	28.8	9094	23	40
35400017	VF 480/70R34		160D		TL	59	DW16L	62.2	19.5	185.8	28.1	9910	44	40
35400031	VF 320/85R38		155D		TL	56	W11	59.3	12.6	178.1	27.3	8540	52	40
35400002	VF 380/80R38		154D		TL	59	DW13	62.6	15.0	185.4	28.5	8260	35	40
35450004	VF 380/95R38		159D		TL	60	DW13	66.4	15.4	196.7	29.9	9640	35	40
35450001	VF 320/80R42		155D		TL	54	W11	62.2	12.6	188.4	29.1	8540	64	40
35400018	VF 480/80R42		162D		TL	66	DW16	72.8	19.3	216.1	32.5	10460	29	40
35450046	VF 320/90R46		160D		TL	56	DW10	68.7	12.4	208.3	31.9	9910	52	40
35400053	VF 320/105R46		172D		TL	59	DW11	72.4	12.8	219.8	33.5	13880	70	40
35400016	VF 380/90R46		173D		TL	61	DW13	73.0	15.4	220.3	33.9	14320	64	40
35450000	VF 420/80R46		172D		TL	61	W13B	72.4	16.5	217.2	32.8	12330	58	40

CONTINUED ON NEXT PAGE

AGRIFLEX+ 354 STEEL BELTED R-1W continued

PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
35400062	VF 480/80R46		164D		TL	66	DW16	76.7	19.3	228.6	34.5	11010	29	40
35400033	VF 520/85R46		170D		TL	67	DW18	80.8	20.9	236.7	36.1	13220	23	40
35400050	VF 340/85R48		164D		TL	56	DW12	71.2	13.5	216.1	33.1	11010	58	40
35400047	VF 320/105R50		158D		TL	59	DW11	76.3	12.7	229.8	35.2	8990	40	40
35400133	VF 320/90R50		166D		TL	56	W11	72.8	12.6	221.3	34.0	11700	64	40
35400023	VF 380/90R50		175D		TL	59	W13B	77.0	15.2	230.6	35.4	15200	64	40
35400090	VF 380/105R50		179D		TL	60	DW13	80.8	15.6	243.1	37.0	17070	64	40
35400180	VF 420/95R50		177D		TL	60	DW14	80.8	16.7	241.4	36.7	16090	52	40
35400021	VF 480/80R50		179D		TL	66	DW16	80.7	19.1	240.7	38.7	17100	52	40
35400027	VF 480/95R50		176D		TL	66	DW16	86.1	19.1	257.9	38.7	15640	35	40
35400006	IF 230/115R54		151D		TL	58	W8	76.7	10.1	233.5	35.9	7600	46	40
35400041	IF 270/105R54		158D		TL	58	W10	76.6	11.0	234.2	36.1	9360	58	40
35400036	VF 320/90R54		168D		TL	56	DW11	76.8	12.6	234.0	35.9	12350	64	40
35400056	VF 320/105R54		172D		TL	59	DW11	80.3	12.8	244.6	37.4	13880	64	172D
35400029	VF 380/90R54		176D		TL	59	DW13	80.7	15.1	244.1	37.4	15640	64	40
35400205	IF 380/105R54		180D		TL	60	DW13	85.2	15.6	257.2	39.4	17620	75	40

550 MULTI-USE STEEL BELTED

OEM FITMENT

The Alliance 550 provides exceptional traction whatever the terrain; snow, sand, hard surfaces and soft surface alike. Steel belts and a cut- and chip-resistant compound make this tire exceedingly puncture resistant.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
55000042	250/75R16		120G		TL	20	W8	30.7	10.0	92.2	14.2	3080	65	55
55000035	250/80R16		126A8/123D		TL	22	W8	32.0	10.6	97.2	14.7	3420	64	40
55000040	265/70R16.5	10R16.5	130A2		TL	29	8.25	30.4	10.5	92.3	13.7	4180	58	5
55000012	305/70R16.5	12R16.5	141A5		TL	30	9.75	32.8	12.0	97.2	14.7	6130	58	5
55010470	340/80R18	12.5/80R18	143A8/138D		TL	31	DW11	39.4	13.5	118.2	17.7	6000	58	40
55010405	365/70R18		142A2/135B		TL	31	DW11	38.1	14.0	113.1	17.6	4940	54	30
55001480	400/70R18		147A8/144D		TL	33	W13	40.2	15.9	120.4	18.4	6150	58	40
55000055	405/70R18	16.0/70R18	153A2/141B		TL	33	W13	40.2	15.9	120.4	18.4	5670	54	30
55010535	340/80R20	12.5R20	144A8/140D		TL	31	DW11	41.4	13.5	124.1	18.9	5520	58	40
55001617	360/70R20		129A8/124D		TL	31	DW11	41.4	14.0	122.9	18.6	3520	35	40
55001620	360/80R20		147A8/143D		TL	34	DW11	43.0	14.1	128.5	19.3	6800	58	40
55001510	400/70R20		149B		TL	33	DW13	42.0	15.9	125.2	19.0	7150	58	30
55000060	405/70R20	16.0/70R20	149B		TL	33	DW13	42.4	15.9	126.2	19.1	7150	58	30
55001450	300/80R24		133A8/128D		TL	32	W9	43.0	11.6	127.5	19.8	3860	46	40
55001615	340/80R24		140A8/135D		TL	31	W11	45.4	13.5	135.4	20.8	4800	46	40
55001406	360/80R24	13.6R24	143A8/138D		TL	32	W11	46.6	14.1	139.6	21.3	5200	46	40
55001710	400/80R24	14.9R24	149A8/144D		TL	34	W13	49.2	15.9	145.8	22.0	6170	46	40
55002475	420/65R24		151A8/146D		TL	33	W13	45.6	16.1	137.4	20.7	6600	46	40
55002025	440/80R24	16.9R24	154A8/149D		TL	34	W13L	51.7	17.4	156.1	23.3	7150	46	40
55000025	460/65R24		156A8/151D		TL	34	W15L	47.6	17.9	141.6	21.5	7600	46	40
55000120	460/70R24	17.5LR24	159B		TL	34	W15L	49.2	18.4	149.0	22.4	9650	46	30

CONTINUED ON NEXT PAGE

550 MULTI-USE STEEL BELTED continued

PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
55002400	480/65R24		151A8/146D		TL	37	W15L	48.8	18.9	146.9	22.1	6600	46	40
55005410	500/70R24	19.5LR24	164B		TL	36	W16L	51.5	19.9	154.4	23.3	11000	46	30
55005330	540/65R24	21LR24	158A8/154D		TL	39	W18L	51.7	21.3	155.6	23.3	8250	46	40
55024950	480/80R26	18.4R26	160B		TL	34	W16L	56.1	19.0	168.0	25.4	9900	46	30
55002360	400/80R28	14.9R28	151A8/146D		TL	34	W13L	53.2	15.9	159.1	24.3	6600	46	40
55002610	440/80R28	16.9R28	156A8/151D		TL	34	W14L	55.8	17.3	166.9	25.2	7600	46	40
55002810	480/65R28		154A8/149D		TL	34	W15L	52.9	18.7	158.3	23.9	7150	46	40
55005390	540/65R28		160A8/155D		TL	39	W18L	55.6	21.7	168.0	25.6	8550	46	40
55002625	440/80R30		157A8/153D		TL	34	W14L	57.8	17.1	174.6	26.4	8050	46	40
55003015	480/80R30	18.4R30	162A8/157D		TL	35	W15L	60.3	18.5	181.7	27.4	9100	46	40
55005510	540/65R30		161A8/156D		TL	38	DW18A	57.6	21.7	176.4	26.7	8800	46	40
55005910	600/70R30		161A8/158D		TL	38	DW20A/B	63.1	24.1	188.7	28.6	9350	35	40
55002760	440/80R34	16.9R34	159A8/155D		TL	36	W14L	61.7	17.4	186.5	28.3	8550	45	40
55003310	480/80R34	18.4R34	164A8/159D		TL	34	W15L	64.3	18.9	192.6	29.1	8550	46	40
55005352	480/80R38	18.4R38	166A8/161D		TL	34	W15L	68.0	18.9	204.6	30.9	10200	46	40
55005810	540/80R38	20.8R38	172A8/167D		TL	38	DW18A	71.8	21.5	216.4	32.8	12000	46	40
55005860	600/65R38		170A8/166D		TL	38	DW18A	68.9	23.3	207.5	31.2	11700	46	40
55006700*	650/65R38		175A8/170D		TL	40	DW20A/B	71.4	25.4	214.6	32.2	13200	46	40
55006725	650/85R38		181A8/177D		TL	40	DW23B	81.4	26.5	245.3	35.9	18170	35	40
55007030	620/80R42		181A8/177D		TL	45	DW20A/B	80.9	25.4	242.9	37.3	16100	46	40
55007160	650/65R42		176A8/171D		TL	40	DW20A/B	75.3	25.4	227.0	34.3	13600	46	40
55007180	710/70R42		181A8/177D		TL	45	DW23A/B	80.8	28.2	243.6	37.0	16100	41	40

MULTISTAR 376 STEEL BELTED R-1

OEM FITMENT

The Alliance Multistar 376 is designed to offer great traction and soil protection on harvesters and floaters. Steel belts and a stubble-resistant rubber compound ensures a long tire life and maximum durability. (TUBELESS - STEEL BELTED - STUBBLE GUARD)



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
37600010	750/50R26		157A8/151D		TL	50	DW25B	55.9	29.6	167.7	25.3	9100	35	25
37600093	680/85R32		178A8/178B		TL	63	DW21B	77.2	26.0	229.3	34.7	16520	46	25
37601055	900/60R32		176D		TL	72	DW27B	74.6	34.2	222.0	33.5	15640	35	40
37601069	900/60R32	35.5LR32	191D		TL	72	DW27B	74.6	34.2	222.9	33.5	23980	64	40
37600091	1050/50R32		185A8/182D		TL	52	DW36A	73.6	41.3	223.9	32.8	26800	63	30
37600094	IF 1050/50R32 CFO		195A8		TL	53	36VA	73.2	41.3	222.4	32.8	26790	58	25
37600040	620/70R46 non steel belt		162A8/159D		TL	73	DW20B	81.1	24.4	241.7	37.0	9650	23	40

AGRIFLEX+ 377 VF R1

OEM FITMENT

The Alliance Agriflex +377 is the latest addition to Alliance's engineered series of Agriflex tires. It has been designed to fulfil the needs of spreaders, sprayers, combine harvesters and grain carts. Its ability to carry 40% more load at the same amount of pressure makes it well equipped to move the additional weight of fertilizers and herbicides with minimum soil compaction.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
37750003	1000/50R25		184D		TL	58	36	64.8	40.6	194.8	27.7	19820	35	40
37750004	750/50R26		169D		TL	50	DW25B	55.6	29.7	167.2	24.1	12780	35	40
37750142	1050/50R32		198D		TL	58	36VA	73.3	41.7	222.4	32.3	29070	52	40

398 MPT FLOTATION R-4

The Alliance 398 MPT is a definitive solution for modern off road and on road vehicles. It enhances the productivity and reduces cycles time by moving effortlessly between the field and the road. Its high load carrying and high speed capacity saves both time and money.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
39800025	445/65R22.5		160J		TL	38	W14L	45.9	17.9	141.4	21.0	9910	87	62
39800060	445/70R24		151J		TL	45	W14L	48.9	17.9	149.0	22.6	7600	65	62
39800075	495/70R24		155J		TL	47	W16L	51.6	20.2	151.5	23.7	8540	65	62
39810020	600/50R22.5		164J		TL	38	AG20.00	46.1	24.4	141.9	21.3	11010	94	62

AGRIFLEX+ 389 VF FLOTATION HF2

OEM FITMENT

The Alliance Agriflex 389 VF-Imp provides the best possible solution for soil protection on large and heavy implements such as towed spreaders, grain wagons, liquid manure tankers and other agricultural trailers.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
38950009	VF500/50R17		150	NA	TL	27	16	36.5	19.8	109.7	15.7	7380	46	40
38900105	VF 500/60R22.5		155D		TL	27	AG16.00	46.1	19.8	139.2	21.0	7165	46	40
38950102	VF500/60R22.5		157	NA	TL	27	16	46.1	19.8	139.0	20.0	9910	46	40
38900011	VF 560/60R22.5		163D		TL	29	AG16.00	49.2	22.2	146.1	21.2	10750	41	40
38900018	VF 600/55R26.5		167D		TL	33	AG20.00	53.1	24.8	160	23.1	12020	41	40
38900025	VF 650/55R26.5		171D		TL	33	AG20.00	54.5	25.6	164.3	23.6	13560	41	40
38900026	VF 650/60R26.5		174D		TL	33	AG20.00	57.2	26.2	172.8	24.5	14760	41	40
38900028	VF 710/50R26.5		173D		TL	33	AG24.00	55.1	28.8	168.1	23.7	14330	41	40
38900030	VF 750/45R26.5		172D		TL	33	AG24.00	53.5	29.7	160.9	23.2	13890	41	40
38900045	VF 750/60R30.5		183D		TL	33	AG24.00	66.1	30.7	199.6	28.4	19290	41	40
38900065	VF 800/60R32		188D		TL	33	DW27B	70.9	31.5	215.2	30.6	22030	41	40

380 STEEL BELTED FLOTATION RADIAL

OEM FITMENT

The Alliance 380 is a premium non-directional radial with steel belts for durability. The flat profile and thick lug design minimizes compaction.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
38022953	550/45R22.5		151E		TL	31	AG16.00	42.1	21.7	125.2	19.3	7600	58	43
38026010	560/45R22.5		152D		TL	31	AG16.00	42.3	21.4	128.5	19.1	7850	58	40
38022922	560/60R22.5		161E		TL	29	AG16.00	49.0	21.8	149.6	22.0	10200	58	43
38025001	560/60R22.5		172D		TL	29	AG16.00	49.2	21.7	150.6	21.8	13880	73	40
38032358	580/65R22.5		166D		TL	29	AG16.00	51.9	23.0	160.3	22.8	11680	58	40
38022960	600/50R22.5		164J		TL	32	AG20.00	46.1	23.9	142.4	21.2	11010	94	62
38022956	600/50R22.5		159D		TL	31	AG20.00	46.1	24.05	139.3	20.8	9640	58	40
38000001	600/50R22.5		168B		TL	32	AG20.00	46.1	24.10	141.4	19.8	12346	46	30
38022999	600/55R22.5		162E		TL	29	AG20.00	49.0	23.6	144.5	22.1	10500	58	43
38028020	620/40R22.5		155D		TL	33	AG20.00	42.2	24.4	125.2	19.2	8550	58	40
38028058	620/40R22.5		171A8		TL	33	AG20.00	42.2	24.4	125.2	19.2	13600	102	25
38022975	650/50R22.5		163E		TL	33	AG20.00	48.6	25.6	142.9	21.8	10700	58	43

CONTINUED ON NEXT PAGE

380 STEEL BELTED FLOTATION RADIAL continued

PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
38040800	710/45R22.5		165D		TL	33	AG24.00	47.6	28.6	145.0	21.0	11350	58	40
38022961	750/45R22.5		166E		TL	33	AG24.00	49.0	29.5	144.5	22.1	11700	58	43
38023010	750/45R22.5		177D		TL	33	AG24.00	49.2	29.3	144.5	21.9	16100	73	40
38030050	600/55R26.5		165E		TL	33	AG20.00	53.1	24.6	162.8	23.9	11350	58	43
38030001	600/55R26.5		177D		TL	33	AG20.00	53.1	24.6	162.8	23.9	16080	73	43
38030110	650/55R26.5		178D		TL	33	AG20.00	53.8	25.2	163.4	24.2	16520	73	40
38031010	650/55R26.5		167E		TL	33	AG20.00	53.5	25.4	164.4	24.3	12000	58	43
38030522	650/60R26.5		173D		TL	33	AG20.00	57.1	26.0	168.5	25.8	14320	58	40
38030545	650/60R26.5		181D		TL	33	AG20.00	57.1	26.0	167.7	25.8	18200	73	40
38030750	650/65R26.5		174D		TL	33	AG20.00	59.8	26.1	180.7	26.9	14770	58	40
38030740	650/65R26.5		181D		TL	33	AG20.00	59.9	26.1	184.1	27.1	18170	73	40
38041001	710/50R26.5		170D		TL	33	AG24.00	55.1	28.8	168.9	24.8	13220	58	40
38041005	710/50R26.5		178D		TL	33	AG24.00	55.2	28.7	168.8	24.8	16500	73	40
38022992	750/45R26.5		170E		TL	33	AG24.00	53.5	29.1	162.9	24.3	13220	58	43
38040751	650/65R30.5		176D		TL	33	AG20.00	64.0	26.8	187.8	28.6	15640	58	40
38040790	650/65R30.5		181D		TL	33	AG20.00	64.1	26.6	197.0	29.2	18170	73	40
38060001	750/60R30.5		181D		TL	33	AG24.00	66.1	30.2	201.3	29.7	18200	58	40
38060008	800/60R32		185D		TL	33	DW27A	70.9	31.7	212.9	32.0	20370	58	40

390 STEEL BELTED AGRI-TRANSPORT FLOTATION RADIAL

OEM FITMENT



The Alliance 390 is the completely original Agri-Transport tire that set the standard for flotation—the tire the competition strives to duplicate. This steel-belted, high-speed tire is sought after by OEMs and in the replacement market for a wide range of on-road and off-road applications.

PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
39000102	24R20.5		176F		TL	29	AG16.00	54.0	23.8	165.6	24.4	15640	87	50
39020700	560/45R22.5		152D		TL	22	AG16.00	42.4	21.5	133.5	19.0	7820	58	40
39021040	500/45R22.5 AS		154F		TL	25	AG16.00	40.4	20.0	124.3	18.6	8250	87	50
39021100	500/60R22.5		155D		TL	22	16.00DC	46.5	20.1	142.4	20.8	8540	58	40
39021250	560/60R22.5		164D		TL	22	AG16.00	49.3	22.5	144.5	22.0	11010	58	40
39021292	560/60R22.5		170D		TL	22	AG16.00	49.7	22.2	151.3	22.1	13220	73	40
39021310	560/60R22.5 AS		170D		TL	22	AG16.00	49.3	21.9	150.9	22.0	13220	73	40
39021285	580/65R22.5		166D		TL	24	AG16.00	51.7	22.9	156.9	22.9	11670	58	40
39022808	600/50R22.5		159E		TL	31	20.00DC	46.1	23.0	136.6	20.9	9640	58	43
39022822	600/50R22.5 AS		166F		TL	31	20.00DC	46.5	23.0	138.2	21.2	11700	87	50
39023150	600/50R22.5		174A8		TL	31	20.00DC	46.0	23.8	135.8	20.8	14800	94	25
39005728	620/75R26		174D		TL	34	DW20B	62.6	24.4	185.9	27.8	14760	58	40
39005725	710/65R26		185D		TL	35	DW25	61.8	28.7	188.3	27.4	20370	73	40
39005710	710/65R26		176D		TL	35	DW25	60.8	28.0	178.3	27.2	15640	58	40
39005731	28LR26	176A8/173B			TL	35	DW25	60.7	28.6	178.0	27.1	14300	41	30
39021300	600/55R26.5		165D		TL	31	AG20.00	53.3	24.6	162.2	24.1	11340	58	40
39021315	600/55R26.5		177D		TL	31	AG20.00	53.1	24.6	162.2	24.0	16080	73	40
39030125	650/55R26.5		170D		TL	31	20.00DC	54.9	26.0	161.8	24.8	13220	58	40
39021600	650/55R26.5		178D		TL	31	20.00DC	54.9	26.2	162.2	24.8	16500	73	40
39022334	800/45R26.5		177D		TL	33	28.00DC	54.7	31.9	161.4	24.7	16080	58	40
39022521	710/50R26.5		172D		TL	33	24.00DC	54.7	28.7	167.3	24.7	13900	58	40
39022524	710/50R26.5		180D		TL	33	24.00DC	55.0	28.9	167.3	24.6	17620	73	40
39022620	600/60R30.5		173D		TL	33	20.00DC	59.3	25.0	175.6	26.9	14320	58	40
39022632	600/60R30.5		179D		TL	33	20.00DC	59.4	24.8	181.9	27.0	17070	73	40
39022775	710/50R30.5		176D		TL	33	24.00DC	58.9	28.6	174.4	26.8	15640	58	40

CONTINUED ON NEXT PAGE

390 STEEL BELTED AGRI-TRANSPORT FLOTATION RADIAL continued

PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
39022112	750/60R30.5		181D		TL	33	24.00DC	65.9	30.7	194.9	29.8	18170	58	40
39022135	750/60R30.5		190D		TL	33	24.00DC	66.3	30.3	201.8	29.6	23350	73	40
39030277	850/50R30.5		182D		TL	34	28.00DC	70.9	31.5	208.3	31.7	19820	58	40
39022456	30.5LR32		181B		TL	39	DW27A	70.9	31.1	207.9	31.7	18200	44	30
39022661	800/60R32		184D/181E		TL	39	DW27A	70.9	31.3	209.8	32.1	19800	58	40

590 STEEL BELTED FLOTATION IMPLEMENT I-2

The Alliance 590 is a heavy duty radial flotation tire designed specifically to suit the needs of agriculture and construction applications. A robust steel belted construction with non-directional tread design and superior cut and chip resistant compound enables it to handle heavy Loads and operate both in farms as well as on/off road applications.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
59000292	560/60R22.5		169D		TL	29	AG16.00	49	21.7	148.6	22.2	10196	58	40
59000315	600/55R26.5		173D		TL	33	AGC20.00	52.5	24.1	160.3	24.1	11354	58	40
59000621	650/55R26.5		177D		TL	34	AGC20.00	54.7	25.6	167.4	25	12787	58	40
59000544	650/60R26.5*		180D		TL	33	AGC20.00	57.2	25.6	174.9	26	13889	58	40
59000002	600/60R30.5		173D		TL	33	AGC20.00	58.9	24.1	178.8	26.9	12787	58	40
59000795	650/65R30.5		184D		TL	34	AGC20.00	63.8	26	193.8	29.2	15653	58	40
59000800	710/50R30.5		181D		TL	34	AGC24.00	58.7	28.6	178.8	26.9	14330	58	40
59000003	750/60R30.5		190D		TL	34	AGC24.00	65.9	29.7	199.6	29.8	18188	58	40

885 STEEL BELTED FLOTATION RADIAL IMPLEMENT OEM FITMENT

The Alliance 885 is the new generation in steel-belted radial flotation tires engineered for all applications. Strong bead bundle, extra-thick reinforced sidewall and a high turn-up plies ensure excellent stability and protection against external damages.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
88500003	560/45R22.5		152D		TL	25	AG16.00	41.7	21.4	128.3	18.8	7850	58	40
88500015	560/60R22.5		164D		TL	25	AG16.00	48.4	21.9	142.5	21.8	11000	58	40
88500502	580/65R22.5		166D		TL	25	AG16.00	51.8	22.6	159.1	22.8	11700	58	40
88500582	600/50R22.5		159D		TL	26	AG20.00	46.1	23.9	136.6	20.9	9650	58	40
88500612	650/50R22.5		163D		TL	25	AG20.00	48.6	25.6	142.9	21.8	10700	58	40
88500622	710/45R22.5		165D		TL	30	AG24.00	47.6	28.5	144.7	21.1	11400	58	40
88500588	600/55R26.5		165D		TL	33	AG20.00	53.0	24.6	156.6	24.0	11340	58	40
88500620	650/55R26.5		170D		TL	33	AG20.00	54.3	25.5	160.6	24.8	13200	58	40
88500621	650/65R26.5		174D		TL	33	AG20.00	59.8	25.4	180.3	26.4	14760	58	40
88500640	710/50R26.5		170D		TL	33	AG24.00	55.1	28.8	168.9	24.8	13200	58	40
88500670	750/45R26.5		170D		TL	33	AG24.00	53.5	29.1	162.9	24.3	13200	58	40
88500600	800/45R26.5		174D	174D	TL	34	28	54.7	31.5	166.0	24.5	14760	58	40
88500645	710/50R30.5		173D	173D	TL	34	24	58.7	28.9	179.5	26.7	14320	58	40
88500710	750/60R30.5		181D		TL	33	AG24.00	66.1	30.2	201.3	29.7	18200	58	40

AGRIFLEX 381 IF/VF I2

Alliance Agriflex 381 is an IF/VF steel belted radial flotation tire that has been developed to serve the needs of implements that are pulled on the road at high speeds and then used in fields full of stubble. The unique rib type pattern, enables a large footprint and low ground pressure. The shoulder lugs prevent any excessive tire slip and any consequent damage to the surface. It's specially designed bead area ensures better load carrying capacity.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
38100005	500/50R17		146D		TL	18		37.4	19.4		16.6	6600	58	40
38100006	500/50R17	SB	146D		TL	18		37.4	19.4		16.6	6600	58	40
38110060	500/45R20		157A8		TL	18		37.7	19.8		16.2	9090	58	30
38100100	560/45R22.5	SB	146D		TL	23		42.5	21.3		19.1	6600	46	40
38100135	560/45R22.5		146D		TL	23		42.5	21.3		19.1	6600	46	40
38100150	560/45R22.5		146D		TL	23		42.5	21.3		19.1	6600	46	40
38102600	620/40R22.5		148D		TL	23		42.5	24.1		19.1	6950	46	40
38102620	620/40R22.5		154D		TL	23		42.5	24.1		19.1	8250	58	40
38102618	620/50R22.5		161D		TL	24		46.1	23.6		20.5	10200	58	40
38100810	710/40R22.5	SB	162D		TL	24		45.7	27.6		20.5	10500	58	40
38101965	710/50R22.5	SB	172D		TL	25		50.4	28.0		22.6	13880	73	40
38100952	620/55R26.5	SB	166D		TL	25		53.4	24.0		23.9	11670	58	40
38101000	710/50R26.5	SB	170D		TL	35		53.5	28.0		24.0	13200	58	40
38101600	800/45R26.5	SB	174D		TL	40		54.1	31.5		24.1	14800	58	40

GALAXY RADIAL SUPER SOFTEE I-2

OEM FITMENT

The Galaxy Radial Super Soft is perfect for pull-type agricultural implements. It is built with a large block type tread to maximize contact with the ground and reduce surface disruption and compaction.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
539943	750/60R26		175A8	TL	43	DW25	62.6	29.5	178.9	28.1	15212	58	25
539942	850/50R32		195A3	TL	38	DH27A	65.9	33.4	194	29.4	17600	48	25

GALAXY HONEY WAGON I-3

OEM FITMENT

The Galaxy Honey Wagon features exceptional flotation and rounded shoulders for minimal soil compaction. The Honey Wagon has been selected as an OEM fitment by several spreader manufacturers.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
558671	725X65-26		20	TL	38	DW25A	61.7	29.1	176	27.3	17400	45	25

VISIT YOKOHAMA-OHT.COM FOR DETAILED LOAD AND PRESSURE TABLES

Distributor:

Yokohama Off-Highway Tires (YOHT) is a division of The Yokohama Rubber Co., specializing in Agriculture, Forestry, Construction, Industrial, Material Handling, Earthmoving, Mining, Port and other commercial tires. YOHT sells its diverse product range, consisting of over 4,000 SKUs, in over 120 countries through its subsidiaries and channel partners. YOHT products are engineered to be application-specific and purpose-built. For more information visit www.yokohama-oht.com or email us at info@yokohama-oht.com.



Contact Yokohama Off-Highway Tires America, Inc. at (800) 343-3276 or (339) 900-8080 for your nearest Yokohama OHT Tire Dealer.

facebook.com/yokohamaohta

[@yokohamaohta](https://twitter.com/yokohamaohta)

yohta-blog.yokohama-oht.com

yokohama-oht.com