

DAIRY BUSINESS FAMILY TIRES FOR EVERY MACHINE ON THE DAIRY FARM



 **ALLIANCE**
ENGINEERED TO KEEP YOU AHEAD

GALAXY
APPLICATION SPECIFIC, PURPOSE BUILT.

PRECISION ENGINEERED FOR THE DAIRY FARM

Few types of farms demand as many different tires—or demand as much performance from them—as dairies. Moving feed ingredients. Maintaining facilities. In order to maneuver on concrete, packed soil, mud, manure, and more, dairy producers need purpose-built tires to maximize productivity and profitability.

The Alliance and Galaxy brands have a wide range of tires engineered and built to handle the real-world challenges of dairy production. Here's a selection.

SKID STEERS

GALAXY AT GRIP STEEL

RADIAL OTR

The steel-belted radial construction of the Galaxy AT Grip Steel delivers longer life and higher performance than bias-ply skid steer tires—plus better traction and a smoother ride. The contact patch is larger and more consistently distributed than bias-ply tires for longer, more even wear. Our unique flex dampening ring reinforces the sidewall and directs flexion toward the tire's shoulder for extra stability and durability, and minimizes bucking and bouncing. This is the time to switch to radial skid steer tires...and the Galaxy AT Grip Steel is the tire to switch to.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
139110	260/70R15	10R16.5	129A8/137A2	TL	27.7	8.25	30.8	10.3	93.1	14.3	4079	73	25
139111	300/70R16.6	12R16.5	137A8/145A2	TL	29.0	9.75	33.0	11.9	99.6	15.2	5070	73	25
139112	360/70R17.5	14R17.4	148A8/156A2	TL	32.1	10.50	37.4	13.7	112.0	17.0	6844	73	25



GALAXY MIGHTY TRAC ND L-4

With its deep, non-directional tread pattern and siped blocks, the Galaxy Mighty Trac ND is a 4-season performer that is equally surefooted on concrete, mud, or snow. With its cut-and-abrasion-resistant compound, rim protector, and reinforced sidewalls, the Mighty Trac ND is just as ready for concrete pads and curb collisions as it is for slick conditions.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
148260	10-16.5		10	TL	38	8.25	31.4	10.2	92	14.4	3500	40	5
148266	12-16.5		12	TL	43	9.75	33	12.1	98	15.1	4220	40	5
148378	14-17.5		14	TL	50	10.5	36.3	13.7	108	16.5	8540	80	5

GALAXY MUDDY BUDDY R-4

OEM FITMENT

With lugs 55% deeper than conventional R-4 bars, squared shoulders for grip, and wide channels for great self-cleaning, the Galaxy Muddy Buddy is the top skid steer tire for mud and manure. Protected from curb impacts and abrasions by a tough rim guard and constructed with abrasion-resistant compound for longer service life, the Muddy Buddy is tailor-made for slick dairy environments.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
144259	10-16.5		8	TL	42	8.25	30.7	10	91	13.9	3500	45	5
144264	12-16.5		10	TL	45	9.75	32.7	11.9	96	14.7	4220	40	5
144278	14-17.5		12	TL	46	10.5	36.3	13.7	107.5	16.5	8540	80	5

GALAXY BEEFY BABY III R-4

OEM FITMENT

The Galaxy Beefy Baby III is a classic for a reason. The durable hockey-stick-style lugs are reinforced with rugged tie bars for added stability. Center overlap ensures a smooth ride and long wear, while tough sidewalls and built-in rim shields protect against hazards. The Beefy Baby III is the dependable, durable backhoe tire that will never let you down.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
112259	10-16.5		8	TL	26	8.25	30.9	10.2	92	14.2	3500	45	5
112260	10-16.5		10	TL	26	8.25	30.9	10.2	92	14.2	3500	45	5
112264	12-16.5		10	TL	28	9.75	32.6	11.8	94	14.6	4220	40	5
112266	12-16.5		12	TL	28	9.75	32.7	12	95.4	14.8	4220	40	5
112276	14-17.5		10	TL	30	10.5	36.3	13.7	107.5	16.5	6850	55	5
112278	14-17.5		14	TL	30	10.5	36.3	13.7	107.5	16.5	8540	80	5



COMPACT UTILITY MACHINES

ALLIANCE 550 MULTI-USE STEEL BELTED

OEM FITMENT

The Alliance 550 Multi-use Radial is the most adaptable tire for compact utility machines. Its unique hybrid tread design arrays the extra biting edges of blocks in the curved, self-cleaning traction pattern of farm tire lugs. The result is outstanding traction on any surface or slope, great self-cleaning, and long wear—up to 30% longer life than many of the toughest tires on the market.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
55000040	265/70R16.5	10R16.5	130A2		TL	29	8.25	30.4	10.5	92.3	13.7	4180	58	5
55000012	305/70R16.5	12R16.5	141A5		TL	30	9.75	32.8	12.0	97.2	14.7	6130	58	5
55010470	340/80R18	12.5/80R18	143A8/138D		TL	31	DW11	39.4	13.5	118.2	17.7	6000	58	40
55010405	365/70R18		142A2/135B		TL	31	DW11	38.1	14.0	113.1	17.6	4940	54	30
55000055	405/70R18	16.0/70R18	153A2/141B		TL	33	W13	40.2	15.9	120.4	18.4	5670	54	30
55010535	340/80R20	12.5R20	144A8/140D		TL	31	DW11	41.4	13.5	124.1	18.9	5520	58	40
55001620	360/80R20		147A8/143D		TL	34	DW11	43.0	14.1	128.5	19.3	6800	58	40
55001510	400/70R20		149B		TL	33	DW13	42.0	15.9	125.2	19.0	7150	58	30
55000060	405/70R20	16.0/70R20	149B		TL	33	DW13	42.4	15.9	126.2	19.1	7150	58	30
55001615	340/80R24		140A8/135D		TL	31	W11	45.4	13.5	135.4	20.8	4800	46	40
55001406	360/80R24	13.6R24	143A8/138D		TL	32	W11	46.6	14.1	139.6	21.3	5200	46	40
55001710	400/80R24	14.9R24	149A8/144D		TL	34	W13	49.2	15.9	145.8	22.0	6170	46	40
55002475	420/65R24		151A8/146D		TL	33	W13	45.6	16.1	137.4	20.7	6600	46	40
55002025	440/80R24	16.9R24	154A8/149D		TL	34	W13L	51.7	17.4	156.1	23.3	7150	46	40
55000120	460/70R24	17.5LR24	159B		TL	34	W15L	49.2	18.4	149.0	22.4	9650	46	30
55005410	500/70R24	19.5LR24	164B		TL	36	W16L	51.5	19.9	154.4	23.3	11000	46	30
55024950	480/80R26	18.4R26	160B		TL	34	W16L	56.1	19.0	168.0	25.4	9900	46	30
55002610	440/80R28	16.9R28	156A8/151D		TL	34	W14L	55.8	17.3	166.9	25.2	7600	46	40
55002810	480/65R28		154A8/149D		TL	34	W15L	52.9	18.7	158.3	23.9	7150	46	40



LOADERS

GALAXY LDSR 300 E-3/L-3

RADIAL OTR

Stepped lugs add extra biting edges to this long-lasting loader tire. Radial construction creates a large, even footprint for stability, traction, and long wear. Chip-resistant compound adds to the durability of the Galaxy LDSR 300 and protects lugs from chunking and tearing, while S-shaped channels provide grip and excellent self-cleaning.



PRODUCT CODE	SIZE	ALT. SIZE	PLY/*	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
299694	17.5R25		**	182A2	TL	36	14	53.1	17.5	157.8	24.5	13120	94	25
299691	20.5R25		**	193A2	TL	40	17	58.8	21.1	171.7	26.1	17750	94	25
299698	23.5R25		**	201A2	TL	44	19.5	63.6	23.9	185.9	28.2	22380	94	25
299700	26.5R25		**	209A2	TL	49	22	68.3	26.7	185.9	29.7	28550	94	25
299702	29.5R25		**	216A2	TL	57	25	73.3	29.8	220.4	32.3	34650	94	25

GALAXY LDSR 510 L-5

The all-steel Galaxy LDSR 510 features extra-deep tread blocks and cut-resistant compound to deliver added performance on rock, gravel, and other tough surfaces—as well as outstanding traction in both forward and reverse. High turn-up construction reinforces the sidewalls for extra stability and durability, while still delivering the large, even footprint that puts your loader's horsepower to the ground.



PRODUCT CODE	SIZE	ALT. SIZE	PLY/*	PR/LI	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
363694	17.5R25		**	182A2	TL	81.8	14.0/1.5-25	55.3	17.5	163.3	25.0	18700	94	10
363696	20.5R25		**	193A2	TL	93.5	17.00/2.0-25	60.9	21.1	179.1	27.0	25400	94	10
363698	23.5R25		**	201A2	TL	102.6	19.5/2.5-25	65.4	24.1	191.3	28.8	27558	94	10

GALAXY MIGHTY TRAC ND L-4

The design and compound that make the Galaxy Mighty Trac ND an ideal skid steer tire also make it indispensable for backhoe loaders. The blocks of the Mighty Trac ND are more concentrated in the center of the tread for longer wear and a smoother ride, and farther apart on the edges for better self-cleaning. Plus, the stepped blocks and extra voids on the shoulder provide more bite when you need it.



PRODUCT CODE	SIZE	ALT. SIZE	PLY/*	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
148288	12.5/80-18			12	TL	37.8	W9	38.8	12.2	113.3	17.9	5840	54	25
148440	19.5L-24			14	TL	35.5	DW16L	51.7	19.5	152.6	23.5	8270	38	25

GALAXY BEEFY BABY III R-4

OEM FITMENT

The Galaxy Beefy Baby III is a classic for a reason. The durable hockey-stick-style lugs are reinforced with rugged tie bars for added stability. Center overlap ensures a smooth ride and long wear, while tough sidewalls and built-in rim shields protect against hazards. The Beefy Baby III is the dependable, durable backhoe tire that will never let you down.



PRODUCT CODE	SIZE	ALT. SIZE	PLY/*	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
112072	26x12D380			8	TL	23	10	26.5	11.9	79.1	12.2	3080	42	5
112301	315/55D20			12	TL	25	11	32.8	12.5	97.9	15.2	7600	80	5
112273	33X15.50-16.5			14	TL	25	12	33.9	15.4	101.3	15.5	7400	80	5
112300	355/55D625			14	TL	25	11.75	37.1	13.9	114	17.4	9100	75	5
112297	15-19.5			14	TL	31.5	11.75	40.1	15.3	125.6	18.2	9920	70	5
112254	15-19.5			16	TL	31.5	11.75	40.1	15.3	118.5	17.4	10745	80	5
112296	15-625			16	TL	25	13	40.4	15.4	123.6	18.9	12300	100	5
112307	18-625			16	TL	28	15	41.4	17.1	125.2	19.3	15200	100	5
112924	445/50D710			18	TL	30	15	46.6	17.1	141.5	21.5	16100	100	5

TRACTORS

ALLIANCE AGRI STAR II 470 - 485

OEM FITMENT

The first thing most people notice about the Alliance Agri Star II is its stratified lug—marked by a single-angle bar lug on top of a broader, multi-angle one to deliver more biting edges and long service life. Those lugs are overlapped in the center of the tread for a stable ride, reinforced with dual step-tie bars to minimize shuffling, and supported by a high-stability polyester casing. Whether it's pulling feed wagons, packing silage, or lifting a heavy bucket in the yard, the Agri Star II delivers top performance.



PRODUCT CODE	SIZE	ALT. SIZE	PLY/*	PR/LI	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
47000037	260/70R16			109D	TL	39	W9	30.6	10.3	92.0	14.1	2270	35	40
47000003	280/70R16			112D	TL	40	W9	31.7	11.2	94.2	14.5	2469	35	40
47000000	280/70R18			114D	TL	40	W9	33.7	11.2	100.2	15.4	2601	35	40
47000033	280/70R20			116D	TL	40	W9	35.7	11.2	107.5	16.6	2756	35	40
47000027	300/70R20			120D	TL	43	W9	37.6	11.8	112.9	17.2	3086	35	40
47000039	320/70R20			123D	TL	44	W10	38.8	12.7	115.9	18.0	3410	35	40
48500022	320/85R20			119D	TL	54	W10	41.5	13.1	121.8	18.6	3000	23	40
47000035	360/70R20			129D	TL	53	W12	41.2	14.2	120.7	18.4	4079	35	40
47000008	380/70R20			122D	TL	57	W12	42.8	15.2	125.0	19.1	3307	23	40
48500020	280/85R24			115D	TL	53	W9	42.9	11.9	126.6	19.5	2680	23	40
47000034	320/70R24			116D	TL	52	W10	43.2	12.7	127.4	20.0	2756	23	40
48500025	320/85R24			122D	TL	54	W10	45.5	13.1	133.8	20.3	3305	23	40
48500101	320/85R24			142D	TL	54	W10	45.5	13.1	133.8	20.3	5840	67	40
48500035	340/85R24			125D	TL	57	W12	46.9	14.0	137.6	20.9	3640	23	40
47000026	360/70R24			122D	TL	53	W12	45.5	14.2	133.9	20.7	3300	23	40
47000001	380/70R24			125D	TL	57	W12	47.0	15.2	137.0	21.6	3630	23	40
48500047	380/85R24			131D	TL	58	W12	49.6	15.2	144.4	22.7	4300	23	40
47000005	420/70R24			130D	TL	59	W13	49.2	16.7	145.3	22.0	4190	23	40
48500165	420/85R24			137D	TL	63	W13	52.3	17.4	152.7	23.3	5070	23	40
47000013	480/70R24			138D	TL	64	DW16	52.1	19.0	151.9	23.1	5203	23	40
48500021	280/85R28			118D	TL	53	W9	46.9	11.9	138.3	21.2	2910	23	40
48500026	320/85R28			124D	TL	54	W10	49.5	13.1	142.1	22.2	3525	23	40
48500040	340/85R28			127D	TL	57	W12	50.9	14.0	150.9	22.8	3860	23	40
47000030	380/70R28			127D	TL	57	W12	51.0	15.2	149.4	23.4	3850	23	40
48500070	380/85R28			133D	TL	58	W12	53.5	15.2	157.6	23.8	4550	23	40
47000002	420/70R28			133D	TL	59	W13	53.3	16.7	149.4	24.4	4540	23	40
48500190	420/85R28			139D	TL	63	W13	56.3	17.4	164.9	24.8	5357	23	40
47000025	480/70R28			151D	TL	64	DW16	56.1	19.0	165.8	25.3	7606	45	40
47000029	480/70R28			140D	TL	64	DW16	56.1	19.0	165.8	25.3	5510	23	40
47000022	600/70R28			161D	TL	69	DW18	61.2	24.2	181.5	27.4	10196	40	40
48500071	380/85R30			135D	TL	58	W12	55.5	15.2	161.8	24.8	4806	23	40
47000009	420/70R30			134D	TL	59	W13	55.2	16.7	162.0	25.0	4674	23	40
48500200	420/85R30			140D	TL	63	W13	58.1	17.4	170.5	25.9	5510	23	40
48500140	460/85R30			145D	TL	67	DW16	60.8	18.9	178.3	26.9	6395	23	40
47000018	480/70R30			156D	TL	64	DW16	58.3	19.0	173.7	26.1	8818	55	40
47025030	480/70R30			150D	TL	64	DW16	58.3	19.0	173.7	26.1	7385	41	40
47000032	480/70R30			141D	TL	64	DW16	58.3	19.0	173.7	26.1	5670	23	40
47000007	600/70R30			152D	TL	69	DW18	63.2	24.2	185.4	27.8	7820	41	40
48500032	320/85R32			126D	TL	54	W10	53.5	13.1	157.9	24.6	3750	23	40
47000028	480/70R34			143D	TL	64	DW16	62.2	19.0	184.1	28.6	6010	23	40
47000041	520/70R34			148D	TL	69	DW16	64.6	20.5	191.1	29.3	6945	23	40
47001541	480/70R34			155D	TL	64	DW16	62.2	19.0	183.7	28.6	8543	47	40
47025034	520/70R34			148D	TL	69	DW16	64.6	20.5	190.0	29.1	12346	64	40
48500037	380/85R34			137D	TL	58	W12	59.4	15.2	175.4	26.8	5070	23	40
48504730	420/85R34			147D	TL	63	W14	62.1	17.4	184.9	28.1	6780	35	40
48500100	420/85R34			142D	TL	63	W14	62.1	17.4	180.7	28.1	5840	23	40
48500145	460/85R34			147D	TL	67	DW16	64.8	18.9	190.7	28.9	6780	23	40
48500151	460/85R34			157D	TL	67	DW16	64.8	18.9	190.7	28.9	9095	44	40
48500033	320/85R36			128D	TL	54	W10	57.5	13.1	170.3	26.6	3970	23	40
48500044	340/85R36			132D	TL	57	W12	58.9	14.0	170.7	27.1	4410	23	40

CONTINUED ON NEXT PAGE

ALLIANCE AGRI STAR II 470 - 485 (CONTINUED)

PRODUCT CODE	SIZE	PLY/*	PLY/*	PR/LI	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
48500031	320/85R38			143D	TL	54	W10	59.5	13.1	178.4	27.6	6010	52	40
48500046	340/85R38			133D	TL	57	W12	60.9	14.0	184.1	28.1	4540	23	40
48500048	340/85R38			151D	TL	57	W12	60.9	14.0	184.1	28.1	7605	64	40
48500120	380/80R38			142D	TL	58	W12	62.0	15.2	185.9	28.7	5840	35	40
48500121	380/80R38			152D	TL	58	W12	62.0	15.2	183.0	28.7	7825	58	40
48500130	420/85R38			144D	TL	63	W13	66.1	17.4	195.8	30.3	6175	23	40
48500160	460/85R38			149D	TL	67	DW16	68.8	18.9	202.8	30.8	7165	23	40
48500167	460/85R38			167D	TL	67	DW16	68.8	18.9	202.8	30.8	12015	64	40
47000038	480/70R38			145D	TL	64	DW16	66.2	19.0	195.9	30.6	6390	23	40
47000004	520/70R38			150D	TL	69	DW16	68.9	20.5	203.7	30.9	7380	23	40
48500300	520/85R38			155D	TL	69	DW16	72.8	20.5	215.6	32.7	8545	23	40
48500301	520/85R38			169D	TL	69	DW16	72.8	20.5	215.6	32.7	12785	52	40
47000011	580/70R38			180D	TL	71	DW18	71.9	22.8	214.0	32.7	17637	80	40
47000031	580/70R38			155D	TL	71	DW18	71.9	22.8	214.0	32.7	8540	23	40
47000024	580/70R38			170D	TL	71	DW18	71.9	22.8	214.0	32.7	13228	58	40
48500125	650/85R38			173D	TL	77	DW20	81.6	26.8	237.5	36.8	14330	35	40
47002588	710/70R38			178D	TL	77	DW25B	77.1	28.3	227.6	33.1	16535	49	40
47000040	710/70R38			172D	TL	77	DW25B	77.1	28.3	227.6	33.1	13880	35	40
48500325	480/80R42			156D	TL	68	DW16	72.0	19.4	213.1	33.1	7605	23	40
48500326	480/80R42			169D	TL	68	DW16	72.0	19.4	213.1	33.1	12785	64	40
48500110	520/85R42			157D	TL	69	DW16	76.9	20.5	227.4	35.0	9095	23	40
48500334	520/85R42			169D	TL	69	DW16	76.9	20.5	227.4	35.0	12785	52	40
47000006	710/70R42			173D	TL	77	DW25B	81.1	28.3	244.2	37.5	14320	35	40
48500260	480/80R46			158D	TL	68	DW16	77.2	19.4	231.2	35.8	9370	35	40
48500360	520/85R46			158D	TL	69	DW16	80.9	20.5	238.3	36.9	9370	23	40
48500264	480/80R50			159D	TL	68	DW16	81.1	19.4	241.1	37.7	9645	35	40



ALLIANCE 550 MULTI-USE STEEL BELTED

OEM FITMENT



The innovative hybrid tread design of the Alliance 550 Multi-use Radial makes it an ideal choice for tractors working on concrete or packed soil—in other words, the perfect tire for utility tractors on dairies. This is the tire for all-season traction, long service life, and the smooth ride you expect from top-quality radials...plus the extra service life that makes it a boost to your bottom line.

PRODUCT CODE	SIZE	ALT. SIZE	PLY/*	PR/LI	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
55000042	250/75R16			120G	TL	20	W8	30.7	10.0	92.2	14.2	3080	65	55
55000035	250/80R16			126A8/123D	TL	22	W8	32.0	10.6	97.2	14.7	3420	64	40
55010470	340/80R18	12.5/80R18		143A8/138D	TL	31	DW11	39.4	13.5	118.2	17.7	6000	58	40
55010405	365/70R18			142A2/135B	TL	31	DW11	38.1	14.0	113.1	17.6	4940	54	30
55001480	400/70R18			147A8/144D	TL	33	W13	40.2	15.9	120.4	18.4	6150	58	40
55001617	360/70R20			129A8/124D	TL	31	DW11	41.4	14.0	122.9	18.6	3520	35	40
55001450	300/80R24			133A8/128D	TL	32	W9	43.0	11.6	127.5	19.8	3860	46	40
55001615	340/80R24			140A8/135D	TL	31	W11	45.4	13.5	135.4	20.8	4800	46	40
55001406	360/80R24	13.6R24		143A8/138D	TL	32	W11	46.6	14.1	139.6	21.3	5200	46	40
55001710	400/80R24	14.9R24		149A8/144D	TL	34	W13	49.2	15.9	145.8	22.0	6170	46	40
55002025	440/80R24	16.9R24		154A8/149D	TL	34	W13L	51.7	17.4	156.1	23.3	7150	46	40
55000025	460/65R24			156A8/151D	TL	34	W15L	47.6	17.9	141.6	21.5	7600	46	40
55002400	480/65R24			151A8/146D	TL	37	W15L	48.8	18.9	146.9	22.1	6600	46	40
55005330	540/65R24	21LR24		158A8/154D	TL	39	W18L	51.7	21.3	155.6	23.3	8250	46	40
55002360	400/80R28	14.9R28		151A8/146D	TL	34	W13L	53.2	15.9	159.1	24.3	6600	46	40
55002610	440/80R28	16.9R28		156A8/151D	TL	34	W14L	55.8	17.3	166.9	25.2	7600	46	40
55002810	480/65R28			154A8/149D	TL	34	W15L	52.9	18.7	158.3	23.9	7150	46	40
55005390	540/65R28			160A8/155D	TL	39	W18L	55.6	21.7	168.0	25.6	8550	46	40
55002625	440/80R30			157A8/153D	TL	34	W14L	57.8	17.1	174.6	26.4	8050	46	40
55003015	480/80R30	18.4R30		162A8/157D	TL	35	W15L	60.3	18.5	181.7	27.4	9100	46	40
55005510	540/65R30			161A8/156D	TL	38	DW18A	57.6	21.7	176.4	26.7	8800	46	40
55005910	600/70R30			161A8/158D	TL	38	DW20A/B	63.1	24.1	188.7	28.6	9350	35	40
55002760	440/80R34	16.9R34		159A8/155D	TL	36	W14L	61.7	17.4	186.5	28.3	8550	45	40
55003310	480/80R34	18.4R34		164A8/159D	TL	34	W15L	64.3	18.9	192.6	29.1	8550	46	40
55005352	480/80R38	18.4R38		166A8/161D	TL	34	W15L	68.0	18.9	204.6	30.9	10200	46	40
55005810	540/80R38	20.8R38		172A8/167D	TL	38	DW18A	71.8	21.5	216.4	32.8	12000	46	40
55005860	600/65R38			170A8/166D	TL	38	DW18A	68.9	23.3	207.5	31.2	11700	46	40
55006700*	650/65R38			175A8/170D	TL	40	DW20A/B	71.4	25.4	214.6	32.2	13200	46	40
55006725	650/85R38			181A8/177D	TL	40	DW23B	81.4	26.5	245.3	35.9	18170	35	40
55007030	620/80R42			181A8/177D	TL	45	DW20A/B	80.9	25.4	242.9	37.3	16100	46	40
55007160	650/65R42			176A8/171D	TL	40	DW20A/B	75.3	25.4	227.0	34.3	13600	46	40
55007180	710/70R42			181A8/177D	TL	45	DW23A/B	80.8	28.2	243.6	37.0	16100	41	40

MORE OPTIONS

The Yokohama Off-Highway Tires lineup covers more than 4,000 patterns, sizes, and SKUs. That means there is an Alliance or Galaxy tire purpose-built for any challenge on your dairy operation, from spraying crops to spearing hay, cleaning alleys, loading feed mixers, or hauling manure. Ask your tire dealer about Alliance and Galaxy tires, call us at (800) 343-3276, or visit www.yokohama-oh.com for more information.

VISIT YOKOHAMA-OHT.COM FOR DETAILED LOAD AND PRESSURE TABLES

Distributor:

Yokohama Off-Highway Tires (YOHT) is a division of The Yokohama Rubber Co., specializing in Agriculture, Forestry, Construction, Industrial, Material Handling, Earthmoving, Mining, Port, and other commercial tires. YOHT sells its diverse product range, consisting of over 4,000 SKUs, in over 120 countries through its subsidiaries and channel partners. YOHT products are engineered to be application-specific and purpose-built. For more information, visit www.yokohama-oh.com or email us at info@yokohama-oh.com.



Contact Yokohama Off-Highway Tires America, Inc. at (800) 343-3276 or (339) 900-8080 for your nearest Yokohama OHT Tire Dealer.

facebook.com/yokohamaohta

[@yokohamaohta](https://twitter.com/yokohamaohta)

yohta-blog.yokohama-oh.com

yokohama-oh.com