



EARTHPRO RADIAL TIRES HIGH QUALITY TIRES FOR SUPERIOR PERFORMANCE.



- Multi-angled lug pattern for traction both on- and off-road
- Aggressive shoulder for better grip and reduced slippage
- Lugs overlap at the centerline for smoother road performance and extended tire life
- Raised inter-lug pads prevent mud caking and provide better performance and traction



GALAXY
APPLICATION SPECIFIC, PURPOSE BUILT.

GALAXY EARTHPRO RADIAL

The Galaxy EarthPRO Radial has a modern multi-angled lug design which makes it suitable for on- and off-road applications. This pattern offers excellent traction and self-cleaning during field operations and a comfortable ride for operators on the road. Its superior compound provides resistance to cut growth and its wide nose bar and central overlapping lugs help in maintaining even wear, resulting in a longer tire life.

65 SERIES

PRODUCT CODE	SIZE	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
525571	480/65R24	140D	TL	58	W15L	48.8	18.9	147.6	21.9	5510	35	40
525556	480/65R28	142D	TL	58	W15L	52.6	18.9	157.7	24.4	5840	35	40
525572	540/65R28	149D	TL	63	W16L	55.6	21.7	170.3	24.9	7160	35	40
525563	600/65R28	154D	TL	60	W18L	58.3	23.3	175.6	26.3	8260	35	40
525570	540/65R30	150D	TL	63	W16L	58.5	21.7	177.3	26.6	7380	35	40
525561	540/65R38	153D	TL	63	W16L	65.9	21.1	200.4	30.2	8040	35	40
525558	600/65R38	159D	TL	60	W18L	68.9	23.3	212.7	31.5	9640	35	40
525555	650/65R38	171D	TL	64	DW20B	72.2	25.4	197.2	28.9	13550	51	40
525557	650/65R42	170D	TL	66	DW20B	76.4	26.2	232.9	35.2	13220	46	40

75 SERIES

PRODUCT CODE	SIZE	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
575764	280/70R20	116A8/B	TL	41	W9	35.9	10.9	106.5	16.3	2760	35	30
575758	300/70R20	120A8/B	TL	41	W10	37.6	11.5	111.5	17.1	3080	35	30
575759	320/70R20	123A8/B	TL	42	W10	38.8	12.8	114.5	17.5	3420	35	30
575778	320/70R24	116A8/B	TL	51	W10	43.1	12.6	127.1	19.6	2760	23	30
575779	360/70R24	122A8/B	TL	52	W11	45.2	14.1	133.3	20.6	3300	23	30
575780	380/70R24	125A8/B	TL	53	W12	46.9	15	138.2	21.2	3640	23	30
575781	420/70R24	130A8/B	TL	54	W13	49.1	16.5	144.9	22.1	4180	23	30
580792	480/70R24	138A8/B	TL	58	W15L	51.8	18.9	151.9	23.1	5200	23	30
575782	320/70R28	119A8/B	TL	51	W10	46.9	12.6	138.4	21.5	3000	23	30
575783	360/70R28	125A8/B	TL	52	W11	48.8	14.1	144	22.5	3640	23	30
575784	380/70R28	127A8/B	TL	53	W12	50.9	15	150.2	23.2	3860	23	30
570785	420/70R28	133A8/B	TL	54	W13	53.1	16.5	156.7	24.1	4540	23	30
575786	480/70R28	140A8/B	TL	58	W15L	55.7	18.9	164.3	25.2	5520	23	30
575787	420/70R30	134A8/B	TL	54	W13	55	16.5	162.4	25	4680	23	30
575788	480/70R30	141A8/B	TL	58	W15L	58.2	18.9	171.7	26.3	5680	23	30
575789	520/70R30	145A8/B	TL	59	W16L	60.5	20.3	178.4	27.2	7600	23	30
575790	480/70R34	143A8/B	TL	58	W15L	62.2	18.9	183.5	28.3	6000	23	30
575791	520/70R34	148A8/B	TL	59	W16L	64.6	20.3	190.5	29.3	6950	23	30
575794	480/70R38	145A8/B	TL	58	W15L	66.2	18.9	195.2	30.3	6400	23	30
575796	480/70R38	155A8/B	TL	58	W15L	66.2	18.9	195.2	30.3	8550	23	30
536795	520/70R38	150A8/B	TL	59	W16L	69.1	20.3	203.8	31.4	7400	23	30
570785	710/70R38	133A8/B	TL	54	DW23	53.1	16.5	157.1	24.1	4540	23	25
517999	710/70R42	173A8/B	TL	74	DW23	81.1	28.2	239.4	36.9	14300	35	25

80/85 SERIES

PRODUCT CODE	SIZE	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
536028	280/85R20	112A8/B	TL	48	W10	38.7	11.3	114.7	17.6	2400	23	30
536029	320/85R20	119A8/B	TL	50	W11	41.1	13	121.8	18	3000	23	30
536766	280/85R24	115A8	TL	49	W9	42.8	10.6	129	19.5	2680	23	30
536767	320/85R24	122 A8	TL	52	W10	45.2	13.2	134	20.3	3300	23	30
536768	340/85R24	125 A8	TL	53	W11	46.5	14	138	20.9	3640	23	30
536769	380/85R24	131A8	TL	57	W12	49.3	15.2	145	21.9	4300	23	30
536931	420/85R24	131A8	TL	60	W13	52.1	16.7	151	22.8	4300	23	30
536770	320/85R28	133 A8	TL	52	W10	49.1	12.8	147	22.2	3520	23	30
536771	340/85R28	127A8/B	TL	53	W11	51	14.2	151	22.8	3860	23	30
536772	380/85R28	133A8	TL	57	W12	53.4	15	157	157	4540	23	30
536906	420/85R28	139A8	TL	60	W13	56.1	16.5	164	24.8	5360	23	30
536928	380/85R30	135A8	TL	57	W12	55.4	14.7	164	24.8	4800	23	30
536773	420/85R30	140A8/B	TL	60	W13	57.8	17	171	25.9	5520	23	30
536836	460/85R30	145A8/B	TL	64	W14	60.4	18.7	178	26.9	6400	23	30
536306	320/85R32	136A8	TL	50	W10	53.4	12.8	158.1	24.6	3740	23	30
536932	380/85R34	137A8	TL	57	W12	59.4	15	177	26.8	5080	23	30
536774	420/85R34	140A8/B	TL	57	W13	62.4	16.5	186	28.1	5840	23	30
536775	460/85R34	147A8	TL	64	W14	64.8	17.9	189	28.7	6800	23	30
536324	320/85R36	128A8	TL	50	W11	57.4	12.8	169.9	26.6	3960	23	30
536833	340/85R36	132A8	TL	52	W12	58.9	13.6	174.2	27.1	4400	23	25
536326	320/85R38	143A8	TL	50	W10	59.4	12.8	178.4	27.6	6000	52	25
536030	340/85R38	133A8	TL	50	W12	60.7	13.6	179.8	28.1	4540	23	25
536933	380/80R38	142 A8/142 B	TL	58	W12	62.1	14.8	185.9	28.7	5840	35	25
536776	420/85R38	144A8	TL	57	W13	66.1	16.3	197	29.8	6150	23	30
536777	460/85R38	149A8	TL	64	W14	68.8	17.9	203	30.8	7150	23	30
536837	520/85R38	155A8	TL	68	W16A	72.8	20.7	216	32.7	8550	23	30
536934	320/80R42	141A8/B	TL	53	W10	62.2	12.6	184.1	29.1	5677	46	25
536904	480/80R42	151A8	TL	66	W16A	72.2	18.9	215	32.6	7600	23	30
536935	520/85R42	157A8/B	TL	68	W16A	76.8	20.3	227	34.4	9100	23	30
536996	480/80R46	158A8	TL	66	W16A	76.2	18.9	228	34.6	9350	23	30
536997	520/85R46	158A8	TL	68	W16L	80.8	20.3	240	36.4	9350	23	30
494663	480/80R50	159D	TL	66	W15L	81.1	18.9	242.4	37.3	9640	35	40

Highlighted sizes represent recently added rear tires for popular front/rear combinations

90 SERIES

PRODUCT CODE	SIZE	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
536929	420/90R30	147A8	TL	60	W13	59.8	16.5	176.3	26.9	6800	23	30
538323	320/90R42	147A8	TL	53	W10	64.7	12.6	194.5	30.1	6800	52	30
536922	320/90R46	148A8/B	TL	54	W10	68.7	12.6	212	32.1	6950	52	30
536918	380/90R46	165A8	TL	59	W13B	72.9	15	221	33.5	10700	68	30

GALAXY EARTHPRO RADIAL INNOVATIVE TREAD DESIGN

The Galaxy EarthPro Radial tire has a highly versatile and modern design providing excellent road wear and ride comfort while at the same time providing high traction in the field. The pads between the lugs act as mud breakers. Also, the reinforced lug and bead areas and improved tread compound provide exceptional working life.



- Performs well for on and off-road applications
- Excellent self-cleaning
- Low road noise with a comfortable ride

TREAD DESIGN

- Multi-angled lug pattern for on and off-road performance
- High traction
- Drive comfort

AGGRESSIVE SHOULDER

- Better grip
- Improved traction



OVERLAPPING CENTRAL LUG

- Better road performance
- Long tire life

MUD EJECTORS

- Excellent self-cleaning

VISIT YOKOHAMA-OHT.COM FOR DETAILED LOAD AND PRESSURE TABLES

Distributor:

Yokohama Off-Highway Tires (YOHT) is a division of The Yokohama Rubber Co., specializing in Agriculture, Forestry, Construction, Industrial, Material Handling, Earthmoving, Mining, Port and other commercial tires. YOHT sells its diverse product range, consisting of over 4,000 SKUs, in over 120 countries through its subsidiaries and channel partners. YOHT products are engineered to be application-specific and purpose-built. For more information visit www.yokohama-oht.com or email us at info@yokohama-oht.com.



Contact Yokohama Off-Highway Tires America, Inc. at (800) 343-3276 or (339) 900-8080 for your nearest Yokohama OHT Tire Dealer.

