

# **OTR G2-E3 FAMILY**

# **SPECIALLY**

# **ENGINEERED FOR**

# **HIGH PERFORMANCE**



**GALAXY**  
APPLICATION SPECIFIC, PURPOSE BUILT.



## GALAXY SLG II G-2

The Galaxy SLG II features an aggressive tread design and self-cleaning characteristics that provide excellent traction in mud and dirt.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
286428	1600-24		16	TL	36	10	57.5	16.8	171.3	26.4	8050	51	25

## GALAXY EXR300 ROCK LUG E-3/L-3

**OEM FITMENT**

The Galaxy EXR300 Rock Lug is designed to provide heavy-duty traction and resistance to slippage. Galaxy engineers designed this tire with a deeper tread depth than the standard E-3/L-3 giving the Rock Lug a longer wear life.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
344418	1400-24		28	TT	32	10	53.5	14.6	161	24.7	22000	134	5
344452	14.00-25		20	TL	31	10	53.9	14.8	160	24.7	18740	102	6
344450	1400-25		28	TL	32	10	53.9	14.6	161	24.7	22000	134	5
344451	15.5-25		12	TL	31	12/1.3	50.3	15	147.8	22.6	12300	58	5
344458	17.5-25		16	TL	34	14/1.5	53.1	17.4	156	23.8	16100	69	5
344459	17.5-25		20	TL	34	14/1.5	53.3	17.4	156	23.8	18200	83	5
344217	17.5-25		24	TL	36	14/1.5	53.1	17.5	161	24.2	20400	105	5
344468	20.5-25		16	TL	38	17/2.0	58.3	21.2	168.7	25.8	18200	51	5
344469	20.5-25		20	TL	38	17/2.0	58.3	21.2	168.7	25.8	20900	65	5
344470	20.5-25		24	TL	38	17/2.0	58.3	21.2	163.3	25	22700	76	5
344478	23.5-25		20	TL	43	19.5/2.5	63.8	23.9	183	27.8	24000	54	5
344662	23.5-25		28	TL	43	19.5/2.5	63.8	23.9	183	27.8	30000	80	5
344485	26.5-25		28	TL	44	22/3.0	67.6	26.2	193	29.5	34200	69	5
344492	29.5-25		28	TL	52	25/3.5	73.2	29.2	208	31.8	38600	62	5

## GALAXY HIPPO E-2/L-2

**OEM FITMENT**

The Galaxy Hippo is designed for performance in soft and wet soil conditions. The tires are designed for operation in conditions where extra flotation is required and, in many cases can eliminate the need for expensive and cumbersome tracks.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
276469	20.5-25		20	TL	62	17/2.5	58.7	19.4	179.2	27	20900	65	5
275478	23.5-25		20	TL	67	19.5/2.5	64.5	24.8	186.6	28	24000	54	5
275477	23.5-25		24	TL	67	19.5/2.5	63.3	22.2	186.9	28.3	27550	69	5
276482	26.5-25		20	TL	71	22/3.0	66.2	29.5	190.6	29.5	29100	51	5

**VISIT YOKOHAMA-OHT.COM FOR DETAILED LOAD AND PRESSURE TABLES**

Distributor:

Yokohama Off-Highway Tires (YOHT) is a division of The Yokohama Rubber Co., specializing in Agriculture, Forestry, Construction, Industrial, Material Handling, Earthmoving, Mining, Port and other commercial tires. YOHT sells its diverse product range, consisting of over 4,000 SKUs, in over 120 countries through its subsidiaries and channel partners. YOHT products are engineered to be application-specific and purpose-built. For more information visit [www.yokohama-oht.com](http://www.yokohama-oht.com) or email us at [info@yokohama-oht.com](mailto:info@yokohama-oht.com).



Contact Yokohama Off-Highway Tires America, Inc. at (800) 343-3276 or (339) 900-8080 for your nearest Yokohama OHT Tire Dealer.

[facebook.com/yokohamaohta](https://www.facebook.com/yokohamaohta)

[@yokohamaohta](https://twitter.com/yokohamaohta)

[yohta-blog.yokohama-oht.com](http://yohta-blog.yokohama-oht.com)

[yokohama-oht.com](http://yokohama-oht.com)