

# GALAXY HULK/JUMBO HULK EXTRA-DEEP CONSTRUCTION TIRE FOR SEVERE APPLICATIONS



- Unique large-block tread design provides long, even wear on hard surfaces and in severe applications
- Special cut-resistant compound for longer tire life
- Extra-deep tread pattern helps prevent punctures and downtime
- Reinforced sidewall protects against cuts and snags
- Sidewall rim protector helps minimize wheel damage

L4/L5

M



S



**GALAXY**  
APPLICATION SPECIFIC, PURPOSE BUILT.

# GALAXY HULK L-5

OEM FITMENT

The Galaxy Hulk has a unique tread pattern that allows it to operate in severe applications while providing superior self-cleaning. The Hulk has a minimum tread depth of 44/32nds and a lug-to-void ratio of 68:32. As a result, the Hulk will provide long wear and reduce downtime caused by cuts and punctures. It is also built with special cut- and chip-resistant compounds for durability.



PRODUCT CODE	SIZE	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
133260	10-16.5	10	TL	44	8.25	31.4	10.2	92	14.4	3500	45	5
133266	12-16.5	12	TL	44	9.75	33	12.1	96	15.1	4220	40	5
133278	14-17.5	14	TL	46	10.5	36.8	14.1	108	16.8	8550	80	5
133273	33X15.50-16.5	14	TL	44	12	33.1	15.1	100	15.1	4800	35	5
202289	12.5/80-18	14	TL	44	9	38	12	111	17	4400	48	25
202562	16.9-30	14	TL	50	W15L	57.4	17.3	160	24.5	8550	44	25
202723	18.4-26	14	TL	52	W16L	56.2	18.5	165	25.3	9900	42	25

# GALAXY JUMBO HULK L-4

Because of its deep tread and high solid-to-void ratio, the Galaxy Jumbo Hulk L-4 provides extraordinary hours of service and reduces downtime due to cuts and punctures. Its unique tread pattern allows it to operate in severe conditions while providing superior self-cleaning characteristics. This is a very reliable tire that does not overheat under extensive use on the road.



PRODUCT CODE	SIZE	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
202432	16.9-24	12	TL	48	W15L	51	16.8	152	23.1	7150	38	25
202440	19.5L-24	14	TL	48	W16L	51.1	19.3	153	23.2	8250	38	25
202443	21L-24	16	TL	50	DW18A	54.3	21	162	24.6	9899	41	25
202723	18.4-26	14	TL	50	W16L	56.2	18.5	165	25.3	9900	42	25
202831	16.9-28	14	TL	50	W15L	55.3	17.3	163	24.9	8550	44	25
202562	16.9-30	14	TL	50	W15L	57.4	17.3	160	24.5	8550	44	25

## TREAD PATTERN



Extra-deep tread and big-block design for long, even wear

## SIDEWALL ANALYSIS



Sidewall rim protection for less wheel damage



VISIT [YOKOHAMA-OHT.COM](http://YOKOHAMA-OHT.COM) FOR DETAILED LOAD AND PRESSURE TABLES

Distributor:

Yokohama Off-Highway Tires (YOHT) is a division of The Yokohama Rubber Co., specializing in Agriculture, Forestry, Construction, Industrial, Material Handling, Earthmoving, Mining, Port and other commercial tires. YOHT sells its diverse product range, consisting of over 4,000 SKUs, in over 120 countries through its subsidiaries and channel partners. YOHT products are engineered to be application-specific and purpose-built. For more information visit [www.yokohama-oht.com](http://www.yokohama-oht.com) or email us at [info@yokohama-oht.com](mailto:info@yokohama-oht.com).



Contact Yokohama Off-Highway Tires America, Inc. at (800) 343-3276 or (339) 900-8080 for your nearest Yokohama OHT Tire Dealer.

