

**RADIAL TRACTOR FAMILY
ENGINEERED TO
PERFORM ON A
WIDE RANGE OF
APPLICATIONS**



AGRIFLEX+ 354 STEEL BELTED R-1W

OEM FITMENT



The Alliance Agriflex+ 354 has state-of-the-art materials and the steel-belted construction allow VF (Very High Flexion) and IF (Increased Flexion) radial tractor tires to deliver outstanding performance in any conditions. VF tires carry 40% more load on the same inflation pressure as conventional radials, or require 40% less inflation pressure for the same load, to reduce soil compaction. IF tires carry 20% more load on the same inflation pressure as conventional radials, or require 20% less inflation pressure for the same load. (TUBELESS - STEEL BELTED - STUBBLE GUARD)

PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
35410005	VF 380/85R30	14.9R30	146D		TL	59	DW13	55.6	15.5	163.9	24.6	6610	29	40
35400105	VF 420/90R30		153D		TL	62	DW13	59.8	17.7	176.6	26.3	8040	29	40
35400224	VF 320/85R32		139D		TL	56	W11	53.4	12.6	158.1	24.2	7490	23	40
35400028	VF 320/85R34		143D		TL	56	W11	55.7	12.8	166.0	25.3	8410	29	40
35400009	VF 380/85R34	14.9R34	149D		TL	59	DW13	60.0	15.6	177.3	26.7	7160	29	40
35450109	VF 420/85R34		159D		TL	60	DW14L	62.0	16.4	183.5	27.7	9640	35	40
35400017	VF 480/70R34		160D		TL	59	DW16L	62.2	19.5	185.8	28.1	9910	44	40
35400031	VF 320/85R38		155D		TL	56	W11	59.3	12.6	178.1	27.3	8540	52	40
35400002	VF 380/80R38	14.9R38	154D		TL	59	DW13	62.6	15.0	185.4	28.5	8260	35	40
35450004	VF 380/95R38		159D		TL	60	DW13	66.4	15.4	196.7	29.9	9640	35	40
35400018	VF 480/80R42	18.4R42	162D		TL	66	DW16	72.8	19.3	216.1	32.5	10460	29	40
35450046	VF 320/90R46		160D		TL	56	DW10	68.7	12.4	208.3	31.9	9910	52	40
35400053	VF 320/105R46		172D		TL	59	DW11	72.4	12.8	219.8	33.5	13880	70	40
35400016	VF 380/90R46	14.9R46	173D		TL	61	DW13	73.0	15.4	220.3	33.9	14320	64	40
35400062	VF 480/80R46	18.4R46	164D		TL	66	DW16	76.7	19.3	228.6	34.5	11010	29	40
35400033	VF 520/85R46	20.8R46	170D		TL	67	DW18	80.8	20.9	236.7	36.1	13220	23	40
35400050	VF 340/85R48		164D		TL	56	DW12	71.2	13.5	216.1	33.1	11010	58	40
35400047	VF 320/105R50		158D		TL	59	DW11	76.3	12.7	229.8	35.2	8990	40	40
35400133	VF 320/90R50	12.4R50	166D		TL	56	W11	72.8	12.6	221.3	34.0	11700	64	40
35400023	VF 380/90R50		175D		TL	59	W13B	77.0	15.2	230.6	35.4	15200	64	40
35400090	VF 380/105R50		179D		TL	60	DW13	80.8	15.6	243.1	37.0	17070	64	40
35400180	VF 420/95R50		177D		TL	60	DW14	80.8	16.7	241.4	36.7	16090	52	40
35400021	VF 480/80R50	18.4R50	179D		TL	66	DW16	80.7	19.1	240.7	38.7	17100	52	40
35400027	VF 480/95R50		176D		TL	66	DW16	86.1	19.1	257.9	38.7	15640	35	40
35400006	IF 230/115R54		151D		TL	58	W8	76.7	10.1	233.5	35.9	7600	46	40
35400041	IF 270/105R54		158D		TL	58	W10	76.6	11.0	234.2	36.1	9360	58	40
35400036	VF 320/90R54	12.4R54	168D		TL	36	DW11	76.8	12.6	234.0	35.9	12350	64	40
35400056	VF 320/105R54		172D		TL	59	DW11	80.3	12.8	244.6	37.4	13880	64	40
35400029	VF 380/90R54		176D		TL	59	DW13	80.7	15.1	244.1	37.4	15640	64	40
35400205	IF 380/105R54		180D		TL	60	DW13	85.2	15.6	257.2	39.4	17620	75	40



AGRIFLEX+ 372 CFO STEEL BELTED R-1W

OEM FITMENT



The Alliance Agriflex+ 372 has state-of-the-art materials and steel-belted construction allowing our IF/VF radial tires to deliver outstanding performance. VF tires carry up to 40% more load at the same inflation pressure as conventional radials, or require 40% lower inflation pressure for the same load, reducing soil compaction. IF tires carry up to 20% more load at the same inflation pressure as conventional radials, or require 20% lower inflation pressure for the same load. Stronger carcass designed for cyclic service and intended for use on minimal torque applications such as combines, harvesters and grain carts (up to 1 mile). (TUBELESS - STEEL BELTED - STUBBLE GUARD)

PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
37250024	VF 520/80R26 CFO		168A8		TL	57	DW16L	57.7	19.9	1707.0	24.7	12330	41	25
37200080	VF 620/70R26		170D		TL	57	DW21B	58.5	24.6	172.7	25.4	13220	35	40
37250001	VF 750/65R26		177B		TL	71	DW25B	64.4	29.7	187.2	27.5	16080	35	40
37200008	VF 420/85R28 CFO		151D		TL	58	DW15	56.6	17.6	167.5	24.7	7600	23	40
37200048	VF 600/60R28		146D		TL	62	DW20B	61.4	24.6	163.7	26.8	14320	41	40
37200052	IF 600/65R28 CFO		160D		TL	57	DW21B	58.5	23.9	176.4	26.2	9900	35	40
37200096	VF 600/70R28 CFO		173D		TL	71	DW21B	61.4	24.6	179.9	26.8	14300	41	40
37200054	VF 600/60R30		147D		TL	63	DW20B	58.7	23.2	170.0	25.6	6770	15	40
37200105	VF 600/70R30 CFO		170D		TL	70	DW21B	63.0	24.6	187.8	28.0	13200	35	40
37200063	IF 620/75R30 CFO		164D		TL	73	DW23B	65.9	25.6	191.1	28.9	11020	23	40
37200126	VF 650/75R30 CFO		172D		TL	74	DW20B	67.7	26.0	194.6	28.9	13900	23	40
37250002	VF 710/55R30		165D		TL	63	DW25B	60.8	28.8	187.2	26.6	19270	23	40
37250003	VF 710/60R30		171D		TL	68	DW25B	63.6	28.0	186.8	27.4	13550	29	40
37200136	VF 800/65R32 CFO	30.5LR32	184D		TL	73	DW27B	72.6	30.5	213.2	31.7	19840	35	40
37200104	IF 800/70R32 CFO		182A8		TL	74	DW27B	76.1	30.9	224.6	33.7	18700	35	25
37200103	IF 900/60R32 CFO	35.LR32	193D		TL	73	DW30B	74.4	34.8	222.4	33.3	22000	46	40
37200150	IF 1250/50R32 CFO		201B		TL	76	DH44B	81.9	49.2	244.5	35.6	22480	46	30
37250004	VF 600/70R34		167D		TL	71	DW21B	67.1	24.6	196.1	26.5	19270	23	40
37200097	IF 650/65R34		161D		TL	73	DW23	67.7	25.6	198.1	30.3	10200	23	40
37250006	VF 710/60R34		173D		TL	68	DW25B	67.5	28.0	201.0	29.7	12787	23	40
37250032	VF 520/85R38		170D		TL	69	DW16L	72.8	20.9	215.9	31.8	13220	29	40
37250052	VF 600/65R38		163D		TL	57	DW21B	58.5	23.9	172.5	25.6	10740	29	40
37200130	VF 710/60R38		160D		TL	68	DW25B	71.5	28.0	209.2	31.6	9910	28	40
37200141	VF 710/70R38 CFO		178D		TL	77	DW25B	77.1	28.3	225.1	33.2	16540	23	40
37250093	VF 710/85R38		183D		TL	84	DW25B	85.2	28.7	249.2	36.7	19270	23	40
37200118	IF 800/70R38 CFO		187A8		TL	79	DW27	81.9	32.3	240.2	36.5	21500	41	25
37250121	VF800/70R38 CFO		190A8		TL	79	DW27B	82.1	32.3	243	25.9	21260	35	30
37250106	VF 900/60R38 CFO NRO		155D		TL	79	DW30B	80.1	35.0	234.8	34.5	21480	29	25
37200035	IF 520/85R42	20.8R42	169D		TL	70	DW16L	77.0	21.3	230.9	34.6	12780	35	40
37200036	VF 520/85R42 CFO		177A8		TL	69	DW16L	77.0	21.3	228.6	34.4	16100	41	25
37200044	VF 580/85R42		183D		TL	71	DW20B	80.3	23.4	238.3	35.8	19270	41	40
37200068	VF 620/70R42		172D		TL	68	DW21B	76.2	24.4	225.0	33.4	13880	23	40
37200133	VF 710/60R42		161D		TL	68	DW25B	75.7	28.0	224.0	33.5	10190	15	40
37200095	VF 710/70R42 CFO		185D		TL	79	DW25B	81.2	29.3	239.9	36.4	20390	35	40
37200180	VF 710/75R42 CFO		181D		TL	79	DW25B	84.8	28.5	247.2	37.0	18190	23	40



AGRI STAR II 470 - 485

OEM FITMENT

The Alliance Agri Star II radial features a two-layer lug—a single-angle layer stacked on top of a wider, multi-angle lug—for a footprint that evolves over the life of the tire, maximizing usable rubber on the ground. Dual step-tie bars anchor the tread, break up mud and minimize lug shuffling. The Agri Star II delivers the lowest cost per 32nd of tread in its category, and creates a 13% larger footprint than a typical, comparatively sized radial.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
47000047	240/70R16		104D		TL	38	W8	29.2	9.6	90.5	13.3	1477	23	40
47000037	260/70R16		109D		TL	39	W9	30.6	10.3	92.0	14.1	2270	35	40
47000003	280/70R16		112D		TL	40	W9	31.7	11.2	94.2	14.5	2469	35	40
47000000	280/70R18		114D		TL	40	W9	33.7	11.2	100.2	15.4	2601	35	40
47000033	280/70R20		116D		TL	40	W9	35.7	11.2	107.5	16.6	2756	35	40
47000027	300/70R20		120D		TL	43	W9	37.6	11.8	112.9	17.2	3086	35	40
47000039	320/70R20		123D		TL	44	W10	38.8	12.7	115.9	18.0	3410	35	40
48500022	320/85R20		119D		TL	54	W10	41.5	13.1	121.8	18.6	3000	23	40
47000035	360/70R20		129D		TL	53	W12	41.2	14.2	120.7	18.4	4079	35	40
47000008	380/70R20		122D		TL	57	W12	42.8	15.2	125.0	19.1	3307	23	40
48500020	280/85R24		115D		TL	53	W9	42.9	11.9	126.6	19.5	2680	23	40
47000034	320/70R24		116D		TL	52	W10	43.2	12.7	127.4	20.0	2756	23	40
48500025	320/85R24		122D		TL	54	W10	45.5	13.1	133.8	20.3	3305	23	40
48500101	320/85R24		142D		TL	54	W10	45.5	13.1	133.8	20.3	5840	67	40
48500035	340/85R24		125D		TL	57	W12	46.9	14.0	137.6	20.9	3640	23	40
47000026	360/70R24		122D		TL	53	W12	45.5	14.2	133.9	20.7	3300	23	40
47000001	380/70R24		125D		TL	57	W12	47.0	15.2	137.0	21.6	3630	23	40
48500047	380/85R24		131D		TL	58	W12	49.6	15.2	144.4	22.7	4300	23	40
47000005	420/70R24		130D		TL	59	W13	49.2	16.7	145.3	22.0	4190	23	40
48500165	420/85R24		137D		TL	63	W13	52.3	17.4	152.7	23.3	5070	23	40
47000013	480/70R24		138D		TL	64	DW16	52.1	19.0	151.9	23.1	5203	23	40
48500021	280/85R28		118D		TL	53	W9	46.9	11.9	138.3	21.2	2910	23	40
48500026	320/85R28		124D		TL	54	W10	49.5	13.1	142.1	22.2	3525	23	40
48500040	340/85R28		127D		TL	57	W12	50.9	14.0	150.9	22.8	3860	23	40
47000030	380/70R28		127D		TL	57	W12	51.0	15.2	149.4	23.4	3850	23	40
48500070	380/85R28		133D		TL	58	W12	53.5	15.2	157.6	23.8	4550	23	40
47000002	420/70R28		133D		TL	59	W13	53.3	16.7	149.4	24.4	4540	23	40
48500190	420/85R28		139D		TL	63	W13	56.3	17.4	164.9	24.8	5357	23	40
47000025	480/70R28		151D		TL	64	DW16	56.1	19.0	165.8	25.3	7606	45	40
47000029	480/70R28		140D		TL	64	DW16	56.1	19.0	165.8	25.3	5510	23	40
47000022	600/70R28		161D		TL	69	DW18	61.2	24.2	181.5	27.4	10196	40	40
48500071	380/85R30		135D		TL	58	W12	55.5	15.2	161.8	24.8	4806	23	40
47000009	420/70R30		134D		TL	59	W13	55.2	16.7	162.0	25.0	4674	23	40
48500200	420/85R30		140D		TL	63	W13	58.1	17.4	170.5	25.9	5510	23	40
48500140	460/85R30		145D		TL	67	DW16	60.8	18.9	178.3	26.9	6395	23	40
47000018	480/70R30		156D		TL	64	DW16	58.3	19.0	173.7	26.1	8818	55	40
47025030	480/70R30		150D		TL	64	DW16	58.3	19.0	173.7	26.1	7385	41	40
47000032	480/70R30		141D		TL	64	DW16	58.3	19.0	173.7	26.1	5670	23	40
47000007	600/70R30		152D		TL	69	DW18	63.2	24.2	185.4	27.8	7820	41	40
48500032	320/85R32		126D		TL	54	W10	53.5	13.1	157.9	24.6	3750	23	40
47000028	480/70R34		143D		TL	64	DW16	62.2	19.0	184.1	28.6	6010	23	40
47001541	480/70R34		155D		TL	64	DW16	62.2	19.0	183.7	28.6	8543	47	40
47025034	520/70R34		168D		TL	69	W16L	64.6	20.5	200.3	30.1	9645	46	40

CONTINUED ON NEXT PAGE

AGRI STAR II 470 - 485 (Continued)

PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
47000041	520/70R34		148D		TL	69	DW16	64.6	20.5	191.1	29.3	6945	23	40
48500103	320/85R34		133D		TL	53	W11	55.4	12.6	164.8	25.8	3858	23	40
48500037	380/85R34		137D		TL	58	W12	59.4	15.2	175.4	26.8	5070	23	40
48504730	420/85R34		147D		TL	63	W14	62.1	17.4	184.9	28.1	6780	35	40
48500100	420/85R34		142D		TL	63	W14	62.1	17.4	180.7	28.1	5840	23	40
48500145	460/85R34		147D		TL	67	DW16	64.8	18.9	190.7	28.9	6780	23	40
48500151	460/85R34		157D		TL	67	DW16	64.8	18.9	190.7	28.9	9095	44	40
48500033	320/85R36		128D		TL	54	W10	57.5	13.1	170.3	26.6	3970	23	40
48500044	340/85R36		132D		TL	57	W12	58.9	14.0	170.7	27.1	4410	23	40
48500031	320/85R38		143D		TL	54	W10	59.5	13.1	178.4	27.6	6010	52	40
48500046	340/85R38		133D		TL	57	W12	60.9	14.0	184.1	28.1	4540	23	40
48500048	340/85R38		151D		TL	57	W12	60.9	14.0	184.1	28.1	7605	64	40
48500120	380/80R38		142D		TL	58	W12	62.0	15.2	185.9	28.7	5840	35	40
48500121	380/80R38		152D		TL	58	W12	62.0	15.2	183.0	28.7	7825	58	40
48500130	420/85R38		144D		TL	63	W13	66.1	17.4	195.8	30.3	6175	23	40
48500160	460/85R38		149D		TL	67	DW16	68.8	18.9	202.8	30.8	7165	23	40
48500167	460/85R38		167D		TL	67	DW16	68.8	18.9	202.8	30.8	12015	64	40
47000038	480/70R38		145D		TL	64	DW16	66.2	19.0	195.9	30.6	6390	23	40
47000004	520/70R38		150D		TL	69	DW16	68.9	20.5	203.7	30.9	7380	23	40
48500300	520/85R38		155D		TL	69	DW16	72.8	20.5	215.6	32.7	8545	23	40
48500301	520/85R38		169D		TL	69	DW16	72.8	20.5	215.6	32.7	12785	52	40
47000011	580/70R38		180D		TL	71	DW18	71.9	22.8	214.0	32.7	17637	80	40
47000031	580/70R38		155D		TL	71	DW18	71.9	22.8	214.0	32.7	8540	23	40
47000024	580/70R38		170D		TL	71	DW18	71.9	22.8	214.0	32.7	13228	58	40
48500125	650/85R38		173D		TL	77	DW20	81.6	26.8	237.5	36.8	14330	35	40
47002588	710/70R38		178D		TL	77	DW25B	77.1	28.3	227.6	33.1	16535	49	40
47000040	710/70R38		172D		TL	77	DW25B	77.1	28.3	227.6	33.1	13880	35	40
48500325	480/80R42		156D		TL	68	DW16	72.0	19.4	213.1	33.1	7605	23	40
48500326	480/80R42		169D		TL	68	DW16	72.0	19.4	213.1	33.1	12785	64	40
48500110	520/85R42		157D		TL	69	DW16	76.9	20.5	227.4	35.0	9095	23	40
48500334	520/85R42		169D		TL	69	DW16	76.9	20.5	227.4	35.0	12785	52	40
48500104	420/80R46		159S		TL	64	W13	72.4	16.5	220.4	33.9	7165	29	40
47000006	710/70R42		173D		TL	77	DW25B	81.1	28.3	244.2	37.5	14320	35	40
48500260	480/80R46		158D		TL	68	DW16	77.2	19.4	231.2	35.8	9370	35	40
48500360	520/85R46		158D		TL	69	DW16	80.9	20.5	238.3	36.9	9370	23	40
48500264	480/80R50		159D		TL	68	DW16	81.1	19.4	241.1	37.7	9645	35	40

550 MULTI-USE STEEL BELTED

OEM FITMENT

The Alliance 550 provides exceptional traction whatever the terrain; snow, sand, hard surfaces and soft surface alike. Steel belts and a cut- and chip-resistant compound make this tire exceedingly puncture resistant.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
55000042	250/75R16		120G		TL	20	W8	30.7	10.0	92.2	14.2	3080	65	55
55000035	250/80R16		126A8/123D		TL	22	W8	32.0	10.6	97.2	14.7	3420	64	40
55000040	265/70R16.5	10R16.5	130A2		TL	29	8.25	30.4	10.5	92.3	13.7	4180	58	5
55000012	305/70R16.5	12R16.5	141/A2		TL	30	9.75	32.8	12.0	97.2	14.7	6130	58	5
55010470	340/80R18	12.5/80R18	143A8/138D		TL	31	DW11	39.4	13.5	118.2	17.7	6000	58	40
55010405	365/70R18		142A2/135B		TL	31	DW11	38.1	14.0	113.1	17.6	4940	54	30
55001480	400/70R18		147A8/144D		TL	33	W13	40.2	15.9	120.4	18.4	6150	58	40
55000055	405/70R18	16.0/70R18	153A2/141B		TL	33	W13	40.2	15.9	120.4	18.4	5670	54	30
55010535	340/80R20	12.5R20	144A8/140D		TL	31	DW11	41.4	13.5	124.1	18.9	5520	58	40
55001617	360/70R20		129A8/124D		TL	31	DW11	41.4	14.0	122.9	18.6	3520	35	40
55001620	360/80R20		147A8/143D		TL	34	DW11	43.0	14.1	128.5	19.3	6800	58	40
55001510	400/70R20		149B		TL	33	DW13	42.0	15.9	125.2	19.0	7150	58	30
55000060	405/70R20	16.0/70R20	149B		TL	33	DW13	42.4	15.9	126.2	19.1	7150	58	30
55001450	300/80R24		133A8/128D		TL	32	W9	43.0	11.6	127.5	19.8	3860	46	40
55001615	340/80R24		140A8/135D		TL	31	W11	45.4	13.5	135.4	20.8	4800	46	40
55001406	360/80R24	13.6R24	143A8/138D		TL	32	W11	46.6	14.1	139.6	21.3	5200	46	40
55001710	400/80R24	14.9R24	149A8/144D		TL	34	W13	49.2	15.9	145.8	22.0	6170	46	40
55002475	420/65R24		151A8/146D		TL	33	W13	45.6	16.1	137.4	20.7	6600	46	40
55002025	440/80R24	16.9R24	154A8/149D		TL	34	W13L	51.7	17.4	156.1	23.3	7150	46	40
55000025	460/65R24		156A8/151D		TL	34	W15L	47.6	17.9	141.6	21.5	7600	46	40
55000120	460/70R24	17.5LR24	159B		TL	34	W15L	49.2	18.4	149.0	22.4	9650	46	30
55002400	480/65R24		151A8/146D		TL	37	W15L	48.8	18.9	146.9	22.1	6600	46	40
55005410	500/70R24	19.5LR24	164B		TL	36	W16L	51.5	19.9	154.4	23.3	11000	46	30
55005330	540/65R24	21LR24	158A8/154D		TL	39	W18L	51.7	21.3	155.6	23.3	8250	46	40
55024950	480/80R26	18.4R26	160B		TL	34	W16L	56.1	19.0	168.0	25.4	9900	46	30
55002360	400/80R28	14.9R28	151A8/146D		TL	34	W13L	53.2	15.9	159.1	24.3	6600	46	40
55002610	440/80R28	16.9R28	156A8/151D		TL	34	W14L	55.8	17.3	166.9	25.2	7600	46	40
55002810	480/65R28		154A8/149D		TL	34	W15L	52.9	18.7	158.3	23.9	7150	46	40
55005390	540/65R28		160A8/155D		TL	39	W18L	55.6	21.7	168.0	25.6	8550	46	40
55002625	440/80R30		157A8/153D		TL	34	W14L	57.8	17.1	174.6	26.4	8050	46	40
55003015	480/80R30	18.4R30	162A8/157D		TL	35	W15L	60.3	18.5	181.7	27.4	9100	46	40
55005510	540/65R30		161A8/156D		TL	38	DW18A	57.6	21.7	176.4	26.7	8800	46	40
55005910	600/70R30		161A8/158D		TL	38	DW20A/B	63.1	24.1	188.7	28.6	9350	35	40
55002760	440/80R34	16.9R34	159A8/155D		TL	36	W14L	61.7	17.4	186.5	28.3	8550	45	40
55003310	480/80R34	18.4R34	164A8/159D		TL	34	W15L	64.3	18.9	192.6	29.1	8550	46	40
55005352	480/80R38	18.4R38	166A8/161D		TL	34	W15L	68.0	18.9	204.6	30.9	10200	46	40
55005810	540/80R38	20.8R38	172A8/167D		TL	38	DW18A	71.8	21.5	216.4	32.8	12000	46	40
55005860	600/65R38		170A8/166D		TL	38	DW18A	68.9	23.3	207.5	31.2	11700	46	40
55006700*	650/65R38		175A8/170D		TL	40	DW20A/B	71.4	25.4	214.6	32.2	13200	46	40
55006725	650/85R38		181A8/177D		TL	40	DW23B	81.4	26.5	245.3	35.9	18170	35	40
55007030	620/80R42		181A8/177D		TL	45	DW20A/B	80.9	25.4	242.9	37.3	16100	46	40
55007160	650/65R42		176A8/171D		TL	40	DW20A/B	75.3	25.4	227.0	34.3	13600	46	40
55007180	710/70R42		181A8/177D		TL	45	DW23A/B	80.8	28.2	243.6	37.0	16100	41	40
55006181	710/70R42 SG		181A8/177D		TL	45	DW23A/B	80.8	28.2	243.6	37	16100	41	40

AGRISTAR 378 XL R-1W

The Alliance Agristar 378 XL has a reinforced bead and sidewall to ensure high load capacity for today's high horsepower tractors and forage harvesters. (TUBELESS)



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
37800018	620/75R30		166D/168A8		TL	57		66.6	23.2	197.8	32.7	12800	46	25
37800498	710/55R30		153D/156A8		TL	63		59.7	26.7	176.0	26.3	8050	23	40
37800500	710/60R30		162D/165A8		TL	71		63.6	27.8	189.8	28.4	11400	35	25
37800010	600/70R34		160D/163A8		TL	64		67.1	24.0	198.2	30.3	10700	35	25
37800504	710/60R34		164D/167A8		TL	71		67.4	28.0	201.9	30.4	12000	35	25
37800400	650/75R38		169D/172A8		TL	69		76.0	26.4	225.6	34.3	13900	35	25
37801618	900/55R38		178D/181A8		TL	78		78.7	33.5	237.0	35.5	18200	35	25
37801200	710/75R42		175D/178A8		TL	79		84.3	28.7	252.3	38.0	16500	35	25
37801642	900/50R42		168D		TL	73		76.7	33.7	227.2	33.9	12330	23	40
37801640	900/60R42		180D		TL	80		84.3	35.0	250.6	37.4	17620	35	40

AGRISTAR 365 RADIAL R-1W

The Alliance Agristar 365 is a high-volume tire designed for high-horsepower tractors as well as flotation tires for high-clearance sprayers. (TUBELESS)

OEM FITMENT



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
36500022	420/65R20		135D		TL	45		41.5	16.5	122.4	20.2	4800	35	40
36500025	420/65R24		126A8		TL	50		45.5	16.5	134.4	22.8	3750	23	30
36516559	440/65R24		138A8/135D		TL	52		46.9	17.6	140.0	21.5	4300	35	25
36516565	480/65R24		140D		TL	55		48.7	19.0	144.5	21.9	5520	29	40
36517950	540/65R24		140D		TL	61		51.7	21.3	152.4	23.3	5520	23	40
36517951	540/65R24		146D		TL	61		51.7	21.3	152.4	23.3	6600	35	40
36516710	440/65R28		138D		TL	56		50.5	17.4	152.3	23.2	5200	35	40
36588012	540/65R28		152A8/149D		TL	60		55.9	20.9	164.7	25.2	6400	23	25
36518668	600/65R28		157A8/154D		TL	69		58.4	23.4	172.2	26.1	9900	35	25
36518652	VF 600/65R28		163D		TL	69		58.9	24.2	172.9	25.5	10700	29	40
36518400	540/65R30		153A8/150D		TL	63		58.3	21.7	172.2	26.3	8050	35	25
36550120	600/65R30		149D		TL	69		60.7	24.0	179.3	27.4	7160	23	40
36550122	600/65R30		158D		TL	69		60.7	24.0	179.3	27.4	9360	36	40
36518802	540/65R34		155A8/152D		TL	61		61.8	21.0	183.9	28.2	8550	35	25
36550168	600/65R34		160A8/157D		TL	69		64.9	23.7	190.8	29.1	8550	35	25
36518808	540/65R38		153D		TL	69		65.6	21.3	196.4	30.3	8040	35	40
36550246	600/65R38		162A8/159D		TL	69		68.8	23.4	203.5	31.3	10500	35	25
36581505	650/65R38		166D/169A8	0	TL	73		71.9	25.9	215.9	32.5	12780	36	25
36581508	650/65R38		171D		TL	73		71.9	25.9	215.9	32.5	13550	52	40
36550346	VF 650/65R38		173D	-	TL	73		71.9	26.0	215.9	32.5	15210	29	40
36580338	710/70R38		168A8/166D		TL	76		76.9	28.6	225.6	34.5	11700	43	25
36580475	710/70R38		174A8/171D		TL	76		76.9	28.6	225.6	34.5	14800	43	25
36581510	650/65R42		173A8/170D		TL	73		76.6	25.9	226.7	34.7	14300	46	25
36561373	VF 650/65R42 NRO		174D		TL	73		76.6	25.9	225.1	33.7	14770	29	40
36580810	710/70R42		173A8/173B		TL	76		80.9	29.1	243.2	36.9	14320	35	25
36580455	710/70R42		180A8/177D		TL	76		80.9	29.1	243.2	36.9	17600	46	25

360 SUPER POWER DRIVE RADIAL R-1+

OEM FITMENT

The Alliance 360 is designed for great traction and flotation on harvesting equipment. The broad tread face and multi-angle tread bar provides a large footprint for maximum flotation and minimal compaction and rutting. (TUBELESS)



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
36016205	480/65-24		140A8/140B		TL	58	W15	49.2	18.5	147.2	22.9	5510	35	25
36086018	480/65R24		136A8/133D		TL	58	W15	48.6	18.9	143.0	21.9	6950	46	25
36050185	620/75R26	23.1R26	167A8/167B		TL	59	DW20B	62.6	24.6	184.4	28.2	12000	46	25
36017501	750/65R26	28LR26	158A8/155B		TL	71	DW25A	63.9	29.6	188.1	28.7	9350	17	25
36087507	750/65R26	28LR26	166A8/163B		TL	71	DW25A	63.9	29.6	189.6	28.5	11670	35	25
36017698	750/65R26	28LR26	173A8/170B		TL	71	DW25A	63.9	29.6	188.1	28.7	14300	44	25
36017702	750/65R26	28LR26	166A8/163B		TL	71	DW25A	63.9	29.6	188.1	28.7	11700	35	25
36018125	480/65-28	FORESTRY	142A8		TL	58	W15	52.6	18.9	155.5	23.8	6950	46	25
36018124	540/65-28	FORESTRY			TL	63	W16L	57.0	20.5	170.5	26.3	8480	48	25
36018031	600/65R28	FORESTRY	157A8/154D		TL	59	DW18L	58.3	23.3	172.8	25.8	9100	35	25
36018062	600/65-28	FORESTRY	154A8		TL	59	W18L	58.3	23.3	172.8	25.8	6950	46	25
36019040	540/65-30	FORESTRY	150A8		TL	63	W16L	58.5	22.0	171.2	26.1	6950	46	25
36035012	540/70-30	FORESTRY	152A8		TL	63	W16L	59.1	20.5	177.6	27.3	7820	35	25
36020025	650/75R32	24.5R32	172A8/172B		TL	63	DW21A	70.9	24.6	207.2	31.5	13900	46	25
36020105	650/75R32	24.5R32	159A8/156B		TL	63	DW21A	70.9	24.5	207.2	31.5	9650	23	25
36020948	650/75R32	24.5R32	172D		TL	63	DW21A	70.9	24.6	212.7	31.5	13880	46	40
36033008	30.5LR32		178A8/175B		TL	62	DH27	71.7	30.5	209.4	31.9	16500	45	25
36035001	800/65R32		181A8/178B		TL	63	DH27	72.8	31.5	215.9	32.5	18200	52	25
36084855	540/65R38		150A8/147D		TL	63	W16L	65.9	21.7	196.3	30.2	7400	25	25
36050028	650/65R38		171D		TL	60	DW20A	72.2	25.4	213.5	32.7	13600	51	40
36080045	710/70R38		181A8/178D		TL	69	DW25B	76.7	28.2	225.9	34.5	18200	54	25
36061582	620/70R42		166A8/163B		TL	66	DW20A	76.4	25.6	226.5	34.8	11700	28	25
36061747	620/70R42		173A8/170B		TL	66	DW20A	76.4	25.6	226.5	34.8	14300	39	25
36021056	650/65R42		165A8		TL	64	DW20A	76.4	25.6	226.5	34.8	6950	46	25



350 ROW CROP - NARROW RADIAL R-1

OEM FITMENT

The Alliance 350 is the market-leading high-clearance tire designed for all types of cultivation, harvesting, and spraying jobs. The strong casing and rigid belts coupled with radial construction provide unbeatable performance. (TUBELESS)



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
35000802	230/95R24	9.5R24	107A8/104B		TL	44	W8	41.2	9.0	120.0	18.9	1980	52	30
35049001	230/95R28		109A8		TL	28	W8	61.0	9.5	187.8	28.7	2270	23	25
35000971	230/95R28	9.5R28	109A*/106B	**	TL	44	W8	45.1	9.0	130.0	20.7	2090	52	30
35050008	8.3R32	210/95R32	116D		TL	41	W7	46.9	8.3	140.8	21.8	2760	52	40
35052001	230/95R32	9.5R32	131A8/128D		TL	43	W8	49.0	9.5	149.4	22.8	3960	52	40
35050001	270/95R32	11.2R32	135A8/132D		TL	35	W10	51.2	11.2	153.3	23.7	4400	52	40
35068010	320/85R34		141A8		TL	55	W10A	13.0	55.4	166.9	25.7	5670	52	25
35050016	210/95R36	8.3R36	118D		TL	41	W7	50.8	8.3	155.6	24.4	2910	52	40
35050007	230/95R36	9.5R36	133A8/130D		TL	43	W8	53.0	9.5	159.1	24.6	4180	52	40
35050002	270/95R36	11.2R36	139A8/136D		TL	40	W10	55.5	11.2	170.4	25.7	4940	52	40
35050003	270/95R38	11.2R38	140A8/137D		TL	43	W10	57.3	11.2	172.8	26.8	5080	52	40
35013260	230/95R40	9.5R40	132A8/119D		TL	44	W8	57.5	9.5	173.9	27.0	4400	52	40
35050108	230/95R42	9.5R42	133D		TL	43	W7	59.3	9.5	178.6	28.0	4540	59	40
35013806	270/95R42	11.2R42	142A8/139D		TL	46	W10	61.6	11.2	190.2	28.7	5360	52	40
35017003	8.3R44	210/95R44	129A8/126D		TL	41	W7	58.9	8.3	178.9	27.9	3740	52	40
35050010	230/95R44	9.5R44	137A8/134D		TL	47	W8	61.0	9.5	184.9	28.7	4680	52	40
35025009	270/95R44	11.2R44	145A8/142D		TL	49	W10	63.2	11.2	190.8	29.6	5840	58	40
35055252	270/95R46	11.2R46	144A8/141D		TL	45	W10	65.6	11.2	197.0	30.5	5680	52	40
35050020	320/90R46	12.4R46	151A8/148D		TL	47	W11	67.1	12.4	205.7	31.4	6800	52	40
35047530	340/85R46		161A2/150D		TL	56	W12	68.7	13.4	211.5	32.2	7400	52	40
35047520	380/90R46	14.9R46	145A8/142D		TL	51	W13A	71.8	14.9	218.9	33.1	5360	30	30
35075100	380/90R46	14.9R46	162A8/159D		TL	51	W13A	71.8	14.9	218.9	33.1	9650	58	40
35047977	380/90R46	14.9R46	175A8/172D		TL	51	W13A	71.8	14.9	218.9	33.1	13900	84	40
35047536	380/105R46		158D		TL	51	W13A	76.8	15.5	231.6	35.4	9350	44	40
35050030	230/95R48	9.5R48	136D		TL	44	W8	65.0	9.5	198.4	30.7	4940	52	40
35050031	270/95R48	11.2R48	145A8/142D		TL	49	W9	67.3	11.2	205.6	31.6	5840	52	40
35050032	13.6R48		154A8/151D		TL	49	W12	71.1	13.6	219.2	33.1	7600	51	40
35067249	13.6R48		167A2/156D		TL	50	W12	71.1	13.6	219.2	33.6	8800	70	40
35075050	320/90R50	12.4R50	153A8/150D		TL	52	W10A	73.5	12.8	222.0	33.1	7400	52	40
35075250	380/90R50	14.9R50	154A8/151D		TL	59	W12A	76.8	15.1	232.1	35.9	7600	52	40
35075255	380/90R50	14.9R50	161A8/158D		TL	59	W12A	76.8	15.1	232.1	36.0	9350	52	40
35075180	380/105R50		179A2/168D		TL	59	W12A	80.7	15.9	244.6	37.6	12300	64	40
35067073	300/95R52	12.4R52	159A2/148D		TL	48	W10	74.4	12.2	226.2	35.2	6950	52	40
35067085	300/95R52	12.4R52	167A2/156D		TL	48	W10	74.4	12.2	226.2	35.2	8800	70	40
35075011	270/95R54	11.2R54	157A2/146D		TL	46	W10A	74.2	10.8	229.4	34.6	6600	52	40
35075080	270/95R54	11.2R54	167A2/156D		TL	46	W10A	74.8	11.2	229.4	35.6	8800	87	40
35076134	320/90R54	12.4R54	162A2/151D		TL	58	W10A	77.1	12.8	233.3	36.5	7606	52	40
35075251	380/90R54	14.9R54	155A8/152D		TL	59	W12A	80.9	15.3	243.0	37.4	7826	35	40
35047682	380/90R54	14.9R54	174A8/171D		TL	59	W12A	80.9	15.3	243.9	38.1	13600	52	40

FARMPRO II 846/842 RADIAL R-1W

OEM FITMENT

The Alliance FarmPRO is a modern R-1W designed to be used in a wide array of farm applications, providing up to 25% improvement in fuel economy over standard bias R-1. Versatile multi-angle lug design provides long wear, smooth roading and excellent self cleaning. (TUBELESS)



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
84200010	280/85R20	11.2R20	112A8/109B		TL	48	W10	38.7	11.3	114.7	17.6	2270	23	30
84200022	320/85R20	12.4R20	119A8/116B		TL	50	W11	41.1	13.0	121.8	18.0	2760	23	30
84600014	250/85R24		109A8/B		TL	45	W8	40.8	9.7	121.8	18.7	2270	23	30
84600020	280/85R24	11.2R24	115A8/B		TL	48	W10	42.8	10.7	126.6	19.4	2680	23	30
84600025	320/85R24	12.4R24	122A8/B		TL	51	W10	45.2	13.2	133.8	20.3	3300	23	30
84600101	320/85R24		142A8/142B		TL	51	W10	45.2	13.2	133.8	20.3	5840	67	25
84600035	340/85R24	13.6R24	125A8/B		TL	52	W11	46.5	14.0	137.6	20.9	3640	23	30
84600047	380/85R24	14.9R24	131A8/B		TL	54	W12	49.3	15.2	145.9	21.9	4300	23	30
84600165	420/85R24	16.9R24	137A8/B		TL	57	W14L	51.8	16.5	152.7	23.3	5080	23	30
84601880	380/85R26		127A8/127B		TL	57	W12	50.8	15.0	149.6	23.4	3850	23	25
84600002	420/85R26		135A8/135B		TL	60	W14L	53.9	16.9	160.3	24.6	4800	23	25
84601935	460/85R26		140A8 /140B		TL	64	W15L	56.1	18.3	166.2	25.1	5510	23	25
84600028	250/85R28		112A8/B		TL	46	W8	44.8	9.8	130.9	20.7	2470	23	30
84600021	280/85R28	11.2R28	118A8/B		TL	48	W9	46.7	11.0	138.3	21.2	2910	23	30
84600026	320/85R28	12.4R28	124A8/B		TL	51	W11	49.1	12.8	145.2	22.2	3520	23	30
84600040	340/85R28	13.6R28	127A8/B		TL	51	W11	51.0	14.1	150.9	22.8	3860	23	30
84600070	380/85R28	14.9R28	133A8/B		TL	54	W12	53.2	15.0	157.6	23.8	4540	23	30
84600190	420/85R28	16.9R28	139A8/B		TL	57	W14L	55.9	16.5	164.9	24.8	5360	23	30
84600180	380/85R30	14.9R30	135A8/B		TL	57	W12	55.2	15.0	162.8	24.8	4800	23	30
84600200	420/85R30	16.9R30	140A8/B		TL	57	W14L	57.8	17.0	170.5	25.9	5520	23	30
84600525	420/90R30		147A8/B		TL	59	W13	59.8	16.5	176.3	26.9	5840	23	30
84600140	460/85R30	18.4R30	145A8/B		TL	61	W15L	60.2	18.7	178.3	26.9	6400	23	30
84600032	320/85R32	12.4R32	126A8/B		TL	50	W11	53.4	12.8	158.1	24.6	3740	23	30
84600031	320/85R34		133A8/133B		TL	52	W11	55.4	12.8	165.7	25.6	4540	35	25
84600080	380/85R34	14.9R34	137A8/B		TL	57	W12	59.4	15.0	175.4	26.8	5080	23	30
84600100	420/85R34	16.9R34	142A8/B		TL	57	W15L	62.0	16.5	182.9	28.1	5840	23	30
84600145	460/85R34	18.4R34	147A8/B		TL	57	W16L	64.4	18.9	190.7	28.9	6800	23	30
84600151	460/85R34	18.4R34	157A8/B		TL	57	W16L	64.4	18.9	190.7	28.9	9100	52	30
84600033	320/85R36	12.4R36	128A8/B		TL	50	W11	57.4	12.8	169.9	26.6	39360	23	30
84600045	340/85R36	13.6R36	132A8/B		TL	52	W12	58.9	13.6	174.2	27.1	4400	23	30
84600046	340/85R38	13.6R38	133A8/B		TL	52	W12	60.7	13.6	179.8	28.1	4540	23	30
84600120	380/80R38	14.9R38	142A8/B		TL	57	W12	62.1	14.8	185.9	28.7	5840	35	30
84200121	380/80R38	14.9R38	152A8/B		TL	57	W12	62.1	14.8	185.9	28.7	7850	58	30
84600001	400/75R38		134A8/134B		TL	60	W12	61.8	15.7	186.1	28.8	4670	24	25
84600130	420/85R38	16.9R38	144A8/B		TL	57	W15L	66.1	16.4	195.8	30.3	6150	23	30
84600160	460/85R38	18.4R38	149A8/B		TL	61	W16L	68.5	17.9	202.8	30.8	7150	23	30
84600166	460/85R38	18.4R38	153A8/B		TL	61	W16L	68.5	17.9	202.8	30.8	8050	35	30
84600167	460/85R38		167A8/167B		TL	61	W16L	68.5	17.9	202.8	30.8	12240	64	25
84600300	520/85R38	20.8R38	155A8/B		TL	67	W16A	72.8	20.7	218.3	32.7	8550	23	30
84600301	520/85R38	20.8R38	169A8/B		TL	66	W16A	72.8	20.7	218.3	32.7	12800	52	30
84200038	320/80R42		141A8/B		TL	51	W10	62.2	12.6	184.1	29.1	5680	46	30
84200028	320/90R42		147A8/B		TL	51	W10	64.7	12.6	194.5	30.1	6800	52	30
84600322	480/80R42	18.4R42	151A8/B		TL	66	W16A	72.2	18.9	213.1	33.1	7600	23	30
84600326	480/80R42	18.4R42	169A8/B		TL	64	W16A	72.2	18.9	213.1	33.1	12800	64	30
84600325	520/85R42	20.8R42	157A8/B		TL	68	W16A	76.8	20.3	227.4	35.0	9100	23	30
84600334	520/85R42	20.8R42	169A8/B		TL	68	W16L	76.8	20.3	227.4	35.0	12785	50	30
84200029	320/90R46	12.4R46	148A8		TL	51	W10	68.7	12.6	207.0	32.1	6950	52	30
84200310	380/90R46	14.9R46	165A8/B		TL	59	W13A	73.3	15.0	217.1	33.8	11400	70	30
84600260	480/80R46	18.4R46	158A8/B		TL	64	W16A	77.2	18.9	227.6	35.0	9350	23	30
84600360	520/85R46	20.8R46	158A8/B		TL	68	W16A	80.8	20.3	238.6	36.9	9350	23	30

FARMPRO 845 70 RADIAL R-1W

OEM FITMENT

The Alliance FarmPRO 70 is a modern R-1W design used in a wide variety of farm applications and up to 25% improvement in fuel economy over standard bias R-1. Versatile multi-angle lug design provides long wear, smooth roading and excellent self cleaning. (TUBELESS)



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
84501048	280/70R20		116A8/113B		TL	42	W10	35.9	10.9	106.5	16.3	2540	23	30
84501055	300/70R20		120A8/117B		TL	42	W10	37.6	11.5	111.5	17.1	2830	35	30
84501060	320/70R20		123A8/120B		TL	42	W10	38.8	12.8	114.5	17.5	3080	35	30
84501300	320/70R24		116A8/113B		TL	51	W10	43.1	12.6	127.1	19.6	2540	23	30
84501320	360/70R24		122A8/119B		TL	52	W11	45.2	14.1	133.3	20.6	3000	23	30
84501340	380/70R24		125A8/122B		TL	53	W12	46.9	15.0	138.2	21.2	3300	23	30
84501360	420/70R24		130A8/127B		TL	54	W13	49.1	16.5	144.9	22.1	3860	23	30
84501470	480/70R24		138A8/B		TL	58	W15L	51.8	18.9	151.9	23.3	5200	23	30
84501400	320/70R28		119A8/116B		TL	51	W10	46.9	12.6	138.4	21.5	2760	23	30
84501420	360/70R28		125A8/122B		TL	52	W11	48.8	14.1	144.0	22.5	3300	23	30
84501450	380/70R28		127A8/124B		TL	53	W12	50.9	15.0	150.2	23.2	3520	23	30
84501462	420/70R28		133A8/129B		TL	54	W13	53.1	16.5	156.7	24.1	4080	23	30
84501480	480/70R28		140A8/137B		TL	58	W15L	55.7	18.9	164.3	25.2	5080	23	30
84501505	420/70R30		134A8/131B		TL	54	W13	55.0	16.5	162.4	25.0	4300	23	30
84501535	480/70R30		141A8/138B		TL	58	W15L	58.2	18.9	171.7	26.3	5200	23	30
84501537	480/70R30		150A8/144E		TL	58	W15L	58.2	18.9	171.7	26.3	7400	41	25
84501550	520/70R30		145A8/B		TL	59	W16L	64.6	20.3	190.5	29.3	6950	23	30
84502571	600/70R30		152A8/B		TL	58	DW20B	63.1	24.1	184.2	28.1	7820	24	30
84501541	480/70R34		155A8/155B	0	TL	59	W15L	62.2	18.9	190.4	28.6	8540	46	25
84501580	520/70R34		148A8/B		TL	59	W16L	64.6	20.3	190.5	29.3	6950	23	30
84502500	480/70R38		145A8/B		TL	58	W15L	66.2	18.9	195.2	30.3	6400	23	30
84502525	520/70R38		150A8/B		TL	59	W16L	69.1	20.3	203.8	31.4	7400	23	30
84502560	580/70R38		155A8/B		TL	62	W18A	72.2	22.7	213.1	32.6	8550	23	30
84502586	710/70R38		172A8/B		TL	74	DW23B	77.1	28.2	227.1	34.6	13900	23	30
84502597	710/70R42		173A8/B		TL	74	DW23B	81.1	28.2	239.4	36.9	14300	23	30

MULTISTAR 374 RICE & CANE R-2

The Alliance Multistar 374 is a R-2 deep lug radial tire, designed to deliver very high traction in rice and cane fields. The stepped lug design helps in increasing the grip and reducing tractor slip. Special tread compound ensures resistance to cut growth.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
37400010	420/90R30	16.9R30	142A8		TL	96	W15L	60.2	16.9	148.3	27	5840	23	30
37400014	620/75R30		151A8		TL	112	W18	68.5	23.6	193.8	31.4	7600	20	25
37400011	460/85R30		145A8		TL	101	W16	62.5	18.3	179.9	28.9	6390	23	25
37400030	480/70R34		155A8		TL	101	W15	63.2	18.9	184.3	29.1	8550	46	30
37400012	340/85R38		125A8		TL	87	W11	62.2	13.8	181.3	29.5	4410	23	25
37400110	520/85R42	20.8R42	165A8		TL	105	W16A	78.1	20.3	228.3	24.2	1985	41	30
37400013	340/85R46		122A8		TL	87	W11	70.1	13.8	206.2	32.9	5510	29	25
37400080	480/80R46	18.4R46	158A8		TL	101	DW16L	78	18.6	226.8	35.8	9360	35	30
37400120	520/85R46	20.8R46	158A8		TL	105	W16L	80.7	20.3	234.7	37.2	2050	23	30
37400090	480/80R50	18.4R50	159A8		TL	101	W16L	81.3	18.9	239.6	37.8	9640	35	30

THE ALL-IN-ONE STEEL-BELTED RADIAL GREAT PERFORMANCE ON BOTH HARD AND SOFT SURFACES

Meet the Alliance 550 Multi-Use – our uniquely-treaded radial R-4 tire that is just as durable on hard surfaces as it is effective in soft conditions, snow, sand and more. Whether it's for mowing, utility work, plowing snow, pulling a trailer or general tractor use, the Alliance Multi-Use 550 was designed to deliver exceptional performance and reliability for construction, municipal and agricultural operators day in and day out.



TREAD

Steel radial belts reduce punctures in the field and provide a larger, more even footprint

SIDEWALL

Special compound improves wear and performance in all operating conditions

CENTER OF TREAD

“S” design block provides a smoother ride on hard surfaces and at high speeds

BEAD AREA

Strong bead construction allows for stability and performance on hillsides

FOOTPRINT

More rubber on the ground backed by strong steel belts create a larger footprint and minimizes soil compaction

THE FOOTPRINT ADVANTAGE

IT'S LARGER

- Increased footprint improves flotation on soft terrains and minimizes soil compaction
- Bigger footprint with stronger sidewall construction enables increased stability on hillsides and slopes
- Unique tread design offers a larger footprint which increases tire life and results in more evenly distributed tread wear

IT'S RECTANGULAR

- Steel belts provide a more rectangular flat footprint to disperse load equally across the tread face
- Unique tread design offers less vibration and noise while traveling at high speeds on hard surfaces
- Radial construction means longer tread life, better traction, higher productivity and less soil compaction

ALLIANCE MULTIUSE 550



COMPETITOR A



VISIT YOKOHAMA-OHT.COM FOR DETAILED LOAD AND PRESSURE TABLES

Distributor:

Yokohama Off-Highway Tires (YOHT) is a division of The Yokohama Rubber Co., specializing in Agriculture, Forestry, Construction, Industrial, Material Handling, Earthmoving, Mining, Port and other commercial tires. YOHT sells its diverse product range, consisting of over 4,000 SKUs, in over 120 countries through its subsidiaries and channel partners. YOHT products are engineered to be application-specific and purpose-built. For more information visit www.yokohama-oht.com or email us at info@yokohama-oht.com.



Contact Yokohama Off-Highway Tires America, Inc. at (800) 343-3276 or (339) 900-8080 for your nearest Yokohama OHT Tire Dealer.

facebook.com/yokohamaohta

[@yokohamaohta](https://twitter.com/yokohamaohta)

yohta-blog.yokohama-oht.com

yokohama-oht.com