

TURF & COMPACT TRACTOR FAMILY
OPTIMIZED
PERFORMANCE
WITH MINIMUM
SURFACE DAMAGE



GALAXY
APPLICATION SPECIFIC, PURPOSE BUILT.

GALAXY GARDEN PRO XTD

CUSTOM BUILT FOR

ALL-PURPOSE

UTILITY TRACTORS

The “XTD” designation in the Galaxy Garden Pro line’s size expansion stands for “extra tread depth,” getting right to the heart of one of the big benefits of the new compact tractor tire line extension. In addition to added tread depth, the Galaxy Garden Pro XTD sizes feature a new, high-density compound and refinements in the innovative block tread pattern to combine the best aspects of lug-style R-1 and R-4 designs with the block design of R-3 tires. XTD sizes are highlighted in the Garden Pro spec chart to the right.

ROUNDED SHOULDERS-SHALLOW LUG



- Offers superior turf protection with excellent self-cleaning properties

DIRECTIONAL BLOCK TREAD DESIGN



- Provides more void between the lugs leading to high traction and self-cleaning properties
- Excellent roadability with low rate of wear on hard surfaces
- Deeper tread for better traction and longer tire life

RADIAL CONSTRUCTION



- Uses lower air pressures than a bias tire thus producing a larger footprint and lower ground pressure
- Low rolling resistance results in better fuel economy



GALAXY GARDEN PRO

OEM FITMENT

The Galaxy Garden Pro is a mixed-service radial tire developed specifically for small tractors used in gardening, orchards, and vineyards. The Garden Pro is also designed to be used on hard surfaces for transporting produce and materials. Highlighted items below are our Garden Pro XTD offerings.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
517275	215/45R10	18X8.50R10	80	TL	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
579750	220/55R12		82A8	TL	16	7	21.7	8.7	64.5	9.9	1050	35	25
517286	315/55R12	26X12.00R12	85B	TL	22	10.5	25.3	12.1	73.5	11.4	1130	15	25
579751	240/60R12	23X9.50-12	89A8	TL	14	8	23.3	9.4	69.4	10.6	1280	35	25
579743	220/55R14	23X8.50-14	93A8	TL	16	7JA	23.3	8.7	69.5	10.2	1430	55	25
517100	215/65R14	25X8.50R14	90B	TL	22	7	24.9	8.5	73.4	11.4	1320	30	25
517099	215/70R15	27X8.50R15	90B	TL	22	7	27.0	8.5	78.9	12.5	1320	26	25
579748	200/60R15		83A8	TL	14	6	24	7.8	72	11.2	1230	43	30
579689	200/65R16		94A8	TL	25	W6	26.2	7.8	77.5	12.1	1480	35	25
579746	200/70R16		94A8	TL	25	W6	27	7.8	79.9	13	1477	35	25
579745	240/70R16		104A8	TL	28	W8	29.1	9.6	86.2	13.6	1984	35	25
579754	260/70R16		109A8	TL	29	W8	30.3	10.2	90.4	13.8	2270	35	25
579755	280/70R16		112A8	TL	30	W9	31.5	11.1	93.9	14.3	2470	35	25
517101	265/70R16.5	10R16.5	105B	TL	34	8.25	31.1	10.4	92.4	14.0	2040	29	25
517298	305/70R16.5	12R16.5	105B	TL	34	9.75	33.0	12.5	95.5	14.8	2040	23	25
517316	355/65R17.5	14R17.5	130B	TL	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
579688	320/65R18		109A8	TL	31	W10	34.4	12.2	101.4	15.3	2270	23	25
579808	260/70R18		114A8/B	TL	32	W8	32.3	10.2	96.9	15.1	2600	41	30
517304	385/65R19.5	15R19.5	130B	TL	32	11.75	39.0	15.5	115.0	17.6	4190	35	25
579758	300/70R20		110A8	TL	31	W9	37.6	11.6	112.2	17.1	2340	23	25
579757	320/70R20		113A8	TL	32	W10	38.7	12.9	115.2	17.6	2540	23	25
579807	380/70R20		122A8/B	TL	32	W12	42.6	15	127.4	19.7	3300	23	30
517256	400/70R20	43X16.00R20	130B	TL	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
579726	125/90R22		98A8	TL	20	W4	30.9	5	94.5	14.7	1650	52	25
579779	360/70R24	12.4R24	122A8	TL	32	W11	45.4	14.2	135.4	21.1	3300	23	25
579760	380/70R24	13.6R24	125A8	TL	34	W12	46.9	15	139.6	21.3	3640	23	25
579781	420/70R24	14.9R24	130A8	TL	35	W13	49.1	16.5	146.4	22.2	4180	23	25
517913	420/85R24	16.9R24	130	TL	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
517912	460/70R24	17.5LR24	139B	TL	38	W15L	49.4	18.3	145.0	22.0	5350	29	25
517911	500/70R24	19.5LR24	140B	TL	38	W16L	51.6	19.8	147.9	21.4	6120	23	25
579770	320/85R28	12.4R28	124A8	TL	30	W10	49.3	12.9	147.2	22.1	3520	23	25
579771	340/85R28	13.6R28	127A8	TL	32	W10	50.7	13.5	151	23.9	3850	23	30
579783	360/70R28	12.4R28	125A8	TL	33	W11	49.3	14.1	148.3	22.6	3640	23	25
579786	480/70R28	16.9R28	140A8/B	TL	32	W15	55.9	18.9	165.7	24.9	5510	23	30
579788	480/70R30	16.9R30	141A8/B	TL	37	W15	58.2	18.9	174	26.3	5670	23	30
579790	480/80R34	16.9R34	143A8/B	TL	37	W15	62.2	18.9	185.6	28.5	4190	35	25

* All sizes marked TBA will be updated on final tire release. Go to yokohama-oh.com for the most recent tire specifications.

GALAXY TURF SPECIAL

MAXIMUM PERFORMANCE.

MAXIMUM TURF PROTECTION.

GALAXY TURF SPECIAL R-3

OEM FITMENT

The Galaxy Turf Special was designed to leave less of a mark on the greens than a standard directional tread. We incorporated the feedback of golf course superintendents from a variety of geographical locations to develop the most sought after golf, turf and sand tires in the industry. Today, the Galaxy Turf Special has set the standard for flotation and minimized surface disturbance.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	PLY/*	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
480089	24X13LL-12		4		TL	7	10.5	23.6	12.1	68.6	10.5	1230	10	
480150	25X10.50LL-15		6		TL	10	8	25.3	10.3	75.8	11.6	1020	10	
480151	27X10.50LL-15		6		TL	8	8	26.7	10.6	81	12.4	965	58	
480158	27X12LL-15		6	114A3	TL	10	10	26.7	12.2	79.7	12.2	1150	8	
551337	27X14LL-15		6		TL	10	12	27.1	14.1	79.7	12.2	1150	6	
480232	12LL-16		6		TL	8	10	32.8	11.5	99	15	1360	6	
480250	22.5LL-16.1		6		TL	12	18	44.6	21.7	125	19.5	3740	6	
480243	33X16LL-16.1		10		TL	9	14	32.8	16.5	99	15	5080	38	
480247	33X18LL-16.1		10		TL	9	16	33.3	18.6	100	15.2	5520	34	
480246	41X18LL-16.1		6		TL	12	16	41.8	19.1	118	18.3	2680	6	
480373	41X18LL-22.5		14		TL	15	14	41.8	19.9	116.3	17.8	9100	50	
480362	41X18LL-22.5		20		TL	12	14	40.6	19	120	18.7	11350	70	

DESIGN



- Geometric block tread ensures optimal weight distribution.
- Lateral tread design provides steering stability, improved lateral traction, and great self cleaning.

CONSTRUCTION



- The elongated lug at the shoulder wraps the tread around the sidewall and reduces the damage caused while turning on turf.

COMPOUND



Special Compound

- Wear-resistant compound ensures long tire life even when intermittently used on hard surfaces.

GALAXY MIGHTY MOW-TS

The Galaxy Mighty Mow is engineered to provide superior flotation resulting in a turf friendly tire that will not damage grass or roots. The Mighty Mow works exceptionally well on equipment for lawns, parks, golf courses, playing fields, and cemeteries.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	TYPE	TREAD DEPTH	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
485040	16X6.50-8		4	TL	9	5.4	16.1	6.5	47.4	7.1	617	28	9
485043	16X7.50-8		4	TL	9	5.4	16.1	7.1	47.7	7.1	675	24	9
485035	18X8.50-8		4	TL	9	7	18.3	8.3	53	8.1	827	22	9
485048	18x9.50-8		6	TL	9	8	18.3	8.8	53.4	8	1294	36	9
485073	20X10-8		4	TL	9	8	20	10.4	59.3	9	545	22	9
485047	18X8.50-10		4	TL	9	7	17.5	8.5	51.9	7.9	827	22	9
485057	18X10.50-10		4	TL	10	8.5	17.7	10.2	51.9	7.9	994	20	9
485074	20X10-10		6	TL	10	8	20.1	9.8	58.3	9.1	1433	32	9
485081	23x8.50-12		6	TL	11	7	23	8.6	67.3	10.2	1433	34	9
485075	23x10.50-12		6	TL	12	8.5	22.6	10.2	65.9	9.8	1764	32	10
485076	24X12-12		4	TL	12	8.5	23.8	11.4	70.6	10.4	1709	20	9
485087	26X12-12		4	TL	12	10.5	25.2	11.8	73	11	1764	20	9
485088	26X12-12		8	TL	12	10.5	25.2	11.8	73	11	1764	20	9

GALAXY MIGHTY MOW R-3

OEM FITMENT

The Galaxy Mighty Mow is engineered to provide superior flotation resulting in a turf friendly tire that will not damage grass or roots. The Mighty Mow works exceptionally well on equipment for lawns, parks, golf courses, playing fields, and cemeteries.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
135848	23X8.50-12		4	TL	11	7	22.6	8.6	62.3	10.2	1477	35	6
135045	23X8.50-14		6	TL	13	7	23.2	8.1	70	10.7	1430	33	15
135141	27X8.50-15		6	TL	13	7	26.8	8.4	79	12.3	2090	45	20
135135	27X8.50-15		12	TL	13	7	27	8.7	81.3	12.4	2469	45	6
135138	27X10.50-15		4	TL	13	8	27.3	10.2	82	12.7	1475	30	20
135845	29X12.50-15		4	TL	13	10LB	29.2	12.2	86	13.4	1320	20	25
135223	9.5-16		6	TL	19	W8	32.3	9.5	91	14.1	1390	30	25
135245	12.4-16		6	TL	21	W10L	36.3	12.4	108	16.4	1820	24	5
135249	21.5L-16.1SL		6	TL	30	W18	44.5	21.5	125	19.4	4409	16	30
135259	10-16.5		8	TL	18	8.25	30.7	10.4	93	14.2	3500	45	5
135262	12-16.5		4	TL	18	9.75	32.9	12.5	97	15	3220	25	5
135266	12-16.5		12	TL	17	9.75	32.8	12.5	99	15	4189	40	5
135274	14-17.5		6	TL	21	10.5	35.9	13.3	105	16.1	8550	30	5
135278	14-17.5NHS		14	TL	21	10.5	35.9	13.3	105	16.1	4806	29	6
135343	41X14.00-20		4	TL	24	11	41.9	13.8	126	19.1	4080	25	20
135875	44X18.00-20		4	TL	25	14	44.6	18	130	20.2	3525	20	25
135433	17.5L-24		8	TL	25	W15L	47.4	17.6	146	22.2	5360	26	25
135439	19.5L24		12	TL	26	W17	51.7	19.5	155	23.5	5203	29	25

GALAXY SUPER SOFT R-3

OEM FITMENT

The Galaxy Super Soft R-3 tires are ideal for pull-type scrapers, fertilizer and lime spreaders, rough mowing tractors, balers, swathers and air seeders. Over the years, these tires have continually been improved, strengthened, and enhanced to provide the very best performance for various agricultural and industrial machines.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
513251	22.5L-16.1		10	TL	32	W18	47.1	22.1	130	20.5	5271	22	10
526252	22.5L-16.1		14	TL	32	W18	47.1	22.1	133	20.5	8685	34	10

GALAXY R-3 (329)

The Galaxy 329 has a diamond tread pattern and is built with a strong nylon construction. The wide and extended tread protects the sidewalls against cuts and snags. Special cut and chip resistant compounds and heat resistant compounds provide a long tire life.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
574425	14.9-24		8	TL	25	W13	49.7	15.2	147.1	22.3	5080	30	25

GALAXY SUPER TRENCHER HF-3/ I-3

OEM FITMENT

The Galaxy Super Trencher was designed with super sidewall and rim shield protection, and works well on trenchers and many other types of machinery.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
160088	26X12-12		8	TL	24	11	25.9	12.4	77	11.7	2998	44	5
160163	29X1250-15		8	TL	21	10.5	29.6	12.5	89	13.5	3420	45	5
160174	31X1550-15		8	TL	25	W13	32.1	15.9	94	14.3	4540	40	5
160351	38X18-20		12	TL	42	14	39.3	18.1	117	17.7	7600	65	5

GALAXY STUBBLE PROOF IMP R-3

OEM FITMENT

The Galaxy Stubble Proof IMP is stubble proof due to its unique design and severe-duty compound. The IMP R-3 also has Galaxy's unique reinforced under-tread which gives it additional penetration protection.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
548171	31X1350-15		12	TL	14	10LB	30.6	13.9	92	13.9	3520	75	30

GALAXY STUBBLE PROOF HIGHWAY

OEM FITMENT

The Galaxy Stubble Proof Highway has designed a tire for heavy wagons that need stubble protection in the fields. The Galaxy Stubble Proof Highway has our unique reinforced under-tread and special tread compound to give it excellent penetration protection.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
550052	20.5x8.0-10SL		8	TL	14	7	20.6	8	62.1	9.4	1323	70	50
550269	12.5L-16.5		14	TL	16	9.75	33.2	12.2	90.4	13.7	4800	90	45
549851	32X1550-16.5		14	TL	16	12	32.9	16	89.7	13.6	5840	90	45

GALAXY AGRI-AIR SEEDER R-3

OEM FITMENT

The Galaxy Agri-Air Seeder is stubble proof due to its unique design and severe-duty compound. It also has Galaxy's unique reinforced under-tread which gives it additional penetration protection.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
142271	33X1550-16.5		10	TL	17	12	32.8	15.2	99	15	4940	60	30

GALAXY MULTI-TOUGH

The Galaxy Multi-Tough works well in hard surface applications and job sites. Radial construction gives this tire a longer footprint for excellent traction, a smooth ride on and off the road and superior service hours.



PRODUCT CODE	SIZE	ALT. SIZE	PR/LI	TYPE	NSD (32NDS)	PREFERRED RIM	OD	WIDTH	RC	SLR	MAX LOAD (LBS)	PSI	MAX SPEED
209211	340/80R18	12.5/80R18	136A8	TL	30	W11	39.4	13.5	115	17.7	4940	46	25
209853	405/70R18		146A8/B	TL	23	W13	40.4	16.2	121.6	18.2	6610	64	30
209854	405/70R20		152A2/143B	TL	23	W13	42.4	16	128.5	19.3	6010	54	30
209855	405/70R24		146A8/B	TL	35	W13	46.4	16	139.8	21.4	6610	54	30
209214	440/80R24	16.9R24	154A8	TL	34	DW14L	51.7	17.7	155.7	23.2	8250	46	25
209215	500/70R24	19.5LR24	157A8	TL	43	DW16L	51.6	19.8	150	23	9100	46	25
209901	480/80R26	18.4R26	160A8	TL	34	DW15L	56.2	18.9	169.1	25.2	9900	46	25
209216	440/80R28	16.9R28	156A8	TL	43	DW14L	55.7	17.4	164	25.2	8800	46	25



THE LAST TIRE YOU'LL BUY FOR YOUR MOWER

GALAXY

MIGHTY MOW

We worked with golf course superintendents and landscape professionals to develop the Mighty Mow and Mighty Mow TS. So it's no surprise that they're the choice of top pros and leading original equipment manufacturers.

It's all in the design and quality. Flotation designed for turf and sensitive areas. Wrapped shoulders to prevent ruts. Block tread patterns that balance traction and turf protection—while always cleaning themselves out efficiently. And wear-resistant rubber compounds that will last and last...backed by the Yokohama Off-Highway Tires aggressive warranty.

In fact, the Galaxy Mighty Mow or Mighty Mow TS may well be the last tire you'll ever buy for your compact tractor or mower.



VISIT YOKOHAMA-OHT.COM FOR DETAILED LOAD AND PRESSURE TABLES

Distributor:


Yokohama Off-Highway Tires (YOHT) is a division of The Yokohama Rubber Co., specializing in Agriculture, Forestry, Construction, Industrial, Material Handling, Earthmoving, Mining, Port and other commercial tires. YOHT sells its diverse product range, consisting of over 4,000 SKUs, in over 120 countries through its subsidiaries and channel partners. YOHT products are engineered to be application-specific and purpose-built. For more information visit www.yokohama-oht.com or email us at info@yokohama-oht.com.



Contact Yokohama Off-Highway Tires America, Inc. at (800) 343-3276 or (339) 900-8080 for your nearest Yokohama OHT Tire Dealer.

 facebook.com/yokohamaohta

 [@yokohamaohta](https://twitter.com/yokohamaohta)

 yohta-blog.yokohama-oht.com

 yokohama-oht.com